| CANNON PART ID | CHAINSAW, HARVESTER, OR REPAIR DISCOUNT CATEGORY | DESCRIPTION 1 | DESCRIPTION 2 |
|---|---|---|---|
| CBT-CS-325-M | CHAINSAW | CANNON REPLACEMENT SPROCKET NOSE for CSM in 0.325 Pitch | 3 Rivets, 10 Teeth, for use on saws less than 60cc displacement |
| CBT-CS-370-LM | CHAINSAW | CANNON REPLACEMENT SPROCKET NOSE for CCM and CSM in 0.370 (Low Profile) Pitch | 3 Rivets, 9 Teeth, for use on saws less than 60cc displacement |
| CBT-CS-325-S | CHAINSAW | CANNON REPLACEMENT SPROCKET NOSE for CCB, CRS, CCE and CSB in 0.325 Pitch | 1 Rivet, 12 Teeth |
| CBT-CS-375-S | CHAINSAW | CANNON REPLACEMENT SPROCKET NOSE for CCB, CRS, CCE and CSB in 0.375 Pitch | 1 Rivet, 11 Teeth |
| CBT-CS-375-S-E | CHAINSAW | CANNON REPLACEMENT INTERNAL/EMBEDDED SPROCKET for CFB-P4 in 0.375 Pitch | 6 Rivets, 11 Teeth |
| CBT-CS-404-S | CHAINSAW | CANNON REPLACEMENT SPROCKET NOSE for CCB, CRS, CCE and CSB in 0.404 Pitch | 1 Rivet, 10 Teeth |
| CBT-CS-375-W | CHAINSAW | CANNON REPLACEMENT SPROCKET NOSE for CBV and CJB in 0.375 Pitch | Stihl Part # 3003 650 2539, 3 Rivets, 13 Teeth |
| CBT-CS-404-W | CHAINSAW | CANNON REPLACEMENT SPROCKET NOSE for CBV and CJB in 0.404 Pitch | Stihl Part # 3003 650 2538, 3 Rivets, 12 Teeth |
| CBT-CS-HN-S | CHAINSAW | CANNON REPLACEMENT HARD NOSE for CCB, CRS, and CSB in .325, .375, .404 Pitch | 1 Rivet |
| CBT-HV-404-S-LM1 | CHAINSAW | CANNON REPLACEMENT SPROCKET NOSE for CDE (Lucas Mill) in 0.404 Pitch | 5 Rivets, 11 Teeth |
| CBT-RN-63-28 | CHAINSAW | CANNON REPLACEMENT ROLLER NOSE for CCP and CPR in 0.325, 0.375, 0.404 Pitch | 3 Rivets, 2.8" Diameter |
| CBT-HV-404-S | HARVESTER | CANNON REPLACEMENT SPROCKET NOSE for CBB, CDE (Peterson Mill), and CHA in 0.404 Pitch | 5 Rivets, 11 Teeth |
| CBT-HV-63-404-E | HARVESTER | CANNON REPLACEMENT INTERNAL/EMBEDDED SPROCKET for .063 Gauge, 0.404 Pitch | 6 Rivets, 11 Teeth |
| CBT-HV-750-S | HARVESTER | CANNON REPLACEMENT SPROCKET NOSE for CHV in 0.750 Pitch | 5 Rivets, 9 Teeth |
| CBT-HV-80-404-E | HARVESTER | CANNON REPLACEMENT INTERNAL/EMBEDDED SPROCKET for .080 Gauge, 0.404 Pitch | 6 Rivets, 11 Teeth |
| CBT-RV-CCP | CHAINSAW | CANNON REPLACEMENT RIVETS for CBT-RN-63-28 | |
| CBT-RV-CSB-232 | CHAINSAW | CANNON REPLACEMENT RIVETS for CBT-CS-325-S, CBT-CS-375-S, and CBT-CS-404-S | .232" Long Rivet for .185" Thickness Tip |
| CBT-RV-CSM-214 | CHAINSAW | CANNON REPLACEMENT RIVETS for CBT-CS-325-M and CBT-CS-370-LM | .214" Long Rivet for .169" Thickness Tip |
| CBT-RV-CHA | HARVESTER | CANNON REPLACEMENT RIVETS for CBT-HV-404-S | |
| CBT-RV-CHE | HARVESTER | CANNON REPLACEMENT RIVETS for CBT-HV-63-404-E and CBT-HV-80-404-E | |
| CBT-RV-CHV | HARVESTER | CANNON REPLACEMENT RIVETS for CBT-HV-750-S | |
| CBW-20020 | CHAINSAW | CANNON CHAINSAW BAR ADAPTOR PLATE, S1 (12.10 mm) TO H1 (9.00 mm), 38 mm Centre to Centre Studs | |
| CBW-20030 | CHAINSAW | CANNON CHAINSAW BAR ADAPTOR PLATE, S1 (12.10 mm) TO H1 (9.00 mm), 44 mm Centre to Centre Studs | |
| CBW-20035 | CHAINSAW | CANNON MILLING BAR ADAPTOR PLATE, G1 (14.00 mm) TO H1 (9.00 mm) 44 mm Centre to Centre Studs | |
| CBW-20040 | CHAINSAW | CANNON CHAINSAW BAR ADAPTOR PLATE, S1 (12.10 mm) TO C1 (8.00 mm), 36 mm Centre to Centre Studs | |
| CBW-20050 | CHAINSAW | CANNON CHAINSAW BAR ADAPTOR PLATE, S1 (12.10 mm) TO P4 (8.00 mm), 40 mm Centre to Centre Studs | |
| CBW-20055 | CHAINSAW | CANNON MILLING BAR ADAPTOR PLATE, G1 (14.00 mm) TO P4 (8.00 mm), 40 mm Centre to Centre Studs | |
| CBW-20060 | CHAINSAW | CANNON CHAINSAW BAR ADAPTOR PLATE, S1 (12.10 mm) TO H1 (9.00 mm), 30 mm Centre to Centre Studs | |
| CBW-20080 | CHAINSAW | CANNON MILLING BAR ADAPTOR PLATE, G1 (14.00 mm) TO S1 (12.10 mm), 35 mm Centre to Centre Studs | |
| CBW-20090 | CHAINSAW | CANNON CHAINSAW BAR ADAPTOR PLATE, S1 (12.10 mm) TO H1 (9.00 mm), 46 mm Centre to Centre Studs | |
| CBW-20095 | CHAINSAW | CANNON MILLING BAR ADAPTOR PLATE, G1 (14.00 mm) TO H1 (9.00 mm), 46 mm Centre to Centre Studs | |
| CBW-30000 | CHAINSAW | CANNON OUTSIDE BAR MOUNT PAD, for C1 Mount Bars Used on Small Saws with 8.2mm Studs | |
| CBW-87575 | CHAINSAW | CANNON MILLING BAR ADAPTOR BUSHING, S2 TO H1, 14.0mm to 9.0mm | |
| CBW-87577 | CHAINSAW | CANNON MILLING BAR ADAPTOR BUSHING, S2 TO S1, 14.0mm to 12.1mm | |
| CBW-HH-971 | CHAINSAW | SUPERBAR HELPER HANDLE, WITHOUT ROLLER | Granberg Part # G971 |
| CBW-HH-975 | CHAINSAW | MILLING BAR HELPER HANDLE, WITH ROLLER | Granberg Part # G975 |
| CBW-OK-801 | CHAINSAW | MILLING BAR AUXILIARY OILER KIT | Granberg Part # G801A |
| CBW-0967F | CHAINSAW | MILLING BAR OIL INJECTOR | Granberg Part # 0967F |
| CBW-0687F | CHAINSAW | MILLING BAR OIL INJECTOR JAM NUT (5/16-24 #5) | Granberg Part # 0687F |
| CBV-B1-27-63-H | CHAINSAW | CANNON BEAVER FIREWOOD PROCESSING BAR, B1 Mount, 27 Inches, .063 Gauge, 0.375 or .404 Pitch, Check Owners Manual for Drive Links | Cobalt Hard Nose Tip |
| CBV-B1-27-63-3 | CHAINSAW | CANNON BEAVER FIREWOOD PROCESSING BAR, B1 Mount, 27 Inches, .063 Gauge, 0.375 Pitch, Check Owners Manual for Drive Links | |
| CBV-B1-27-63-4 | CHAINSAW | CANNON BEAVER FIREWOOD PROCESSING BAR, B1 Mount, 27 Inches, .063 Gauge, 0.404 Pitch, Check Owners Manual for Drive Links | |
| CBB-B1-27-80-4 | CHAINSAW | CANNON BEAVER FIREWOOD PROCESSING BAR, B1 Mount, 27 Inches, .080 Gauge, 0.404 Pitch, Check Owners Manual for Drive Links | |
| CBV-B1-33-63-4 | CHAINSAW | CANNON BEAVER FIREWOOD PROCESSING BAR, B1 Mount, 33 Inches, .063 Gauge, 0.404 Pitch, Check Owners Manual for Drive Links | |
| CBB-B2-29-80-4 | CHAINSAW | CANNON BUILTRITE FIREWOOD PROCESSING BAR, B2 Mount, 29 Inches, .080 Gauge, 0.404 Pitch, Check Owners Manual for Drive Links | |
| CKF-SP-16-58-2 | CHAINSAW | CANNON KOSKELO FIREWOOD PROCESSING BAR, SP Mount, 16 Inches, .058 Gauge, 0.325 Pitch, Check Owners Manual for Drive Links | |
| CJB-U1-24-63-3 | CHAINSAW | CANNON CARPENTRY BAR, PANEL SAW, U1 Mount, 24 Inches, .063 Gauge, 0.375 Pitch, Check Owners Manual for Drive Links | |
| CJB-U1-24-63-4 | CHAINSAW | CANNON CARPENTRY BAR, PANEL SAW, U1 Mount, 24 Inches, .063 Gauge, 0.404 Pitch, Check Owners Manual for Drive Links | |
| CJB-U2-24-63-3 | CHAINSAW | CANNON CARPENTRY BAR, PANEL SAW, U2 Mount, 24 Inches, .063 Gauge, 0.375 Pitch, Check Owners Manual for Drive Links | |
| CJB-U2-24-63-4 | CHAINSAW | CANNON CARPENTRY BAR, PANEL SAW, U2 Mount, 24 Inches, .063 Gauge, 0.404 Pitch, Check Owners Manual for Drive Links | |
| CJB-U3-21-63-3 | CHAINSAW | CANNON CARPENTRY BAR, PANEL SAW, U3 Mount, 21 Inches, .063 Gauge, 0.375 Pitch, Check Owners Manual for Drive Links | |
| CJB-U3-21-63-4 | CHAINSAW | CANNON CARPENTRY BAR, PANEL SAW, U3 Mount, 21 Inches, .063 Gauge, 0.404 Pitch, Check Owners Manual for Drive Links | |
| CCB-H1-20-50-2 | CHAINSAW | CANNON CARPENTRY SUPERBAR, PARALLEL RAILS, H1 Mount, 20 Inches, .050 Gauge, 0.325 Pitch, 81 Drive Links | 3.6" Width Cut |
| CCB-H1-20-50-3 | CHAINSAW | CANNON CARPENTRY SUPERBAR, PARALLEL RAILS, H1 Mount, 20 Inches, .050 Gauge, 0.375 Pitch, 72 Drive Links | 3.6" Width Cut |
| CCB-H1-24-50-2 | CHAINSAW | CANNON CARPENTRY SUPERBAR, PARALLEL RAILS, H1 Mount, 24 Inches, .050 Gauge, 0.325 Pitch | 3.6" Width Cut |
| CCB-H1-24-50-3 | CHAINSAW | CANNON CARPENTRY SUPERBAR, PARALLEL RAILS, H1 Mount, 24 Inches, .050 Gauge, 0.375 Pitch | 3.6" Width Cut |
| CCB-H1-28-50-2 | CHAINSAW | CANNON CARPENTRY SUPERBAR, PARALLEL RAILS, H1 Mount, 28 Inches, .050 Gauge, 0.325 Pitch | 3.6" Width Cut |
| CCB-H1-28-50-3 | CHAINSAW | CANNON CARPENTRY SUPERBAR, PARALLEL RAILS, H1 Mount, 28 Inches, .050 Gauge, 0.375 Pitch | 3.6" Width Cut |
| CCB-S1-20-50-2 | CHAINSAW | CANNON CARPENTRY SUPERBAR, PARALLEL RAILS, S1 Mount, 20 Inches, .050 Gauge, 0.325 Pitch, 81 Drive Links | 3.6" Width Cut |
| CCB-S1-20-50-3 | CHAINSAW | CANNON CARPENTRY SUPERBAR, PARALLEL RAILS, S1 Mount, 20 Inches, .050 Gauge, 0.375 Pitch, 72 Drive Links | 3.6" Width Cut |
| CCB-S1-24-50-2 | CHAINSAW | CANNON CARPENTRY SUPERBAR, PARALLEL RAILS, S1 Mount, 24 Inches, .050 Gauge, 0.325 Pitch | 3.6" Width Cut |
| CCB-S1-24-50-3 | CHAINSAW | CANNON CARPENTRY SUPERBAR, PARALLEL RAILS, S1 Mount, 24 Inches, .050 Gauge, 0.375 Pitch | 3.6" Width Cut |
| CCB-S1-28-50-2 | CHAINSAW | CANNON CARPENTRY SUPERBAR, PARALLEL RAILS, S1 Mount, 28 Inches, .050 Gauge, 0.325 Pitch | 3.6" Width Cut |
| CCB-S1-28-50-3 | CHAINSAW | CANNON CARPENTRY SUPERBAR, PARALLEL RAILS, S1 Mount, 28 Inches, .050 Gauge, 0.375 Pitch | 3.6" Width Cut |
| CCM-C1-20-50-3LM | CHAINSAW | CANNON CARPENTRY SUPERMINI BAR, PARALLEL RAILS, C1 Mount, 20 Inches, .050 Gauge, 0.370 Pitch (Low Profile) | 3" Width Cut |
| CCM-C1-24-50-3LM | CHAINSAW | CANNON CARPENTRY SUPERMINI BAR, PARALLEL RAILS, C1 Mount, 24 Inches, .050 Gauge, 0.370 Pitch (Low Profile) | 3" Width Cut |
| CCA-C1-11-43 | CHAINSAW | CANNON CARVING BAR, ARBOR TIP, C1 Mount, 11 Inches, .043 Gauge (0.250 Pitch = 66 Drive Links, 0.325 Pitch = 51 Drive Links, 0.375/0.370 Pitch (Low Profile)= 45 Drive Links) | |
| CCA-C1-11-50 | CHAINSAW | CANNON CARVING BAR, ARBOR TIP, C1 Mount, 11 Inches, .050 Gauge (0.250 Pitch = 66 Drive Links, 0.325 Pitch = 51 Drive Links, 0.375/0.370 Pitch (Low Profile)= 45 Drive Links) | |
| CCA-C1-14-50 | CHAINSAW | CANNON CARVING BAR, ARBOR TIP, C1 Mount, 14 Inches, .050 Gauge (0.250 Pitch = 78 Drive Links, 0.325 Pitch = 62 Drive Links, 0.375/0.370 Pitch (Low Profile)= 55 Drive Links) | |
| CCA-C1-16-50 | CHAINSAW | CANNON CARVING BAR, ARBOR TIP, C1 Mount, 16 Inches, .050 Gauge (0.250 Pitch = 86 Drive Links, 0.325 Pitch = 68 Drive Links, 0.375/0.370 Pitch (Low Profile)= 60 Drive Links) | |
| CCA-C1-18-50 | CHAINSAW | CANNON CARVING BAR, ARBOR TIP, C1 Mount, 18 Inches, .050 Gauge (0.250 Pitch = 93 Drive Links, 0.325 Pitch = 72 Drive Links, 0.375/0.370 Pitch (Low Profile)= 64 Drive Links) | |
| CCA-H1-16-50 | CHAINSAW | CANNON CARVING BAR, ARBOR TIP, H1 Mount, 16 Inches, .050 Gauge (0.250 Pitch = 86 Drive Links, 0.325 Pitch = 68 Drive Links, 0.375/0.370 Pitch (Low Profile)= 60 Drive Links) | |
| CCA-H1-18-50 | CHAINSAW | CANNON CARVING BAR, ARBOR TIP, H1 Mount, 18 Inches, .050 Gauge (0.250 Pitch = 93 Drive Links, 0.325 Pitch = 72 Drive Links, 0.375/0.370 Pitch (Low Profile)= 64 Drive Links) | |
| CCA-H1-20-50 | CHAINSAW | CANNON CARVING BAR, ARBOR TIP, H1 Mount, 20 Inches, .050 Gauge (0.250 Pitch = 103 Drive Links, 0.325 Pitch = 80 Drive Links, 0.375/0.370 Pitch (Low Profile)= 71 Drive Links) | |
| CCA-S1-16-50 | CHAINSAW | CANNON CARVING BAR, ARBOR TIP, S1 Mount, 16 Inches, .050 Gauge (0.250 Pitch = 86 Drive Links, 0.325 Pitch = 68 Drive Links, 0.375/0.370 Pitch (Low Profile)= 60 Drive Links) | |
| CCA-S1-18-50 | CHAINSAW | CANNON CARVING BAR, ARBOR TIP, S1 Mount, 18 Inches, .050 Gauge (0.250 Pitch = 93 Drive Links, 0.325 Pitch = 72 Drive Links, 0.375/0.370 Pitch (Low Profile)= 64 Drive Links) | |
| CCA-S1-20-50 | CHAINSAW | CANNON CARVING BAR, ARBOR TIP, S1 Mount, 20 Inches, .050 Gauge (0.250 Pitch = 103 Drive Links, 0.325 Pitch = 80 Drive Links, 0.375/0.370 Pitch (Low Profile)= 71 Drive Links) | |
| CCD-C1-10-43 | CHAINSAW | CANNON CARVING BAR, DIME TIP, C1 Mount, 10 Inches, .043 Gauge, 0.250 Pitch, 56 Drive Links | For use on saws less than 40cc displacement |
| CCD-C1-10-50 | CHAINSAW | CANNON CARVING BAR, DIME TIP, C1 Mount, 10 Inches, .050 Gauge, 0.250 Pitch, 56 Drive Links | |
| CCD-C1-12-43 | CHAINSAW | CANNON CARVING BAR, DIME TIP, C1 Mount, 12 Inches, .043 Gauge, 0.250 Pitch, 64 Drive Links | For use on saws less than 40cc displacement |
| CCD-C1-12-50 | CHAINSAW | CANNON CARVING BAR, DIME TIP, C1 Mount, 12 Inches, .050 Gauge, 0.250 Pitch, 64 Drive Links | |
| CCD-C1-14-43 | CHAINSAW | CANNON CARVING BAR, DIME TIP, C1 Mount, 14 Inches, .043 Gauge, 0.250 Pitch, 77 Drive Links | For use on saws less than 40cc displacement |
| CCD-C1-14-50 | CHAINSAW | CANNON CARVING BAR, DIME TIP, C1 Mount, 14 Inches, .050 Gauge, 0.250 Pitch, 77 Drive Links | |
| CCD-C1-16-43 | CHAINSAW | CANNON CARVING BAR, DIME TIP, C1 Mount, 16 Inches, .043 Gauge, 0.250 Pitch, 85 Drive Links | For use on saws less than 40cc displacement |
| CCD-C1-16-50 | CHAINSAW | CANNON CARVING BAR, DIME TIP, C1 Mount, 16 Inches, .050 Gauge, 0.250 Pitch, 85 Drive Links | |
| CCD-C1-8-43 | CHAINSAW | CANNON CARVING BAR, DIME TIP, C1 Mount, 8 Inches, .043 Gauge, 0.250 Pitch, 48 Drive Links | For use on saws less than 40cc displacement |
| CCD-C1-8-50 | CHAINSAW | CANNON CARVING BAR, DIME TIP, C1 Mount, 8 Inches, .050 Gauge, 0.250 Pitch, 48 Drive Links | |
| CCQ-C1-11-43 | CHAINSAW | CANNON CARVING BAR, QUARTER TIP, C1 Mount, 11 Inches, .043 Gauge (0.250 Pitch = 60 Drive Links, 0.325 Pitch = 48 Drive Links) | For use on saws less than 40cc displacement |
| CCQ-C1-11-50 | CHAINSAW | CANNON CARVING BAR, QUARTER TIP, C1 Mount, 11 Inches, .050 Gauge (0.250 Pitch = 60 Drive Links, 0.325 Pitch = 48 Drive Links) | |
| CCQ-C1-12-43 | CHAINSAW | CANNON CARVING BAR, QUARTER TIP, C1 Mount, 12 Inches, .043 Gauge (0.250 Pitch = 64 Drive Links, 0.325 Pitch = 50 Drive Links) | For use on saws less than 40cc displacement |
| CCQ-C1-12-50 | CHAINSAW | CANNON CARVING BAR, QUARTER TIP, C1 Mount, 12 Inches, .050 Gauge (0.250 Pitch = 64 Drive Links, 0.325 Pitch = 50 Drive Links) | |
| CCQ-C1-14-43 | CHAINSAW | CANNON CARVING BAR, QUARTER TIP, C1 Mount, 14 Inches, .043 Gauge (0.250 Pitch = 78 Drive Links, 0.325 Pitch = 61 Drive Links) | For use on saws less than 40cc displacement |
| CCQ-C1-14-50 | CHAINSAW | CANNON CARVING BAR, QUARTER TIP, C1 Mount, 14 Inches, .050 Gauge (0.250 Pitch = 78 Drive Links, 0.325 Pitch = 61 Drive Links) | |
| CCQ-C1-16-43 | CHAINSAW | CANNON CARVING BAR, QUARTER TIP, C1 Mount, 16 Inches, .043 Gauge (0.250 Pitch = 86 Drive Links, 0.325 Pitch = 67 Drive Links) | For use on saws less than 40cc displacement |
| CCQ-C1-16-50 | CHAINSAW | CANNON CARVING BAR, QUARTER TIP, C1 Mount, 16 Inches, .050 Gauge (0.250 Pitch = 86 Drive Links, 0.325 Pitch = 67 Drive Links) | |
| CCQ-C1-20-43 | CHAINSAW | CANNON CARVING BAR, QUARTER TIP, C1 Mount, 20 Inches, .043 Gauge (0.250 Pitch = 102 Drive Links, 0.325 Pitch = 80 Drive Links) | For use on saws less than 40cc displacement |
| CCQ-C1-20-50 | CHAINSAW | CANNON CARVING BAR, QUARTER TIP, C1 Mount, 20 Inches, .050 Gauge (0.250 Pitch = 102 Drive Links, 0.325 Pitch = 80 Drive Links) | |
| CCQ-C1-8-43 | CHAINSAW | CANNON CARVING BAR, QUARTER TIP, C1 Mount, 8 Inches, .043 Gauge (0.250 Pitch = 48 Drive Links, 0.325 Pitch = 38 Drive Links) | For use on saws less than 40cc displacement |
| CCQ-C1-8-50 | CHAINSAW | CANNON CARVING BAR, QUARTER TIP, C1 Mount, 8 Inches, .050 Gauge (0.250 Pitch = 48 Drive Links, 0.325 Pitch = 38 Drive Links) | |
| CCQ-H1-14-43 | CHAINSAW | CANNON CARVING BAR, QUARTER TIP, H1 Mount, 14 Inches, .043 Gauge (0.250 Pitch = 76 Drive Links, 0.325 Pitch = 61 Drive Links) | For use on saws less than 40cc displacement |
| CCQ-H1-14-50 | CHAINSAW | CANNON CARVING BAR, QUARTER TIP, H1 Mount, 14 Inches, .050 Gauge (0.250 Pitch = 76 Drive Links, 0.325 Pitch = 61 Drive Links) | |
| CCQ-H1-16-43 | CHAINSAW | CANNON CARVING BAR, QUARTER TIP, H1 Mount, 16 Inches, .043 Gauge (0.250 Pitch = 86 Drive Links, 0.325 Pitch = 67 Drive Links) | For use on saws less than 40cc displacement |
| CCQ-H1-16-50 | CHAINSAW | CANNON CARVING BAR, QUARTER TIP, H1 Mount, 16 Inches, .050 Gauge (0.250 Pitch = 86 Drive Links, 0.325 Pitch = 67 Drive Links) | |
| CCQ-H1-20-43 | CHAINSAW | CANNON CARVING BAR, QUARTER TIP, H1 Mount, 20 Inches, .043 Gauge (0.250 Pitch = 101 Drive Links, 0.325 Pitch = 79 Drive Links) | For use on saws less than 40cc displacement |
| CCQ-H1-20-50 | CHAINSAW | CANNON CARVING BAR, QUARTER TIP, H1 Mount, 20 Inches, .050 Gauge (0.250 Pitch = 101 Drive Links, 0.325 Pitch = 79 Drive Links) | |
| CCQ-H1-24-43 | CHAINSAW | CANNON CARVING BAR, QUARTER TIP, H1 Mount, 24 Inches, .043 Gauge (0.250 Pitch = 116 Drive Links, 0.325 Pitch = 92 Drive Links) | For use on saws less than 40cc displacement |
| CCQ-H1-24-50 | CHAINSAW | CANNON CARVING BAR, QUARTER TIP, H1 Mount, 24 Inches, .050 Gauge (0.250 Pitch = 116 Drive Links, 0.325 Pitch = 92 Drive Links) | |
| CCQ-S1-12-43 | CHAINSAW | CANNON CARVING BAR, QUARTER TIP, S1 Mount, 12 Inches, .043 Gauge (0.250 Pitch = 64 Drive Links, 0.325 Pitch = 50 Drive Links) | For use on saws less than 40cc displacement |
| CCQ-S1-12-50 | CHAINSAW | CANNON CARVING BAR, QUARTER TIP, S1 Mount, 12 Inches, .050 Gauge (0.250 Pitch = 64 Drive Links, 0.325 Pitch = 50 Drive Links) | |
| CCQ-S1-14-43 | CHAINSAW | CANNON CARVING BAR, QUARTER TIP, S1 Mount, 14 Inches, .043 Gauge (0.250 Pitch = 76 Drive Links, 0.325 Pitch = 61 Drive Links) | For use on saws less than 40cc displacement |
| CCQ-S1-14-50 | CHAINSAW | CANNON CARVING BAR, QUARTER TIP, S1 Mount, 14 Inches, .050 Gauge (0.250 Pitch = 76 Drive Links, 0.325 Pitch = 61 Drive Links) | |
| CCQ-S1-16-43 | CHAINSAW | CANNON CARVING BAR, QUARTER TIP, S1 Mount, 16 Inches, .043 Gauge (0.250 Pitch = 86 Drive Links, 0.325 Pitch = 67 Drive Links) | For use on saws less than 40cc displacement |
| CCQ-S1-16-50 | CHAINSAW | CANNON CARVING BAR, QUARTER TIP, S1 Mount, 16 Inches, .050 Gauge (0.250 Pitch = 86 Drive Links, 0.325 Pitch = 67 Drive Links) | |
| CCQ-S1-20-43 | CHAINSAW | CANNON CARVING BAR, QUARTER TIP, S1 Mount, 20 Inches, .043 Gauge (0.250 Pitch = 101 Drive Links, 0.325 Pitch = 79 Drive Links) | For use on saws less than 40cc displacement |
| CCQ-S1-20-50 | CHAINSAW | CANNON CARVING BAR, QUARTER TIP, S1 Mount, 20 Inches, .050 Gauge (0.250 Pitch = 101 Drive Links, 0.325 Pitch = 79 Drive Links) | |
| CCQ-S1-24-43 | CHAINSAW | CANNON CARVING BAR, QUARTER TIP, S1 Mount, 24 Inches, .043 Gauge (0.250 Pitch = 116 Drive Links, 0.325 Pitch = 92 Drive Links) | For use on saws less than 40cc displacement |
| CCQ-S1-24-50 | CHAINSAW | CANNON CARVING BAR, QUARTER TIP, S1 Mount, 24 Inches, .050 Gauge (0.250 Pitch = 116 Drive Links, 0.325 Pitch = 92 Drive Links) | |
| CCT-C1-12-43 | CHAINSAW | CANNON CARVING BAR, TOONIE TIP, C1 Mount, 12 Inches, .043 Gauge (0.250 Pitch = 69 Drive Links, 0.325 Pitch = 55 Drive Links, 0.375/0.370 Pitch (Low Profile)= 48 Drive Links) | For use on saws less than 40cc displacement |
| CCT-C1-12-50 | CHAINSAW | CANNON CARVING BAR, TOONIE TIP, C1 Mount, 12 Inches, .050 Gauge (0.250 Pitch = 69 Drive Links, 0.325 Pitch = 55 Drive Links, 0.375/0.370 Pitch (Low Profile)= 48 Drive Links) | |
| CCT-C1-14-43 | CHAINSAW | CANNON CARVING BAR, TOONIE TIP, C1 Mount, 14 Inches, .043 Gauge (0.250 Pitch = 77 Drive Links, 0.325 Pitch = 61 Drive Links, 0.375/0.370 Pitch (Low Profile)= 54 Drive Links) | For use on saws less than 40cc displacement |
| CCT-C1-14-50 | CHAINSAW | CANNON CARVING BAR, TOONIE TIP, C1 Mount, 14 Inches, .050 Gauge (0.250 Pitch = 77 Drive Links, 0.325 Pitch = 61 Drive Links, 0.375/0.370 Pitch (Low Profile)= 54 Drive Links) | |
| CCT-C1-16-43 | CHAINSAW | CANNON CARVING BAR, TOONIE TIP, C1 Mount, 16 Inches, .043 Gauge (0.250 Pitch = 86 Drive Links, 0.325 Pitch = 67 Drive Links, 0.375/0.370 Pitch (Low Profile)= 60 Drive Links) | For use on saws less than 40cc displacement |
| CCT-C1-16-50 | CHAINSAW | CANNON CARVING BAR, TOONIE TIP, C1 Mount, 16 Inches, .050 Gauge (0.250 Pitch = 86 Drive Links, 0.325 Pitch = 67 Drive Links, 0.375/0.370 Pitch (Low Profile)= 60 Drive Links) | |
| CCT-C1-20-43 | CHAINSAW | CANNON CARVING BAR, TOONIE TIP, C1 Mount, 20 Inches, .043 Gauge (0.250 Pitch = 102 Drive Links, 0.325 Pitch = 80 Drive Links, 0.375/0.370 Pitch (Low Profile)= 70 Drive Links) | For use on saws less than 40cc displacement |
| CCT-C1-20-50 | CHAINSAW | CANNON CARVING BAR, TOONIE TIP, C1 Mount, 20 Inches, .050 Gauge (0.250 Pitch = 102 Drive Links, 0.325 Pitch = 80 Drive Links, 0.375/0.370 Pitch (Low Profile)= 70 Drive Links) | |
| CCT-C1-24-43 | CHAINSAW | CANNON CARVING BAR, TOONIE TIP, C1 Mount, 24 Inches, .043 Gauge (0.250 Pitch = 118 Drive Links, 0.325 Pitch = 92 Drive Links, 0.375/0.370 Pitch (Low Profile)= 82 Drive Links) | For use on saws less than 40cc displacement |
| CCT-C1-24-50 | CHAINSAW | CANNON CARVING BAR, TOONIE TIP, C1 Mount, 24 Inches, .050 Gauge (0.250 Pitch = 118 Drive Links, 0.325 Pitch = 92 Drive Links, 0.375/0.370 Pitch (Low Profile)= 82 Drive Links) | |
| CCT-H1-14-43 | CHAINSAW | CANNON CARVING BAR, TOONIE TIP, H1 Mount, 14 Inches, .043 Gauge (0.250 Pitch = 77 Drive Links, 0.325 Pitch = 61 Drive Links, 0.375/0.370 Pitch (Low Profile)= 54 Drive Links) | For use on saws less than 40cc displacement |
| CCT-H1-14-50 | CHAINSAW | CANNON CARVING BAR, TOONIE TIP, H1 Mount, 14 Inches, .050 Gauge (0.250 Pitch = 77 Drive Links, 0.325 Pitch = 61 Drive Links, 0.375/0.370 Pitch (Low Profile)= 54 Drive Links) | |
| CCT-H1-16-43 | CHAINSAW | CANNON CARVING BAR, TOONIE TIP, H1 Mount, 16 Inches, .043 Gauge (0.250 Pitch = 86 Drive Links, 0.325 Pitch = 67 Drive Links, 0.375/0.370 Pitch (Low Profile)= 60 Drive Links) | For use on saws less than 40cc displacement |
| CCT-H1-16-50 | CHAINSAW | CANNON CARVING BAR, TOONIE TIP, H1 Mount, 16 Inches, .050 Gauge (0.250 Pitch = 86 Drive Links, 0.325 Pitch = 67 Drive Links, 0.375/0.370 Pitch (Low Profile)= 60 Drive Links) | |
| CCT-H1-20-43 | CHAINSAW | CANNON CARVING BAR, TOONIE TIP, H1 Mount, 20 Inches, .043 Gauge (0.250 Pitch = 102 Drive Links, 0.325 Pitch = 80 Drive Links, 0.375/0.370 Pitch (Low Profile)= 70 Drive Links) | For use on saws less than 40cc displacement |
| CCT-H1-20-50 | CHAINSAW | CANNON CARVING BAR, TOONIE TIP, H1 Mount, 20 Inches, .050 Gauge (0.250 Pitch = 102 Drive Links, 0.325 Pitch = 80 Drive Links, 0.375/0.370 Pitch (Low Profile)= 70 Drive Links) | |
| CCT-H1-24-43 | CHAINSAW | CANNON CARVING BAR, TOONIE TIP, H1 Mount, 24 Inches, .043 Gauge (0.250 Pitch = 118 Drive Links, 0.325 Pitch = 92 Drive Links, 0.375/0.370 Pitch (Low Profile)= 82 Drive Links) | For use on saws less than 40cc displacement |
| CCT-H1-24-50 | CHAINSAW | CANNON CARVING BAR, TOONIE TIP, H1 Mount, 24 Inches, .050 Gauge (0.250 Pitch = 118 Drive Links, 0.325 Pitch = 92 Drive Links, 0.375/0.370 Pitch (Low Profile)= 82 Drive Links) | |
| CCT-H1-28-43 | CHAINSAW | CANNON CARVING BAR, TOONIE TIP, H1 Mount, 28 Inches, .043 Gauge (0.250 Pitch = 130 Drive Links, 0.325 Pitch = 102 Drive Links, 0.375/0.370 Pitch (Low Profile)= 90 Drive Links) | For use on saws less than 40cc displacement |

| | | | |
|---|---|---|---|
| CCT-H1-28-50 | CHAINSAW | CANNON CARVING BAR, TOONIE TIP, H1 Mount, 28 Inches, .050 Gauge (0.250 Pitch = 130 Drive Links, 0.325 Pitch = 102 Drive Links, 0.375/0.370 Pitch (Low Profile)= 90 Drive Links) | |
| CCT-S1-14-43 | CHAINSAW | CANNON CARVING BAR, TOONIE TIP, S1 Mount, 14 Inches, .043 Gauge (0.250 Pitch = 77 Drive Links, 0.325 Pitch = 61 Drive Links, 0.375/0.370 Pitch (Low Profile)= 54 Drive Links) | For use on saws less than 40cc displacement |
| CCT-S1-14-50 | CHAINSAW | CANNON CARVING BAR, TOONIE TIP, S1 Mount, 14 Inches, .050 Gauge (0.250 Pitch = 77 Drive Links, 0.325 Pitch = 61 Drive Links, 0.375/0.370 Pitch (Low Profile)= 54 Drive Links) | |
| CCT-S1-16-43 | CHAINSAW | CANNON CARVING BAR, TOONIE TIP, S1 Mount, 16 Inches, .043 Gauge (0.250 Pitch = 86 Drive Links, 0.325 Pitch = 67 Drive Links, 0.375/0.370 Pitch (Low Profile)= 60 Drive Links) | For use on saws less than 40cc displacement |
| CCT-S1-16-50 | CHAINSAW | CANNON CARVING BAR, TOONIE TIP, S1 Mount, 16 Inches, .050 Gauge (0.250 Pitch = 86 Drive Links, 0.325 Pitch = 67 Drive Links, 0.375/0.370 Pitch (Low Profile)= 60 Drive Links) | |
| CCT-S1-20-43 | CHAINSAW | CANNON CARVING BAR, TOONIE TIP, S1 Mount, 20 Inches, .043 Gauge (0.250 Pitch = 102 Drive Links, 0.325 Pitch = 80 Drive Links, 0.375/0.370 Pitch (Low Profile)= 70 Drive Links) | For use on saws less than 40cc displacement |
| CCT-S1-20-50 | CHAINSAW | CANNON CARVING BAR, TOONIE TIP, S1 Mount, 20 Inches, .050 Gauge (0.250 Pitch = 102 Drive Links, 0.325 Pitch = 80 Drive Links, 0.375/0.370 Pitch (Low Profile)= 70 Drive Links) | |
| CCT-S1-24-43 | CHAINSAW | CANNON CARVING BAR, TOONIE TIP, S1 Mount, 24 Inches, .043 Gauge (0.250 Pitch = 118 Drive Links, 0.325 Pitch = 92 Drive Links, 0.375/0.370 Pitch (Low Profile)= 82 Drive Links) | For use on saws less than 40cc displacement |
| CCT-S1-24-50 | CHAINSAW | CANNON CARVING BAR, TOONIE TIP, S1 Mount, 24 Inches, .050 Gauge (0.250 Pitch = 118 Drive Links, 0.325 Pitch = 92 Drive Links, 0.375/0.370 Pitch (Low Profile)= 82 Drive Links) | |
| CCT-S1-28-43 | CHAINSAW | CANNON CARVING BAR, TOONIE TIP, S1 Mount, 28 Inches, .043 Gauge (0.250 Pitch = 130 Drive Links, 0.325 Pitch = 102 Drive Links, 0.375/0.370 Pitch (Low Profile)= 90 Drive Links) | For use on saws less than 40cc displacement |
| CCT-S1-28-50 | CHAINSAW | CANNON CARVING BAR, TOONIE TIP, S1 Mount, 28 Inches, .050 Gauge (0.250 Pitch = 130 Drive Links, 0.325 Pitch = 102 Drive Links, 0.375/0.370 Pitch (Low Profile)= 90 Drive Links) | |
| CCP-A1-25-63-R | CHAINSAW | CANNON COMPETITION BAR, ROLLER NOSE, A1 Mount, 25 Inches, .063 Gauge, 0.325, 0.375 or 0.404 Pitch, Drive Link Count Varies with Drive Sprocket | 2.8" Diameter Roller Nose Tip |
| CCP-C1-16-50-R | CHAINSAW | CANNON COMPETITION BAR, ROLLER NOSE, C1 Mount, 16 Inches, .050 Gauge, 0.325, 0.375 or 0.404 Pitch, Drive Link Count Varies with Drive Sprocket | 2.245" Diameter Roller Nose Tip |
| CCP-H1-16-50-R | CHAINSAW | CANNON COMPETITION BAR, ROLLER NOSE, H1 Mount, 16 Inches, .050 Gauge, 0.325, 0.375 or 0.404 Pitch, Drive Link Count Varies with Drive Sprocket | 2.8" Diameter Roller Nose Tip |
| CCP-H1-16-58-R | CHAINSAW | CANNON COMPETITION BAR, ROLLER NOSE, H1 Mount, 16 Inches, .058 Gauge, 0.325, 0.375 or 0.404 Pitch, Drive Link Count Varies with Drive Sprocket | 2.8" Diameter Roller Nose Tip |
| CCP-H1-16-63-R | CHAINSAW | CANNON COMPETITION BAR, ROLLER NOSE, H1 Mount, 16 Inches, .063 Gauge, 0.325, 0.375 or 0.404 Pitch, Drive Link Count Varies with Drive Sprocket | 2.8" Diameter Roller Nose Tip |
| CPR-H1-18-63-R | CHAINSAW | CANNON COMPETITION BAR, ROLLER NOSE, H1 Mount, 18 Inches, .063 Gauge, 0.325, 0.375 or 0.404 Pitch, Drive Link Count Varies with Drive Sprocket | 2.8" Diameter Roller Nose Tip |
| CCP-H1-20-50-R | CHAINSAW | CANNON COMPETITION BAR, ROLLER NOSE, H1 Mount, 20 Inches, .050 Gauge, 0.325, 0.375 or 0.404 Pitch, Drive Link Count Varies with Drive Sprocket | 2.8" Diameter Roller Nose Tip |
| CCP-H1-20-63-R | CHAINSAW | CANNON COMPETITION BAR, ROLLER NOSE, H1 Mount, 20 Inches, .063 Gauge, 0.325, 0.375 or 0.404 Pitch, Drive Link Count Varies with Drive Sprocket | 2.8" Diameter Roller Nose Tip |
| CCP-H1-25-50-R | CHAINSAW | CANNON COMPETITION BAR, ROLLER NOSE, H1 Mount, 25 Inches, .050 Gauge, 0.325, 0.375 or 0.404 Pitch, Drive Link Count Varies with Drive Sprocket | 2.8" Diameter Roller Nose Tip |
| CCP-H1-25-58-R | CHAINSAW | CANNON COMPETITION BAR, ROLLER NOSE, H1 Mount, 25 Inches, .058 Gauge, 0.325, 0.375 or 0.404 Pitch, Drive Link Count Varies with Drive Sprocket | 2.8" Diameter Roller Nose Tip |
| CCP-H1-25-63-R | CHAINSAW | CANNON COMPETITION BAR, ROLLER NOSE, H1 Mount, 25 Inches, .063 Gauge, 0.325, 0.375 or 0.404 Pitch, Drive Link Count Varies with Drive Sprocket | 2.8" Diameter Roller Nose Tip |
| CCP-H1-30-50-R | CHAINSAW | CANNON COMPETITION BAR, ROLLER NOSE, H1 Mount, 30 Inches, .050 Gauge, 0.325, 0.375 or 0.404 Pitch, Drive Link Count Varies with Drive Sprocket | 2.8" Diameter Roller Nose Tip |
| CCP-H1-30-63-R | CHAINSAW | CANNON COMPETITION BAR, ROLLER NOSE, H1 Mount, 30 Inches, .063 Gauge, 0.325, 0.375 or 0.404 Pitch, Drive Link Count Varies with Drive Sprocket | 2.8" Diameter Roller Nose Tip |
| CCP-H1-36-50-R | CHAINSAW | CANNON COMPETITION BAR, ROLLER NOSE, H1 Mount, 36 Inches, .050 Gauge, 0.325, 0.375 or 0.404 Pitch, Drive Link Count Varies with Drive Sprocket | 2.8" Diameter Roller Nose Tip |
| CCP-H1-36-63-R | CHAINSAW | CANNON COMPETITION BAR, ROLLER NOSE, H1 Mount, 36 Inches, .063 Gauge, 0.325, 0.375 or 0.404 Pitch, Drive Link Count Varies with Drive Sprocket | 2.8" Diameter Roller Nose Tip |
| CCP-H1R-20-50-R | CHAINSAW | CANNON COMPETITION BAR, ROLLER NOSE, H1R Mount, 20 Inches, .050 Gauge, 0.325, 0.375 or 0.404 Pitch, Drive Link Count Varies with Drive Sprocket | 2.8" Diameter Roller Nose Tip |
| CCP-H1W1-25-58-R | CHAINSAW | CANNON COMPETITION BAR, ROLLER NOSE, H1W1 Mount, 25 Inches, .058 Gauge, 0.325, 0.375 or 0.404 Pitch, Drive Link Count Varies with Drive Sprocket | 2.8" Diameter Roller Nose Tip |
| CCP-M1-25-63-R | CHAINSAW | CANNON COMPETITION BAR, ROLLER NOSE, M1 Mount, 25 Inches, .063 Gauge, 0.325, 0.375 or 0.404 Pitch, Drive Link Count Varies with Drive Sprocket | 2.8" Diameter Roller Nose Tip |
| CCP-M1-30-63-R | CHAINSAW | CANNON COMPETITION BAR, ROLLER NOSE, M1 Mount, 30 Inches, .063 Gauge, 0.325, 0.375 or 0.404 Pitch, Drive Link Count Varies with Drive Sprocket | 2.8" Diameter Roller Nose Tip |
| CCP-N1-29-63-R | CHAINSAW | CANNON COMPETITION BAR, ROLLER NOSE, N1 Mount, 29 Inches, .063 Gauge, 0.325, 0.375 or 0.404 Pitch, Drive Link Count Varies with Drive Sprocket | 2.8" Diameter Roller Nose Tip |
| CCP-N1W1-29-63-R | CHAINSAW | CANNON COMPETITION BAR, ROLLER NOSE, N1W1 Mount, 29 Inches, .063 Gauge, 0.325, 0.375 or 0.404 Pitch, Drive Link Count Varies with Drive Sprocket | 2.8" Diameter Roller Nose Tip |
| CCP-RT10-25-63-R | CHAINSAW | CANNON COMPETITION BAR, ROLLER NOSE, RT10 Mount, 25 Inches, .063 Gauge, 0.325, 0.375 or 0.404 Pitch, Drive Link Count Varies with Drive Sprocket | 2.8" Diameter Roller Nose Tip |
| CCP-RT11-22-63-R | CHAINSAW | CANNON COMPETITION BAR, ROLLER NOSE, RT11 Mount, 22 Inches, .063 Gauge, 0.325, 0.375 or 0.404 Pitch, Drive Link Count Varies with Drive Sprocket | 2.8" Diameter Roller Nose Tip |
| CCP-RT11-24-63-R | CHAINSAW | CANNON COMPETITION BAR, ROLLER NOSE, RT11 Mount, 24 Inches, .063 Gauge, 0.325, 0.375 or 0.404 Pitch, Drive Link Count Varies with Drive Sprocket | 2.8" Diameter Roller Nose Tip |
| CCP-RT12-25-63-R | CHAINSAW | CANNON COMPETITION BAR, ROLLER NOSE, RT12 Mount, 25 Inches, .063 Gauge, 0.325, 0.375 or 0.404 Pitch, Drive Link Count Varies with Drive Sprocket | 2.8" Diameter Roller Nose Tip |
| CCP-RT14-25-63-R | CHAINSAW | CANNON COMPETITION BAR, ROLLER NOSE, RT14 Mount, 25 Inches, .063 Gauge, 0.325, 0.375 or 0.404 Pitch, Drive Link Count Varies with Drive Sprocket | 2.8" Diameter Roller Nose Tip |
| CCP-RT15-24-63-R | CHAINSAW | CANNON COMPETITION BAR, ROLLER NOSE, RT15 Mount, 24 Inches, .063 Gauge, 0.325, 0.375 or 0.404 Pitch, Drive Link Count Varies with Drive Sprocket | 2.8" Diameter Roller Nose Tip |
| CCP-RT16-24-63-R | CHAINSAW | CANNON COMPETITION BAR, ROLLER NOSE, RT16 Mount, 24 Inches, .063 Gauge, 0.325, 0.375 or 0.404 Pitch, Drive Link Count Varies with Drive Sprocket | 2.8" Diameter Roller Nose Tip |
| CCP-RT17-23-63-R | CHAINSAW | CANNON COMPETITION BAR, ROLLER NOSE, RT17 Mount, 23 Inches, .063 Gauge, 0.325, 0.375 or 0.404 Pitch, Drive Link Count Varies with Drive Sprocket | 2.8" Diameter Roller Nose Tip |
| CCP-RT18-24-63-R | CHAINSAW | CANNON COMPETITION BAR, ROLLER NOSE, RT18 Mount, 24 Inches, .063 Gauge, 0.325, 0.375 or 0.404 Pitch, Drive Link Count Varies with Drive Sprocket | 2.8" Diameter Roller Nose Tip |
| CCP-RT19-21-63-R | CHAINSAW | CANNON COMPETITION BAR, ROLLER NOSE, RT19 Mount, 21 Inches, .063 Gauge, 0.325, 0.375 or 0.404 Pitch, Drive Link Count Varies with Drive Sprocket | 2.8" Diameter Roller Nose Tip |
| CCP-RT20-25-63-R | CHAINSAW | CANNON COMPETITION BAR, ROLLER NOSE, RT20 Mount, 25 Inches, .063 Gauge, 0.325, 0.375 or 0.404 Pitch, Drive Link Count Varies with Drive Sprocket | 2.8" Diameter Roller Nose Tip |
| CCP-RT21-24-63-R | CHAINSAW | CANNON COMPETITION BAR, ROLLER NOSE, RT21 Mount, 24 Inches, .063 Gauge, 0.325, 0.375 or 0.404 Pitch, Drive Link Count Varies with Drive Sprocket | 2.8" Diameter Roller Nose Tip |
| CCP-RT22-25-63-R | CHAINSAW | CANNON COMPETITION BAR, ROLLER NOSE, RT22 Mount, 25 Inches, .063 Gauge, 0.325, 0.375 or 0.404 Pitch, Drive Link Count Varies with Drive Sprocket | 2.8" Diameter Roller Nose Tip |
| CCP-RT2-25-63-R | CHAINSAW | CANNON COMPETITION BAR, ROLLER NOSE, RT2 Mount, 25 Inches, .063 Gauge, 0.325, 0.375 or 0.404 Pitch, Drive Link Count Varies with Drive Sprocket | 2.8" Diameter Roller Nose Tip |
| CCP-RT2-30-63-R | CHAINSAW | CANNON COMPETITION BAR, ROLLER NOSE, RT2 Mount, 30 Inches, .063 Gauge, 0.325, 0.375 or 0.404 Pitch, Drive Link Count Varies with Drive Sprocket | 2.8" Diameter Roller Nose Tip |
| CCP-RT23-22-63-R | CHAINSAW | CANNON COMPETITION BAR, ROLLER NOSE, RT23 Mount, 22 Inches, .063 Gauge, 0.325, 0.375 or 0.404 Pitch, Drive Link Count Varies with Drive Sprocket | 2.8" Diameter Roller Nose Tip |
| CCP-RT23-24-63-R | CHAINSAW | CANNON COMPETITION BAR, ROLLER NOSE, RT23 Mount, 24 Inches, .063 Gauge, 0.325, 0.375 or 0.404 Pitch, Drive Link Count Varies with Drive Sprocket | 2.8" Diameter Roller Nose Tip |
| CCP-RT24-25-63-R | CHAINSAW | CANNON COMPETITION BAR, ROLLER NOSE, RT24 Mount, 25 Inches, .063 Gauge, 0.325, 0.375 or 0.404 Pitch, Drive Link Count Varies with Drive Sprocket | 2.8" Diameter Roller Nose Tip |
| CCP-RT25-25-63-R | CHAINSAW | CANNON COMPETITION BAR, ROLLER NOSE, RT25 Mount, 25 Inches, .063 Gauge, 0.325, 0.375 or 0.404 Pitch, Drive Link Count Varies with Drive Sprocket | 2.8" Diameter Roller Nose Tip |
| CCP-RT26-24-63-R | CHAINSAW | CANNON COMPETITION BAR, ROLLER NOSE, RT26 Mount, 24 Inches, .063 Gauge, 0.325, 0.375 or 0.404 Pitch, Drive Link Count Varies with Drive Sprocket | 2.8" Diameter Roller Nose Tip |
| CCP-RT26-36-63-R | CHAINSAW | CANNON COMPETITION BAR, ROLLER NOSE, RT26 Mount, 36 Inches, .063 Gauge, 0.325, 0.375 or 0.404 Pitch, Drive Link Count Varies with Drive Sprocket | 2.8" Diameter Roller Nose Tip |
| CCP-RT27-18-50-R | CHAINSAW | CANNON COMPETITION BAR, ROLLER NOSE, RT27 Mount, 18 Inches, .050 Gauge, 0.325, 0.375 or 0.404 Pitch, Drive Link Count Varies with Drive Sprocket | 2.8" Diameter Roller Nose Tip |
| CCP-RT28-20-50-R | CHAINSAW | CANNON COMPETITION BAR, ROLLER NOSE, RT28 Mount, 20 Inches, .050 Gauge, 0.325, 0.375 or 0.404 Pitch, Drive Link Count Varies with Drive Sprocket | 2.8" Diameter Roller Nose Tip |
| CCP-RT29-25-63-R | CHAINSAW | CANNON COMPETITION BAR, ROLLER NOSE, RT29 Mount, 25 Inches, .063 Gauge, 0.325, 0.375 or 0.404 Pitch, Drive Link Count Varies with Drive Sprocket | 2.8" Diameter Roller Nose Tip |
| CCP-RT30-25-63-R | CHAINSAW | CANNON COMPETITION BAR, ROLLER NOSE, RT30 Mount, 25 Inches, .063 Gauge, 0.325, 0.375 or 0.404 Pitch, Drive Link Count Varies with Drive Sprocket | 2.8" Diameter Roller Nose Tip |
| CCP-RT3-25-63-R | CHAINSAW | CANNON COMPETITION BAR, ROLLER NOSE, RT3 Mount, 25 Inches, .063 Gauge, 0.325, 0.375 or 0.404 Pitch, Drive Link Count Varies with Drive Sprocket | 2.8" Diameter Roller Nose Tip |
| CCP-RT4-25-63-R | CHAINSAW | CANNON COMPETITION BAR, ROLLER NOSE, RT4 Mount, 25 Inches, .063 Gauge, 0.325, 0.375 or 0.404 Pitch, Drive Link Count Varies with Drive Sprocket | 2.8" Diameter Roller Nose Tip |
| CCP-RT5-23-63-R | CHAINSAW | CANNON COMPETITION BAR, ROLLER NOSE, RT5 Mount, 23 Inches, .063 Gauge, 0.325, 0.375 or 0.404 Pitch, Drive Link Count Varies with Drive Sprocket | 2.8" Diameter Roller Nose Tip |
| CCP-RT5-25-63-R | CHAINSAW | CANNON COMPETITION BAR, ROLLER NOSE, RT5 Mount, 25 Inches, .063 Gauge, 0.325, 0.375 or 0.404 Pitch, Drive Link Count Varies with Drive Sprocket | 2.8" Diameter Roller Nose Tip |
| CCP-RT6-22-63-R | CHAINSAW | CANNON COMPETITION BAR, ROLLER NOSE, RT6 Mount, 22 Inches, .063 Gauge, 0.325, 0.375 or 0.404 Pitch, Drive Link Count Varies with Drive Sprocket | 2.8" Diameter Roller Nose Tip |
| CCP-RT7-25-63-R | CHAINSAW | CANNON COMPETITION BAR, ROLLER NOSE, RT7 Mount, 25 Inches, .063 Gauge, 0.325, 0.375 or 0.404 Pitch, Drive Link Count Varies with Drive Sprocket | 2.8" Diameter Roller Nose Tip |
| CCP-RT8-25-63-R | CHAINSAW | CANNON COMPETITION BAR, ROLLER NOSE, RT8 Mount, 25 Inches, .063 Gauge, 0.325, 0.375 or 0.404 Pitch, Drive Link Count Varies with Drive Sprocket | 2.8" Diameter Roller Nose Tip |
| CCP-RT9-25-63-R | CHAINSAW | CANNON COMPETITION BAR, ROLLER NOSE, RT9 Mount, 25 Inches, .063 Gauge, 0.325, 0.375 or 0.404 Pitch, Drive Link Count Varies with Drive Sprocket | 2.8" Diameter Roller Nose Tip |
| CCP-S1-16-50-R | CHAINSAW | CANNON COMPETITION BAR, ROLLER NOSE, S1 Mount, 16 Inches, .050 Gauge, 0.325, 0.375 or 0.404 Pitch, Drive Link Count Varies with Drive Sprocket | 2.8" Diameter Roller Nose Tip |
| CCP-S1-16-63-R | CHAINSAW | CANNON COMPETITION BAR, ROLLER NOSE, S1 Mount, 16 Inches, .063 Gauge, 0.325, 0.375 or 0.404 Pitch, Drive Link Count Varies with Drive Sprocket | 2.8" Diameter Roller Nose Tip |
| CCP-S1-20-50-R | CHAINSAW | CANNON COMPETITION BAR, ROLLER NOSE, S1 Mount, 20 Inches, .050 Gauge, 0.325, 0.375 or 0.404 Pitch, Drive Link Count Varies with Drive Sprocket | 2.8" Diameter Roller Nose Tip |
| CCP-S1-20-63-R | CHAINSAW | CANNON COMPETITION BAR, ROLLER NOSE, S1 Mount, 20 Inches, .063 Gauge, 0.325, 0.375 or 0.404 Pitch, Drive Link Count Varies with Drive Sprocket | 2.8" Diameter Roller Nose Tip |
| CCP-S1-25-50-R | CHAINSAW | CANNON COMPETITION BAR, ROLLER NOSE, S1 Mount, 25 Inches, .050 Gauge, 0.325, 0.375 or 0.404 Pitch, Drive Link Count Varies with Drive Sprocket | 2.8" Diameter Roller Nose Tip |
| CCP-S1-25-63-R | CHAINSAW | CANNON COMPETITION BAR, ROLLER NOSE, S1 Mount, 25 Inches, .063 Gauge, 0.325, 0.375 or 0.404 Pitch, Drive Link Count Varies with Drive Sprocket | 2.8" Diameter Roller Nose Tip |
| CCP-S1-30-50-R | CHAINSAW | CANNON COMPETITION BAR, ROLLER NOSE, S1 Mount, 30 Inches, .050 Gauge, 0.325, 0.375 or 0.404 Pitch, Drive Link Count Varies with Drive Sprocket | 2.8" Diameter Roller Nose Tip |
| CCP-S1-30-63-R | CHAINSAW | CANNON COMPETITION BAR, ROLLER NOSE, S1 Mount, 30 Inches, .063 Gauge, 0.325, 0.375 or 0.404 Pitch, Drive Link Count Varies with Drive Sprocket | 2.8" Diameter Roller Nose Tip |
| CCP-S1-36-50-R | CHAINSAW | CANNON COMPETITION BAR, ROLLER NOSE, S1 Mount, 36 Inches, .050 Gauge, 0.325, 0.375 or 0.404 Pitch, Drive Link Count Varies with Drive Sprocket | 2.8" Diameter Roller Nose Tip |
| CCP-S1-36-63-R | CHAINSAW | CANNON COMPETITION BAR, ROLLER NOSE, S1 Mount, 36 Inches, .063 Gauge, 0.325, 0.375 or 0.404 Pitch, Drive Link Count Varies with Drive Sprocket | 2.8" Diameter Roller Nose Tip |
| CCP-S2-16-50-R | CHAINSAW | CANNON COMPETITION BAR, ROLLER NOSE, S2 Mount, 16 Inches, .050 Gauge, 0.325, 0.375 or 0.404 Pitch, Drive Link Count Varies with Drive Sprocket | 2.8" Diameter Roller Nose Tip |
| CCP-S2-16-63-R | CHAINSAW | CANNON COMPETITION BAR, ROLLER NOSE, S2 Mount, 16 Inches, .063 Gauge, 0.325, 0.375 or 0.404 Pitch, Drive Link Count Varies with Drive Sprocket | 2.8" Diameter Roller Nose Tip |
| CPR-S2-18-63-R | CHAINSAW | CANNON COMPETITION BAR, ROLLER NOSE, S2 Mount, 18 Inches, .063 Gauge, 0.325, 0.375 or 0.404 Pitch, Drive Link Count Varies with Drive Sprocket | 2.8" Diameter Roller Nose Tip |
| CCP-S2-20-50-R | CHAINSAW | CANNON COMPETITION BAR, ROLLER NOSE, S2 Mount, 20 Inches, .050 Gauge, 0.325, 0.375 or 0.404 Pitch, Drive Link Count Varies with Drive Sprocket | 2.8" Diameter Roller Nose Tip |
| CCP-S2-20-63-R | CHAINSAW | CANNON COMPETITION BAR, ROLLER NOSE, S2 Mount, 20 Inches, .063 Gauge, 0.325, 0.375 or 0.404 Pitch, Drive Link Count Varies with Drive Sprocket | 2.8" Diameter Roller Nose Tip |
| CCP-S2-25-50-R | CHAINSAW | CANNON COMPETITION BAR, ROLLER NOSE, S2 Mount, 25 Inches, .050 Gauge, 0.325, 0.375 or 0.404 Pitch, Drive Link Count Varies with Drive Sprocket | 2.8" Diameter Roller Nose Tip |
| CCP-S2-25-63-R | CHAINSAW | CANNON COMPETITION BAR, ROLLER NOSE, S2 Mount, 25 Inches, .063 Gauge, 0.325, 0.375 or 0.404 Pitch, Drive Link Count Varies with Drive Sprocket | 2.8" Diameter Roller Nose Tip |
| CCP-S2-30-50-R | CHAINSAW | CANNON COMPETITION BAR, ROLLER NOSE, S2 Mount, 30 Inches, .050 Gauge, 0.325, 0.375 or 0.404 Pitch, Drive Link Count Varies with Drive Sprocket | 2.8" Diameter Roller Nose Tip |
| CCP-S2-30-63-R | CHAINSAW | CANNON COMPETITION BAR, ROLLER NOSE, S2 Mount, 30 Inches, .063 Gauge, 0.325, 0.375 or 0.404 Pitch, Drive Link Count Varies with Drive Sprocket | 2.8" Diameter Roller Nose Tip |
| CCP-S2-36-50-R | CHAINSAW | CANNON COMPETITION BAR, ROLLER NOSE, S2 Mount, 36 Inches, .050 Gauge, 0.325, 0.375 or 0.404 Pitch, Drive Link Count Varies with Drive Sprocket | 2.8" Diameter Roller Nose Tip |
| CCP-S2-36-63-R | CHAINSAW | CANNON COMPETITION BAR, ROLLER NOSE, S2 Mount, 36 Inches, .063 Gauge, 0.325, 0.375 or 0.404 Pitch, Drive Link Count Varies with Drive Sprocket | 2.8" Diameter Roller Nose Tip |
| CDE-G1-108-63 | CHAINSAW | CANNON MILLING BAR, DOUBLE ENDED, G1 Mount, 108 Inches, .063 Gauge, 0.375 or .404 Pitch, Drive Link Count Varies with Drive Sprocket | |
| CDE-G1-120-63 | CHAINSAW | CANNON MILLING BAR, DOUBLE ENDED, G1 Mount, 120 Inches, .063 Gauge, 0.375 or .404 Pitch, Drive Link Count Varies with Drive Sprocket | |
| CDE-G1-138-63 | CHAINSAW | CANNON MILLING BAR, DOUBLE ENDED, G1 Mount, 138 Inches, .063 Gauge, 0.375 or .404 Pitch, Drive Link Count Varies with Drive Sprocket | |
| CDE-G1-144-63 | CHAINSAW | CANNON MILLING BAR, DOUBLE ENDED, G1 Mount, 144 Inches, .063 Gauge, 0.375 or .404 Pitch, Drive Link Count Varies with Drive Sprocket | |
| CDE-G1-44-63 | CHAINSAW | CANNON MILLING BAR, DOUBLE ENDED, G1 Mount, 44 Inches, .063 Gauge (0.375 Pitch = 136 Drive Links, 0.404 Pitch = 124 Drive Links) | |
| CDE-G1-50-63 | CHAINSAW | CANNON MILLING BAR, DOUBLE ENDED, G1 Mount, 50 Inches, .063 Gauge (0.375 Pitch = 153 Drive Links, 0.404 Pitch = 138 Drive Links) | |
| CDE-G1-56-63 | CHAINSAW | CANNON MILLING BAR, DOUBLE ENDED, G1 Mount, 56 Inches, .063 Gauge (0.375 Pitch = 170 Drive Links, 0.404 Pitch = 154 Drive Links) | |
| CDE-G1-66-63 | CHAINSAW | CANNON MILLING BAR, DOUBLE ENDED, G1 Mount, 66 Inches, .063 Gauge (0.375 Pitch = 200 Drive Links, 0.404 Pitch = 180 Drive Links) | |
| CDE-G1-72-63 | CHAINSAW | CANNON MILLING BAR, DOUBLE ENDED, G1 Mount, 72 Inches, .063 Gauge (0.375 Pitch = 213 Drive Links, 0.404 Pitch = 194 Drive Links) | |
| CDE-G1-84-63 | CHAINSAW | CANNON MILLING BAR, DOUBLE ENDED, G1 Mount, 84 Inches, .063 Gauge (0.375 Pitch = 246 Drive Links, 0.404 Pitch = 221 Drive Links) | |
| CDE-G1-96-63 | CHAINSAW | CANNON MILLING BAR, DOUBLE ENDED, G1 Mount, 96 Inches, .063 Gauge (0.375 Pitch = 277 Drive Links, 0.404 Pitch = 252 Drive Links) | |
| CDE-G2-66-63 | CHAINSAW | CANNON MILLING BAR, DOUBLE ENDED, G2 Mount, 66 Inches, .063 Gauge, 0.404 Pitch, Check Owners Manual for Drive Links | |
| CDE-G2-87-63 | CHAINSAW | CANNON MILLING BAR, DOUBLE ENDED, G2 Mount, 87 Inches, .063 Gauge, 0.404 Pitch, Check Owners Manual for Drive Links | |
| CDE-LM-132-63 | CHAINSAW | CANNON MILLING BAR, DOUBLE ENDED, LM Mount, 132 Inches, .063 Gauge, 0.404 Pitch, Check Owners Manual for Drive Links | |
| CDE-LM-72-63-4LM1 | CHAINSAW | CANNON MILLING BAR, REPLACEABLE SPROCKET NOSE, LM Mount, 72 Inches, .063 Gauge, 0.404 Pitch, Check Owners Manual for Drive Links | |
| CDE-LM-87-63-4LM1 | CHAINSAW | CANNON MILLING BAR, REPLACEABLE SPROCKET NOSE, LM Mount, 87 Inches, .063 Gauge, 0.404 Pitch, Check Owners Manual for Drive Links | |
| CDE-LM1-72-63-4LM1 | CHAINSAW | CANNON MILLING BAR, REPLACEABLE SPROCKET NOSE, LM1 Mount, 72 Inches, .063 Gauge, 0.404 Pitch, Check Owners Manual for Drive Links | |
| CDE-LM1-87-63-4LM1 | CHAINSAW | CANNON MILLING BAR, REPLACEABLE SPROCKET NOSE, LM1 Mount, 87 Inches, .063 Gauge, 0.404 Pitch, Check Owners Manual for Drive Links | |
| CDE-LM2-84-63 | CHAINSAW | CANNON MILLING BAR, DOUBLE ENDED, LM2 Mount, 84 Inches, .063 Gauge, 0.404 Pitch, Check Owners Manual for Drive Links | |
| CDE-PM-73-63-4 | CHAINSAW | CANNON MILLING BAR, REPLACEABLE SPROCKET NOSE, PM Mount, 73 Inches, .063 Gauge, 0.404 Pitch, Check Owners Manual for Drive Links | |
| CDE-PM1-72-63 | CHAINSAW | CANNON MILLING BAR, REPLACEABLE SPROCKET NOSE, PM1 Mount, 72 Inches, .063 Gauge, 0.404 Pitch, Check Owners Manual for Drive Links | |
| CDE-PM1-87-63 | CHAINSAW | CANNON MILLING BAR, REPLACEABLE SPROCKET NOSE, PM1 Mount, 87 Inches, .063 Gauge, 0.404 Pitch, Check Owners Manual for Drive Links | |
| CMM-C1-36-50 | CHAINSAW | CANNON MILLING BAR, DOUBLE ENDED, NARROW KERF, C1 Mount, 36 Inches, .050 Gauge, 0.370 Pitch (Low Profile), 111 Drive Links | |
| CLW-C1-12-50 | CHAINSAW | CANNON MOUNTING BAR, LOG WIZARD, C1 Mount, 12 Inches, .050 Gauge, 0.375 Pitch, Check Owners Manual for Drive Links | |
| CLW-C1-12-58 | CHAINSAW | CANNON MOUNTING BAR, LOG WIZARD, C1 Mount, 12 Inches, .058 Gauge, 0.375 Pitch, Check Owners Manual for Drive Links | |
| CLW-C1-12-63 | CHAINSAW | CANNON MOUNTING BAR, LOG WIZARD, C1 Mount, 12 Inches, .063 Gauge, 0.375 Pitch, Check Owners Manual for Drive Links | |
| CLW-H1-12-50 | CHAINSAW | CANNON MOUNTING BAR, LOG WIZARD, H1 Mount, 12 Inches, .050 Gauge, 0.375 Pitch, Check Owners Manual for Drive Links | |
| CLW-H1-12-58 | CHAINSAW | CANNON MOUNTING BAR, LOG WIZARD, H1 Mount, 12 Inches, .058 Gauge, 0.375 Pitch, Check Owners Manual for Drive Links | |
| CLW-H1-12-63 | CHAINSAW | CANNON MOUNTING BAR, LOG WIZARD, H1 Mount, 12 Inches, .063 Gauge, 0.375 Pitch, Check Owners Manual for Drive Links | |
| CLW-S1-12-50 | CHAINSAW | CANNON MOUNTING BAR, LOG WIZARD, S1 Mount, 12 Inches, .050 Gauge, 0.375 Pitch, Check Owners Manual for Drive Links | |
| CLW-S1-12-58 | CHAINSAW | CANNON MOUNTING BAR, LOG WIZARD, S1 Mount, 12 Inches, .058 Gauge, 0.375 Pitch, Check Owners Manual for Drive Links | |
| CLW-S1-12-63 | CHAINSAW | CANNON MOUNTING BAR, LOG WIZARD, S1 Mount, 12 Inches, .063 Gauge, 0.375 Pitch, Check Owners Manual for Drive Links | |
| CLW-S1-24-50 | CHAINSAW | CANNON MOUNTING BAR, LOG WIZARD, S1 Mount, 24 Inches, .050 Gauge, 0.375 Pitch, Check Owners Manual for Drive Links | |
| CLW-S1-24-58 | CHAINSAW | CANNON MOUNTING BAR, LOG WIZARD, S1 Mount, 24 Inches, .058 Gauge, 0.375 Pitch, Check Owners Manual for Drive Links | |
| CLW-S1-24-63 | CHAINSAW | CANNON MOUNTING BAR, LOG WIZARD, S1 Mount, 24 Inches, .063 Gauge, 0.375 Pitch, Check Owners Manual for Drive Links | |
| CPB-E1-84-80 | CHAINSAW | CANNON PACKAGE BAR, DOUBLE ENDED, E1 Mount, 84 Inches, .080 Gauge, 0.404 Pitch, Check Owners Manual for Drive Links | |
| CPB-E2-108-63 | CHAINSAW | CANNON PACKAGE BAR, DOUBLE ENDED, E2 Mount, 108 Inches, .063 Gauge, 0.404 Pitch, Check Owners Manual for Drive Links | |
| CPB-E2-60-63 | CHAINSAW | CANNON PACKAGE BAR, DOUBLE ENDED, E2 Mount, 60 Inches, .063 Gauge, 0.404 Pitch, Check Owners Manual for Drive Links | |
| CPB-E2-60-80 | CHAINSAW | CANNON PACKAGE BAR, DOUBLE ENDED, E2 Mount, 60 Inches, .080 Gauge, 0.404 Pitch, Check Owners Manual for Drive Links | |
| CPB-E2-72-63 | CHAINSAW | CANNON PACKAGE BAR, DOUBLE ENDED, E2 Mount, 72 Inches, .063 Gauge, 0.404 Pitch, Check Owners Manual for Drive Links | |
| CPB-E2-72-80 | CHAINSAW | CANNON PACKAGE BAR, DOUBLE ENDED, E2 Mount, 72 Inches, .080 Gauge, 0.404 Pitch, Check Owners Manual for Drive Links | |
| CPB-E2-84-63 | CHAINSAW | CANNON PACKAGE BAR, DOUBLE ENDED, E2 Mount, 84 Inches, .063 Gauge, 0.404 Pitch, Check Owners Manual for Drive Links | |
| CPB-E2-84-80 | CHAINSAW | CANNON PACKAGE BAR, DOUBLE ENDED, E2 Mount, 84 Inches, .080 Gauge, 0.404 Pitch, Check Owners Manual for Drive Links | |
| CPB-E2-96-63 | CHAINSAW | CANNON PACKAGE BAR, DOUBLE ENDED, E2 Mount, 96 Inches, .063 Gauge, 0.404 Pitch, Check Owners Manual for Drive Links | |
| CPB-E2-96-80 | CHAINSAW | CANNON PACKAGE BAR, DOUBLE ENDED, E2 Mount, 96 Inches, .080 Gauge, 0.404 Pitch, Check Owners Manual for Drive Links | |
| CPB-HT-60-63 | CHAINSAW | CANNON PACKAGE BAR, DOUBLE ENDED, HT Mount, 60 Inches, .063 Gauge, 0.404 Pitch, Check Owners Manual for Drive Links | |
| CPB-HT-60-80 | CHAINSAW | CANNON PACKAGE BAR, DOUBLE ENDED, HT Mount, 60 Inches, .080 Gauge, 0.404 Pitch, Check Owners Manual for Drive Links | |
| CPB-HT-72-63 | CHAINSAW | CANNON PACKAGE BAR, DOUBLE ENDED, HT Mount, 72 Inches, .063 Gauge

| | | | |
|---|---|---|---|
| CPB-M3-80-63 | CHAINSAW | CANNON PACKAGE BAR, DOUBLE ENDED, M3 Mount, 80 Inches, .063 Gauge, 0.404 Pitch, Check Owners Manual for Drive Links | |
| CPB-M3-80-80 | CHAINSAW | CANNON PACKAGE BAR, DOUBLE ENDED, M3 Mount, 80 Inches, .080 Gauge, 0.404 Pitch, Check Owners Manual for Drive Links | |
| CPB-M4-64-63 | CHAINSAW | CANNON PACKAGE BAR, DOUBLE ENDED, M4 Mount, 64 Inches, .063 Gauge, 0.404 Pitch, Check Owners Manual for Drive Links | |
| CPB-PU-83-63 | CHAINSAW | CANNON PACKAGE BAR, DOUBLE ENDED, PU Mount, 83 Inches, .063 Gauge, 0.404 Pitch, Check Owners Manual for Drive Links | |
| CPB-PU-83-80 | CHAINSAW | CANNON PACKAGE BAR, DOUBLE ENDED, PU Mount, 83 Inches, .080 Gauge, 0.404 Pitch, Check Owners Manual for Drive Links | |
| CPB-RT-66-63 | CHAINSAW | CANNON PACKAGE BAR, DOUBLE ENDED, RT Mount, 66 Inches, .063 Gauge, 0.404 Pitch, Check Owners Manual for Drive Links | |
| CPB-RT-66-80 | CHAINSAW | CANNON PACKAGE BAR, DOUBLE ENDED, RT Mount, 66 Inches, .080 Gauge, 0.404 Pitch, Check Owners Manual for Drive Links | |
| CPB-RT-76-63 | CHAINSAW | CANNON PACKAGE BAR, DOUBLE ENDED, RT Mount, 76 Inches, .063 Gauge, 0.404 Pitch, Check Owners Manual for Drive Links | |
| CPB-RT-76-80 | CHAINSAW | CANNON PACKAGE BAR, DOUBLE ENDED, RT Mount, 76 Inches, .080 Gauge, 0.404 Pitch, Check Owners Manual for Drive Links | |
| CPB-S9-59-80 | CHAINSAW | CANNON PACKAGE BAR, DOUBLE ENDED, S9 Mount, 59 Inches, .080 Gauge, 0.404 Pitch, Check Owners Manual for Drive Links | |
| CPB-T1-83-63 | CHAINSAW | CANNON PACKAGE BAR, DOUBLE ENDED, T1 Mount, 83 Inches, .063 Gauge, 0.404 Pitch, Check Owners Manual for Drive Links | |
| CPK-E10-57-12 | CHAINSAW | CANNON PACKAGE BAR, DOUBLE ENDED, E10 Mount, 57 Inches, .122 Gauge, 0.750 Pitch, Check Owners Manual for Drive Links | |
| CPK-E2-60-12 | CHAINSAW | CANNON PACKAGE BAR, DOUBLE ENDED, E2 Mount, 60 Inches, .122 Gauge, 0.750 Pitch, Check Owners Manual for Drive Links | |
| CPK-E2-72-12 | CHAINSAW | CANNON PACKAGE BAR, DOUBLE ENDED, E2 Mount, 72 Inches, .122 Gauge, 0.750 Pitch, Check Owners Manual for Drive Links | |
| CPK-E2-84-12 | CHAINSAW | CANNON PACKAGE BAR, DOUBLE ENDED, E2 Mount, 84 Inches, .122 Gauge, 0.750 Pitch, Check Owners Manual for Drive Links | |
| CPK-E2-96-12 | CHAINSAW | CANNON PACKAGE BAR, DOUBLE ENDED, E2 Mount, 96 Inches, .122 Gauge, 0.750 Pitch, Check Owners Manual for Drive Links | |
| CPK-HT-60-118 | CHAINSAW | CANNON PACKAGE BAR, DOUBLE ENDED, HT Mount, 60 Inches, .118 Gauge, 0.750 Pitch, Check Owners Manual for Drive Links | |
| CPK-HT-60-12 | CHAINSAW | CANNON PACKAGE BAR, DOUBLE ENDED, HT Mount, 60 Inches, .122 Gauge, 0.750 Pitch, Check Owners Manual for Drive Links | |
| CPK-HT-72-118 | CHAINSAW | CANNON PACKAGE BAR, DOUBLE ENDED, HT Mount, 72 Inches, .118 Gauge, 0.750 Pitch, Check Owners Manual for Drive Links | |
| CPK-HT-72-12 | CHAINSAW | CANNON PACKAGE BAR, DOUBLE ENDED, HT Mount, 72 Inches, .122 Gauge, 0.750 Pitch, Check Owners Manual for Drive Links | |
| CPK-HT-84-118 | CHAINSAW | CANNON PACKAGE BAR, DOUBLE ENDED, HT Mount, 84 Inches, .118 Gauge, 0.750 Pitch, Check Owners Manual for Drive Links | |
| CPK-HT-84-12 | CHAINSAW | CANNON PACKAGE BAR, DOUBLE ENDED, HT Mount, 84 Inches, .122 Gauge, 0.750 Pitch, Check Owners Manual for Drive Links | |
| CPK-SP-84-12 | CHAINSAW | CANNON PACKAGE BAR, DOUBLE ENDED, SP Mount, 84 Inches, .122 Gauge, 0.750 Pitch, Check Owners Manual for Drive Links | |
| CPP-C1-12-43 | CHAINSAW | CANNON PRUNING BAR, C1 Mount, 12 Inches, .043 Gauge (0.250 Pitch = 61 Drive Links, 0.325 Pitch = 47 Drive Links, 0.375/0.370 Pitch (Low Profile) = 42 Drive Links) | Cobalt Hard Nose Tip |
| CPP-C1-12-50 | CHAINSAW | CANNON PRUNING BAR, C1 Mount, 12 Inches, .050 Gauge (0.250 Pitch = 61 Drive Links, 0.325 Pitch = 47 Drive Links, 0.375/0.370 Pitch (Low Profile) = 42 Drive Links) | Cobalt Hard Nose Tip |
| CPP-H8-10-43 | CHAINSAW | CANNON PRUNING BAR, H8 Mount, 10 Inches, .043 Gauge (0.250 Pitch = 58 Drive Links, 0.375/0.370 Pitch (Low Profile) = 40 Drive Links) | Cobalt Hard Nose Tip |
| CPP-H8-10-50 | CHAINSAW | CANNON PRUNING BAR, H8 Mount, 10 Inches, .050 Gauge (0.250 Pitch = 58 Drive Links, 0.375/0.370 Pitch (Low Profile) = 40 Drive Links) | Cobalt Hard Nose Tip |
| CPP-H8-12-43 | CHAINSAW | CANNON PRUNING BAR, H8 Mount, 12 Inches, .043 Gauge (0.250 Pitch = 66 Drive Links, 0.375/0.370 Pitch (Low Profile) = 44 Drive Links) | Cobalt Hard Nose Tip |
| CPP-H8-12-50 | CHAINSAW | CANNON PRUNING BAR, H8 Mount, 12 Inches, .050 Gauge (0.250 Pitch = 66 Drive Links, 0.375/0.370 Pitch (Low Profile) = 44 Drive Links) | Cobalt Hard Nose Tip |
| CPP-P5-10-43 | CHAINSAW | CANNON PRUNING BAR, P5 Mount, 10 Inches, .043 Gauge (0.250 Pitch = 56 Drive Links, 0.375/0.370 Pitch (Low Profile) = 39 Drive Links) | Cobalt Hard Nose Tip |
| CPP-P5-10-50 | CHAINSAW | CANNON PRUNING BAR, P5 Mount, 10 Inches, .050 Gauge (0.250 Pitch = 56 Drive Links, 0.375/0.370 Pitch (Low Profile) = 39 Drive Links) | Cobalt Hard Nose Tip |
| CPP-P5-12-43 | CHAINSAW | CANNON PRUNING BAR, P5 Mount, 12 Inches, .043 Gauge (0.250 Pitch = 66 Drive Links, 0.375/0.370 Pitch (Low Profile) = 44 Drive Links) | Cobalt Hard Nose Tip |
| CPP-P5-12-50 | CHAINSAW | CANNON PRUNING BAR, P5 Mount, 12 Inches, .050 Gauge (0.250 Pitch = 66 Drive Links, 0.375/0.370 Pitch (Low Profile) = 44 Drive Links) | Cobalt Hard Nose Tip |
| CPP-S5-10-43 | CHAINSAW | CANNON PRUNING BAR, S5 Mount, 10 Inches, .043 Gauge (0.250 Pitch = 56 Drive Links, 0.375/0.370 Pitch (Low Profile) = 39 Drive Links) | Cobalt Hard Nose Tip |
| CPP-S5-10-50 | CHAINSAW | CANNON PRUNING BAR, S5 Mount, 10 Inches, .050 Gauge (0.250 Pitch = 56 Drive Links, 0.375/0.370 Pitch (Low Profile) = 39 Drive Links) | Cobalt Hard Nose Tip |
| CPP-S5-12-43 | CHAINSAW | CANNON PRUNING BAR, S5 Mount, 12 Inches, .043 Gauge (0.250 Pitch = 66 Drive Links, 0.375/0.370 Pitch (Low Profile) = 44 Drive Links) | Cobalt Hard Nose Tip |
| CPP-S5-12-50 | CHAINSAW | CANNON PRUNING BAR, S5 Mount, 12 Inches, .050 Gauge (0.250 Pitch = 66 Drive Links, 0.375/0.370 Pitch (Low Profile) = 44 Drive Links) | Cobalt Hard Nose Tip |
| CCE-H1-12-63-4 | CHAINSAW | CANNON RESCUE BAR, CUTTERS EDGE, H1 Mount, 12 Inches, .063 Gauge, 0.404 Pitch, 48 Drive Links | Replaceable Sprocket Nose |
| CCE-H1-16-63-4 | CHAINSAW | CANNON RESCUE BAR, CUTTERS EDGE, H1 Mount, 16 Inches, .063 Gauge, 0.404 Pitch, 56 Drive Links | Replaceable Sprocket Nose |
| CCE-H1-20-63-4 | CHAINSAW | CANNON RESCUE BAR, CUTTERS EDGE, H1 Mount, 20 Inches, .063 Gauge, 0.404 Pitch, 66 Drive Links | Replaceable Sprocket Nose |
| CFB-P1-15-63 | CHAINSAW | CANNON RESCUE BAR, POULAN, P1 Mount, 15 Inches, .063 Gauge, 0.375 or .404 Pitch, Check Owners Manual for Drive Links | Cobalt Hard Nose Tip |
| CFB-P4-15-63-3-E | CHAINSAW | CANNON RESCUE BAR, ECHO, P4 Mount, 15 Inches, .063 Gauge, 0.375 Pitch, Check Owners Manual for Drive Links | Embedded Tip |
| CFB-S1-15-63 | CHAINSAW | CANNON RESCUE BAR, STIHL, S1 Mount, 15 Inches, .063 Gauge, 0.375 or .404 Pitch, Check Owners Manual for Drive Links | Cobalt Hard Nose Tip |
| CRS-S1-20-63-3 | CHAINSAW | CANNON RESCUE BAR, STIHL, S1 Mount, 20 Inches, .063 Gauge, 0.375 Pitch, 72 Drive Links | Replaceable Sprocket Nose |
| CRS-S1-20-63-4 | CHAINSAW | CANNON RESCUE BAR, STIHL, S1 Mount, 20 Inches, .063 Gauge, 0.404 Pitch, 65 Drive Links | Replaceable Sprocket Nose |
| CRS-S1-20-63-H | CHAINSAW | CANNON RESCUE BAR, STIHL, S1 Mount, 20 Inches, .063 Gauge (0.375 Pitch = 72 Drive Links, 0.404 Pitch = 65 Drive Links) | Replaceable Hard Nose |
| CSB-C1-12-50-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, C1 Mount, 12 Inches, .050 Gauge (0.325 Pitch = 56 Drive Links, 0.375 Pitch = 49 Drive Links, 0.404 Pitch = 44 Drive Links) | |
| CSB-C1-12-58-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, C1 Mount, 12 Inches, .058 Gauge (0.325 Pitch = 56 Drive Links, 0.375 Pitch = 49 Drive Links, 0.404 Pitch = 44 Drive Links) | |
| CSB-C1-12-63-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, C1 Mount, 12 Inches, .063 Gauge (0.325 Pitch = 56 Drive Links, 0.375 Pitch = 49 Drive Links, 0.404 Pitch = 44 Drive Links) | |
| CSB-C1-15-50-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, C1 Mount, 15 Inches, .050 Gauge (0.325 Pitch = 64 Drive Links, 0.375 Pitch = 56 Drive Links, 0.404 Pitch = 51 Drive Links) | |
| CSB-C1-15-58-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, C1 Mount, 15 Inches, .058 Gauge (0.325 Pitch = 64 Drive Links, 0.375 Pitch = 56 Drive Links, 0.404 Pitch = 51 Drive Links) | |
| CSB-C1-15-63-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, C1 Mount, 15 Inches, .063 Gauge (0.325 Pitch = 64 Drive Links, 0.375 Pitch = 56 Drive Links, 0.404 Pitch = 51 Drive Links) | |
| CSB-C1-16-50-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, C1 Mount, 16 Inches, .050 Gauge (0.325 Pitch = 68 Drive Links, 0.375 Pitch = 60 Drive Links, 0.404 Pitch = 55 Drive Links) | |
| CSB-C1-16-58-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, C1 Mount, 16 Inches, .058 Gauge (0.325 Pitch = 68 Drive Links, 0.375 Pitch = 60 Drive Links, 0.404 Pitch = 55 Drive Links) | |
| CSB-C1-16-63-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, C1 Mount, 16 Inches, .063 Gauge (0.325 Pitch = 68 Drive Links, 0.375 Pitch = 60 Drive Links, 0.404 Pitch = 55 Drive Links) | |
| CSB-C1-18-50-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, C1 Mount, 18 Inches, .050 Gauge (0.325 Pitch = 77 Drive Links, 0.375 Pitch = 68 Drive Links, 0.404 Pitch = 62 Drive Links) | |
| CSB-C1-18-58-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, C1 Mount, 18 Inches, .058 Gauge (0.325 Pitch = 77 Drive Links, 0.375 Pitch = 68 Drive Links, 0.404 Pitch = 62 Drive Links) | |
| CSB-C1-18-63-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, C1 Mount, 18 Inches, .063 Gauge (0.325 Pitch = 77 Drive Links, 0.375 Pitch = 68 Drive Links, 0.404 Pitch = 62 Drive Links) | |
| CSB-C1-20-50-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, C1 Mount, 20 Inches, .050 Gauge (0.325 Pitch = 81 Drive Links, 0.375 Pitch = 72 Drive Links, 0.404 Pitch = 66 Drive Links) | |
| CSB-C1-20-58-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, C1 Mount, 20 Inches, .058 Gauge (0.325 Pitch = 81 Drive Links, 0.375 Pitch = 72 Drive Links, 0.404 Pitch = 66 Drive Links) | |
| CSB-C1-20-63-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, C1 Mount, 20 Inches, .063 Gauge (0.325 Pitch = 81 Drive Links, 0.375 Pitch = 72 Drive Links, 0.404 Pitch = 66 Drive Links) | |
| CSB-C1-24-50-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, C1 Mount, 24 Inches, .050 Gauge (0.325 Pitch = 95 Drive Links, 0.375 Pitch = 84 Drive Links, 0.404 Pitch = 76 Drive Links) | |
| CSB-C1-24-58-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, C1 Mount, 24 Inches, .058 Gauge (0.325 Pitch = 95 Drive Links, 0.375 Pitch = 84 Drive Links, 0.404 Pitch = 76 Drive Links) | |
| CSB-C1-24-63-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, C1 Mount, 24 Inches, .063 Gauge (0.325 Pitch = 95 Drive Links, 0.375 Pitch = 84 Drive Links, 0.404 Pitch = 76 Drive Links) | |
| CSB-H1-12-50-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, H1 Mount, 12 Inches, .050 Gauge (0.325 Pitch = 56 Drive Links, 0.375 Pitch = 49 Drive Links, 0.404 Pitch = 44 Drive Links) | |
| CSB-H1-12-58-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, H1 Mount, 12 Inches, .058 Gauge (0.325 Pitch = 56 Drive Links, 0.375 Pitch = 49 Drive Links, 0.404 Pitch = 44 Drive Links) | |
| CSB-H1-12-63-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, H1 Mount, 12 Inches, .063 Gauge (0.325 Pitch = 56 Drive Links, 0.375 Pitch = 49 Drive Links, 0.404 Pitch = 44 Drive Links) | |
| CSB-H1-15-50-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, H1 Mount, 15 Inches, .050 Gauge (0.325 Pitch = 64 Drive Links, 0.375 Pitch = 56 Drive Links, 0.404 Pitch = 51 Drive Links) | |
| CSB-H1-15-58-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, H1 Mount, 15 Inches, .058 Gauge (0.325 Pitch = 64 Drive Links, 0.375 Pitch = 56 Drive Links, 0.404 Pitch = 51 Drive Links) | |
| CSB-H1-15-63-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, H1 Mount, 15 Inches, .063 Gauge (0.325 Pitch = 64 Drive Links, 0.375 Pitch = 56 Drive Links, 0.404 Pitch = 51 Drive Links) | |
| CSB-H1-16-50-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, H1 Mount, 16 Inches, .050 Gauge (0.325 Pitch = 68 Drive Links, 0.375 Pitch = 60 Drive Links, 0.404 Pitch = 55 Drive Links) | |
| CSB-H1-16-58-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, H1 Mount, 16 Inches, .058 Gauge (0.325 Pitch = 68 Drive Links, 0.375 Pitch = 60 Drive Links, 0.404 Pitch = 55 Drive Links) | |
| CSB-H1-16-63-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, H1 Mount, 16 Inches, .063 Gauge (0.325 Pitch = 68 Drive Links, 0.375 Pitch = 60 Drive Links, 0.404 Pitch = 55 Drive Links) | |
| CSB-H1-17-50-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, H1 Mount, 17 Inches, .050 Gauge (0.325 Pitch = 72 Drive Links, 0.375 Pitch = 64 Drive Links, 0.404 Pitch = 58 Drive Links) | |
| CSB-H1-17-58-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, H1 Mount, 17 Inches, .058 Gauge (0.325 Pitch = 72 Drive Links, 0.375 Pitch = 64 Drive Links, 0.404 Pitch = 58 Drive Links) | |
| CSB-H1-17-63-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, H1 Mount, 17 Inches, .063 Gauge (0.325 Pitch = 72 Drive Links, 0.375 Pitch = 64 Drive Links, 0.404 Pitch = 58 Drive Links) | |
| CSB-H1-18-50-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, H1 Mount, 18 Inches, .050 Gauge (0.325 Pitch = 77 Drive Links, 0.375 Pitch = 68 Drive Links, 0.404 Pitch = 62 Drive Links) | |
| CSB-H1-18-58-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, H1 Mount, 18 Inches, .058 Gauge (0.325 Pitch = 77 Drive Links, 0.375 Pitch = 68 Drive Links, 0.404 Pitch = 62 Drive Links) | |
| CSB-H1-18-63-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, H1 Mount, 18 Inches, .063 Gauge (0.325 Pitch = 77 Drive Links, 0.375 Pitch = 68 Drive Links, 0.404 Pitch = 62 Drive Links) | |
| CSB-H1-20-50-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, H1 Mount, 20 Inches, .050 Gauge (0.325 Pitch = 81 Drive Links, 0.375 Pitch = 72 Drive Links, 0.404 Pitch = 66 Drive Links) | |
| CSB-H1-20-58-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, H1 Mount, 20 Inches, .058 Gauge (0.325 Pitch = 81 Drive Links, 0.375 Pitch = 72 Drive Links, 0.404 Pitch = 66 Drive Links) | |
| CSB-H1-20-63-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, H1 Mount, 20 Inches, .063 Gauge (0.325 Pitch = 81 Drive Links, 0.375 Pitch = 72 Drive Links, 0.404 Pitch = 66 Drive Links) | |
| CSB-H1-22-50-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, H1 Mount, 22 Inches, .050 Gauge (0.325 Pitch = 86 Drive Links, 0.375 Pitch = 76 Drive Links, 0.404 Pitch = 69 Drive Links) | |
| CSB-H1-22-58-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, H1 Mount, 22 Inches, .058 Gauge (0.325 Pitch = 86 Drive Links, 0.375 Pitch = 76 Drive Links, 0.404 Pitch = 69 Drive Links) | |
| CSB-H1-22-63-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, H1 Mount, 22 Inches, .063 Gauge (0.325 Pitch = 86 Drive Links, 0.375 Pitch = 76 Drive Links, 0.404 Pitch = 69 Drive Links) | |
| CSB-H1-24-50-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, H1 Mount, 24 Inches, .050 Gauge (0.325 Pitch = 95 Drive Links, 0.375 Pitch = 84 Drive Links, 0.404 Pitch = 76 Drive Links) | |
| CSB-H1-24-58-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, H1 Mount, 24 Inches, .058 Gauge (0.325 Pitch = 95 Drive Links, 0.375 Pitch = 84 Drive Links, 0.404 Pitch = 76 Drive Links) | |
| CSB-H1-24-63-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, H1 Mount, 24 Inches, .063 Gauge (0.325 Pitch = 95 Drive Links, 0.375 Pitch = 84 Drive Links, 0.404 Pitch = 76 Drive Links) | |
| CSB-H1-26-50-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, H1 Mount, 26 Inches, .050 Gauge (0.325 Pitch = 101 Drive Links, 0.375 Pitch = 89 Drive Links, 0.404 Pitch = 81 Drive Links) | |
| CSB-H1-26-58-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, H1 Mount, 26 Inches, .058 Gauge (0.325 Pitch = 101 Drive Links, 0.375 Pitch = 89 Drive Links, 0.404 Pitch = 81 Drive Links) | |
| CSB-H1-26-63-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, H1 Mount, 26 Inches, .063 Gauge (0.325 Pitch = 101 Drive Links, 0.375 Pitch = 89 Drive Links, 0.404 Pitch = 81 Drive Links) | |
| CSB-H1-28-50-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, H1 Mount, 28 Inches, .050 Gauge (0.325 Pitch = 105 Drive Links, 0.375 Pitch = 93 Drive Links, 0.404 Pitch = 85 Drive Links) | |
| CSB-H1-28-58-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, H1 Mount, 28 Inches, .058 Gauge (0.325 Pitch = 105 Drive Links, 0.375 Pitch = 93 Drive Links, 0.404 Pitch = 85 Drive Links) | |
| CSB-H1-28-63-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, H1 Mount, 28 Inches, .063 Gauge (0.325 Pitch = 105 Drive Links, 0.375 Pitch = 93 Drive Links, 0.404 Pitch = 85 Drive Links) | |
| CSB-H1-30-50-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, H1 Mount, 30 Inches, .050 Gauge (0.325 Pitch = 115 Drive Links, 0.375 Pitch = 102 Drive Links, 0.404 Pitch = 92 Drive Links) | |
| CSB-H1-30-58-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, H1 Mount, 30 Inches, .058 Gauge (0.325 Pitch = 115 Drive Links, 0.375 Pitch = 102 Drive Links, 0.404 Pitch = 92 Drive Links) | |
| CSB-H1-30-63-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, H1 Mount, 30 Inches, .063 Gauge (0.325 Pitch = 115 Drive Links, 0.375 Pitch = 102 Drive Links, 0.404 Pitch = 92 Drive Links) | |
| CSB-H1-32-50-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, H1 Mount, 32 Inches, .050 Gauge (0.325 Pitch = 119 Drive Links, 0.375 Pitch = 105 Drive Links, 0.404 Pitch = 95 Drive Links) | |
| CSB-H1-32-58-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, H1 Mount, 32 Inches, .058 Gauge (0.325 Pitch = 119 Drive Links, 0.375 Pitch = 105 Drive Links, 0.404 Pitch = 95 Drive Links) | |
| CSB-H1-32-63-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, H1 Mount, 32 Inches, .063 Gauge (0.325 Pitch = 119 Drive Links, 0.375 Pitch = 105 Drive Links, 0.404 Pitch = 95 Drive Links) | |
| CSB-H1-33-50-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, H1 Mount, 33 Inches, .050 Gauge (0.325 Pitch = 125 Drive Links, 0.375 Pitch = 110 Drive Links, 0.404 Pitch = 100 Drive Links) | |
| CSB-H1-33-58-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, H1 Mount, 33 Inches, .058 Gauge (0.325 Pitch = 125 Drive Links, 0.375 Pitch = 110 Drive Links, 0.404 Pitch = 100 Drive Links) | |
| CSB-H1-33-63-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, H1 Mount, 33 Inches, .063 Gauge (0.325 Pitch = 125 Drive Links, 0.375 Pitch = 110 Drive Links, 0.404 Pitch = 100 Drive Links) | |
| CSB-H1-34-50-H | | ORDER AS CSB-H1-33-50-H (SAME BAR) | |
| CSB-H1-34-58-H | | ORDER AS CSB-H1-33-58-H (SAME BAR) | |
| CSB-H1-34-63-H | | ORDER AS CSB-H1-33-63-H (SAME BAR) | |
| CSB-H1-36-50-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, H1 Mount, 36 Inches, .050 Gauge (0.325 Pitch = 130 Drive Links, 0.375 Pitch = 115 Drive Links, 0.404 Pitch = 104 Drive Links) | |
| CSB-H1-36-58-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, H1 Mount, 36 Inches, .058 Gauge (0.325 Pitch = 130 Drive Links, 0.375 Pitch = 115 Drive Links, 0.404 Pitch = 104 Drive Links) | |
| CSB-H1-36-63-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, H1 Mount, 36 Inches, .063 Gauge (0.325 Pitch = 130 Drive Links, 0.375 Pitch = 115 Drive Links, 0.404 Pitch = 104 Drive Links) | |
| CSB-H1-37-50-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, H1 Mount, 37 Inches, .050 Gauge (0.325 Pitch = 135 Drive Links, 0.375 Pitch = 119 Drive Links, 0.404 Pitch = 108 Drive Links) | |
| CSB-H1-37-58-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, H1 Mount, 37 Inches, .058 Gauge (0.325 Pitch = 135 Drive Links, 0.375 Pitch = 119 Drive Links, 0.404 Pitch = 108 Drive Links) | |
| CSB-H1-37-63-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, H1 Mount, 37 Inches, .063 Gauge (0.325 Pitch = 135 Drive Links, 0.375 Pitch = 119 Drive Links, 0.404 Pitch = 108 Drive Links) | |
| CSB-H1-42-50-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, H1 Mount, 42 Inches, .050 Gauge (0.325 Pitch = 153 Drive Links, 0.375 Pitch = 135 Drive Links, 0.404 Pitch = 122 Drive Links) | |
| CSB-H1-42-58-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, H1 Mount, 42 Inches, .058 Gauge (0.325 Pitch = 153 Drive Links, 0.375 Pitch = 135 Drive Links, 0.404 Pitch = 122 Drive Links) | |
| CSB-H1-42-63-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, H1 Mount, 42 Inches, .063 Gauge (0.325 Pitch = 153 Drive Links, 0.375 Pitch = 135 Drive Links, 0.404 Pitch = 122 Drive Links) | |
| CSB-H1-50-50-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, H1 Mount, 50 Inches, .050 Gauge (0.325 Pitch = 177 Drive Links, 0.375 Pitch = 156 Drive Links, 0.404 Pitch = 142 Drive Links) | |
| CSB-H1-50-58-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, H1 Mount, 50 Inches, .058 Gauge (0.325 Pitch = 177 Drive Links, 0.375 Pitch = 156 Drive Links, 0.404 Pitch = 142 Drive Links) | |
| CSB-H1-50-63-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, H1 Mount, 50 Inches, .063 Gauge (0.325 Pitch = 177 Drive Links, 0.375 Pitch = 156 Drive Links, 0.404 Pitch = 142 Drive Links) | |
| CSB-H1-60-50-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, H1 Mount, 60 Inches, .050 Gauge (0.325 Pitch = 209 Drive Links, 0.375 Pitch = 185 Drive Links, 0.404 Pitch = 167 Drive Links) | |
| CSB-H1-60-58-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, H1 Mount, 60 Inches, .058 Gauge (0.325 Pitch = 209 Drive Links, 0.375 Pitch = 185 Drive Links, 0.404 Pitch = 167 Drive Links) | |
| CSB-H1-60-63-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, H1 Mount, 60 Inches, .063 Gauge (0.325 Pitch = 209 Drive Links, 0.375 Pitch = 185 Drive Links, 0.404 Pitch = 167 Drive Links) | |
| CSB-H1-72-50-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, H1 Mount, 72 Inches, .050 Gauge (0.325 Pitch = 247 Drive Links, 0.375 Pitch = 218 Drive Links, 0.404 Pitch = 196 Drive Links) | |
| CSB-H1-72-58-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, H1 Mount, 72 Inches, .058 Gauge (0.325 Pitch = 247 Drive Links, 0.375 Pitch = 218 Drive Links, 0.404 Pitch = 196 Drive Links) | |
| CSB-H1-72-63-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, H1 Mount, 72 Inches, .063 Gauge (0.325 Pitch = 247 Drive Links, 0.375 Pitch = 218 Drive Links, 0.404 Pitch = 196 Drive Links) | |
| CSB-H1-84-50-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, H1 Mount, 84 Inches, .050 Gauge (0.325 Pitch = 281 Drive Links, 0.375 Pitch = 249 Drive Links, 0.404 Pitch = 226 Drive Links) | |
| CSB-H1-84-58-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, H1 Mount, 84 Inches, .058 Gauge (0.325 Pitch = 281 Drive Links, 0.375 Pitch = 249 Drive Links, 0.404 Pitch = 226 Drive Links) | |
| CSB-H1-84-63-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, H1 Mount, 84 Inches, .063 Gauge (0.325 Pitch = 281 Drive Links, 0.375 Pitch = 249 Drive Links, 0.404 Pitch = 226 Drive Links) | |
| CSB-P4-16-50-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, P4 Mount, 16 Inches, .050 Gauge (0.325 Pitch = 68 Drive Links, 0.375 Pitch = 60 Drive Links, 0.404 Pitch = 55 Drive Links) | |
| CSB-P4-16-58-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, P4 Mount, 16 Inches, .058 Gauge (0.325 Pitch = 68 Drive Links, 0.375 Pitch = 60 Drive Links, 0.404 Pitch = 55 Drive Links) | |
| CSB-P4-16-63-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, P4 Mount, 16 Inches, .063 Gauge (0.325 Pitch = 68 Drive Links, 0.375 Pitch = 60 Drive Links, 0.404 Pitch = 55 Drive Links) | |
| CSB-P4-20-50-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, P4 Mount, 20 Inches, .050 Gauge (0.325 Pitch = 79 Drive Links, 0.375 Pitch = 70 Drive Links, 0.404 Pitch = 64 Drive Links) | |
| CSB-P4-20-58-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, P4 Mount, 20 Inches, .058 Gauge (0.325 Pitch = 79 Drive Links, 0.375 Pitch = 70 Drive Links, 0.404 Pitch = 64 Drive Links) | |
| CSB-P4-20-63-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, P4 Mount, 20 Inches, .063 Gauge (0.325 Pitch = 79 Drive Links, 0.375 Pitch = 70 Drive Links, 0.404 Pitch = 64 Drive Links) | |
| CSB-P

| | | |
|---|---|---|
| CSB-P4-28-63-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, P4 Mount, 28 Inches, .063 Gauge (0.325 Pitch = 105 Drive Links, 0.375 Pitch = 93 Drive Links, 0.404 Pitch = 84 Drive Links) |
| CSB-P4-32-50-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, P4 Mount, 32 Inches, .050 Gauge (0.325 Pitch = 119 Drive Links, 0.375 Pitch = 105 Drive Links, 0.404 Pitch = 95 Drive Links) |
| CSB-P4-32-58-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, P4 Mount, 32 Inches, .058 Gauge (0.325 Pitch = 119 Drive Links, 0.375 Pitch = 105 Drive Links, 0.404 Pitch = 95 Drive Links) |
| CSB-P4-32-63-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, P4 Mount, 32 Inches, .063 Gauge (0.325 Pitch = 119 Drive Links, 0.375 Pitch = 105 Drive Links, 0.404 Pitch = 95 Drive Links) |
| CSB-S1-12-50-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, S1 Mount, 12 Inches, .050 Gauge (0.325 Pitch = 56 Drive Links, 0.375 Pitch = 49 Drive Links, 0.404 Pitch = 44 Drive Links) |
| CSB-S1-12-58-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, S1 Mount, 12 Inches, .058 Gauge (0.325 Pitch = 56 Drive Links, 0.375 Pitch = 49 Drive Links, 0.404 Pitch = 44 Drive Links) |
| CSB-S1-12-63-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, S1 Mount, 12 Inches, .063 Gauge (0.325 Pitch = 56 Drive Links, 0.375 Pitch = 49 Drive Links, 0.404 Pitch = 44 Drive Links) |
| CSB-S1-16-50-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, S1 Mount, 16 Inches, .050 Gauge (0.325 Pitch = 67 Drive Links, 0.375 Pitch = 60 Drive Links, 0.404 Pitch = 55 Drive Links) |
| CSB-S1-16-58-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, S1 Mount, 16 Inches, .058 Gauge (0.325 Pitch = 67 Drive Links, 0.375 Pitch = 60 Drive Links, 0.404 Pitch = 55 Drive Links) |
| CSB-S1-16-63-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, S1 Mount, 16 Inches, .063 Gauge (0.325 Pitch = 67 Drive Links, 0.375 Pitch = 60 Drive Links, 0.404 Pitch = 55 Drive Links) |
| CSB-S1-18-50-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, S1 Mount, 18 Inches, .050 Gauge (0.325 Pitch = 74 Drive Links, 0.375 Pitch = 66 Drive Links, 0.404 Pitch = 60 Drive Links) |
| CSB-S1-18-58-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, S1 Mount, 18 Inches, .058 Gauge (0.325 Pitch = 74 Drive Links, 0.375 Pitch = 66 Drive Links, 0.404 Pitch = 60 Drive Links) |
| CSB-S1-18-63-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, S1 Mount, 18 Inches, .063 Gauge (0.325 Pitch = 74 Drive Links, 0.375 Pitch = 66 Drive Links, 0.404 Pitch = 60 Drive Links) |
| CSB-S1-20-50-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, S1 Mount, 20 Inches, .050 Gauge (0.325 Pitch = 81 Drive Links, 0.375 Pitch = 72 Drive Links, 0.404 Pitch = 66 Drive Links) |
| CSB-S1-20-58-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, S1 Mount, 20 Inches, .058 Gauge (0.325 Pitch = 81 Drive Links, 0.375 Pitch = 72 Drive Links, 0.404 Pitch = 66 Drive Links) |
| CSB-S1-20-63-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, S1 Mount, 20 Inches, .063 Gauge (0.325 Pitch = 81 Drive Links, 0.375 Pitch = 72 Drive Links, 0.404 Pitch = 66 Drive Links) |
| CSB-S1-22-50-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, S1 Mount, 22 Inches, .050 Gauge (0.325 Pitch = 87 Drive Links, 0.375 Pitch = 77 Drive Links, 0.404 Pitch = 70 Drive Links) |
| CSB-S1-22-58-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, S1 Mount, 22 Inches, .058 Gauge (0.325 Pitch = 87 Drive Links, 0.375 Pitch = 77 Drive Links, 0.404 Pitch = 70 Drive Links) |
| CSB-S1-22-63-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, S1 Mount, 22 Inches, .063 Gauge (0.325 Pitch = 87 Drive Links, 0.375 Pitch = 77 Drive Links, 0.404 Pitch = 70 Drive Links) |
| CSB-S1-24-50-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, S1 Mount, 24 Inches, .050 Gauge (0.325 Pitch = 95 Drive Links, 0.375 Pitch = 84 Drive Links, 0.404 Pitch = 76 Drive Links) |
| CSB-S1-24-58-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, S1 Mount, 24 Inches, .058 Gauge (0.325 Pitch = 95 Drive Links, 0.375 Pitch = 84 Drive Links, 0.404 Pitch = 76 Drive Links) |
| CSB-S1-24-63-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, S1 Mount, 24 Inches, .063 Gauge (0.325 Pitch = 95 Drive Links, 0.375 Pitch = 84 Drive Links, 0.404 Pitch = 76 Drive Links) |
| CSB-S1-28-50-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, S1 Mount, 28 Inches, .050 Gauge (0.325 Pitch = 104 Drive Links, 0.375 Pitch = 91 Drive Links, 0.404 Pitch = 83 Drive Links) |
| CSB-S1-28-58-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, S1 Mount, 28 Inches, .058 Gauge (0.325 Pitch = 104 Drive Links, 0.375 Pitch = 91 Drive Links, 0.404 Pitch = 83 Drive Links) |
| CSB-S1-28-63-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, S1 Mount, 28 Inches, .063 Gauge (0.325 Pitch = 104 Drive Links, 0.375 Pitch = 91 Drive Links, 0.404 Pitch = 83 Drive Links) |
| CSB-S1-30-50-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, S1 Mount, 30 Inches, .050 Gauge (0.325 Pitch = 111 Drive Links, 0.375 Pitch = 98 Drive Links, 0.404 Pitch = 89 Drive Links) |
| CSB-S1-30-58-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, S1 Mount, 30 Inches, .058 Gauge (0.325 Pitch = 111 Drive Links, 0.375 Pitch = 98 Drive Links, 0.404 Pitch = 89 Drive Links) |
| CSB-S1-30-63-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, S1 Mount, 30 Inches, .063 Gauge (0.325 Pitch = 111 Drive Links, 0.375 Pitch = 98 Drive Links, 0.404 Pitch = 89 Drive Links) |
| CSB-S1-32-50-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, S1 Mount, 32 Inches, .050 Gauge (0.325 Pitch = 119 Drive Links, 0.375 Pitch = 105 Drive Links, 0.404 Pitch = 95 Drive Links) |
| CSB-S1-32-58-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, S1 Mount, 32 Inches, .058 Gauge (0.325 Pitch = 119 Drive Links, 0.375 Pitch = 105 Drive Links, 0.404 Pitch = 95 Drive Links) |
| CSB-S1-32-63-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, S1 Mount, 32 Inches, .063 Gauge (0.325 Pitch = 119 Drive Links, 0.375 Pitch = 105 Drive Links, 0.404 Pitch = 95 Drive Links) |
| CSB-S1-34-50-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, S1 Mount, 34 Inches, .050 Gauge (0.325 Pitch = 125 Drive Links, 0.375 Pitch = 110 Drive Links, 0.404 Pitch = 100 Drive Links) |
| CSB-S1-34-58-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, S1 Mount, 34 Inches, .058 Gauge (0.325 Pitch = 125 Drive Links, 0.375 Pitch = 110 Drive Links, 0.404 Pitch = 100 Drive Links) |
| CSB-S1-34-63-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, S1 Mount, 34 Inches, .063 Gauge (0.325 Pitch = 125 Drive Links, 0.375 Pitch = 110 Drive Links, 0.404 Pitch = 100 Drive Links) |
| CSB-S1-36-50-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, S1 Mount, 36 Inches, .050 Gauge (0.325 Pitch = 129 Drive Links, 0.375 Pitch = 114 Drive Links, 0.404 Pitch = 104 Drive Links) |
| CSB-S1-36-58-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, S1 Mount, 36 Inches, .058 Gauge (0.325 Pitch = 129 Drive Links, 0.375 Pitch = 114 Drive Links, 0.404 Pitch = 104 Drive Links) |
| CSB-S1-36-63-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, S1 Mount, 36 Inches, .063 Gauge (0.325 Pitch = 129 Drive Links, 0.375 Pitch = 114 Drive Links, 0.404 Pitch = 104 Drive Links) |
| CSB-S1-41-50-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, S1 Mount, 41 Inches, .050 Gauge (0.325 Pitch = 147 Drive Links, 0.375 Pitch = 130 Drive Links, 0.404 Pitch = 117 Drive Links) |
| CSB-S1-41-58-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, S1 Mount, 41 Inches, .058 Gauge (0.325 Pitch = 147 Drive Links, 0.375 Pitch = 130 Drive Links, 0.404 Pitch = 117 Drive Links) |
| CSB-S1-41-63-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, S1 Mount, 41 Inches, .063 Gauge (0.325 Pitch = 147 Drive Links, 0.375 Pitch = 130 Drive Links, 0.404 Pitch = 117 Drive Links) |
| CSB-S1-50-50-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, S1 Mount, 50 Inches, .050 Gauge (0.325 Pitch = 176 Drive Links, 0.375 Pitch = 156 Drive Links, 0.404 Pitch = 142 Drive Links) |
| CSB-S1-50-58-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, S1 Mount, 50 Inches, .058 Gauge (0.325 Pitch = 176 Drive Links, 0.375 Pitch = 156 Drive Links, 0.404 Pitch = 142 Drive Links) |
| CSB-S1-50-63-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, S1 Mount, 50 Inches, .063 Gauge (0.325 Pitch = 176 Drive Links, 0.375 Pitch = 156 Drive Links, 0.404 Pitch = 142 Drive Links) |
| CSB-S1-60-50-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, S1 Mount, 60 Inches, .050 Gauge (0.325 Pitch = 209 Drive Links, 0.375 Pitch = 185 Drive Links, 0.404 Pitch = 167 Drive Links) |
| CSB-S1-60-58-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, S1 Mount, 60 Inches, .058 Gauge (0.325 Pitch = 209 Drive Links, 0.375 Pitch = 185 Drive Links, 0.404 Pitch = 167 Drive Links) |
| CSB-S1-60-63-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, S1 Mount, 60 Inches, .063 Gauge (0.325 Pitch = 209 Drive Links, 0.375 Pitch = 185 Drive Links, 0.404 Pitch = 167 Drive Links) |
| CSB-S2-16-50-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, S2 Mount, 16 Inches, .050 Gauge (0.325 Pitch = 74 Drive Links, 0.375 Pitch = 66 Drive Links, 0.404 Pitch = 59 Drive Links) |
| CSB-S2-16-58-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, S2 Mount, 16 Inches, .058 Gauge (0.325 Pitch = 74 Drive Links, 0.375 Pitch = 66 Drive Links, 0.404 Pitch = 59 Drive Links) |
| CSB-S2-16-63-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, S2 Mount, 16 Inches, .063 Gauge (0.325 Pitch = 74 Drive Links, 0.375 Pitch = 66 Drive Links, 0.404 Pitch = 59 Drive Links) |
| CSB-S2-18-50-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, S2 Mount, 18 Inches, .050 Gauge (0.325 Pitch = 80 Drive Links, 0.375 Pitch = 72 Drive Links, 0.404 Pitch = 64 Drive Links) |
| CSB-S2-18-58-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, S2 Mount, 18 Inches, .058 Gauge (0.325 Pitch = 80 Drive Links, 0.375 Pitch = 72 Drive Links, 0.404 Pitch = 64 Drive Links) |
| CSB-S2-18-63-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, S2 Mount, 18 Inches, .063 Gauge (0.325 Pitch = 80 Drive Links, 0.375 Pitch = 72 Drive Links, 0.404 Pitch = 64 Drive Links) |
| CSB-S2-21-50-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, S2 Mount, 21 Inches, .050 Gauge (0.325 Pitch = 85 Drive Links, 0.375 Pitch = 75 Drive Links, 0.404 Pitch = 68 Drive Links) |
| CSB-S2-21-58-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, S2 Mount, 21 Inches, .058 Gauge (0.325 Pitch = 85 Drive Links, 0.375 Pitch = 75 Drive Links, 0.404 Pitch = 68 Drive Links) |
| CSB-S2-21-63-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, S2 Mount, 21 Inches, .063 Gauge (0.325 Pitch = 85 Drive Links, 0.375 Pitch = 75 Drive Links, 0.404 Pitch = 68 Drive Links) |
| CSB-S2-25-50-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, S2 Mount, 25 Inches, .050 Gauge (0.325 Pitch = 100 Drive Links, 0.375 Pitch = 89 Drive Links, 0.404 Pitch = 80 Drive Links) |
| CSB-S2-25-58-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, S2 Mount, 25 Inches, .058 Gauge (0.325 Pitch = 100 Drive Links, 0.375 Pitch = 89 Drive Links, 0.404 Pitch = 80 Drive Links) |
| CSB-S2-25-63-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, S2 Mount, 25 Inches, .063 Gauge (0.325 Pitch = 100 Drive Links, 0.375 Pitch = 89 Drive Links, 0.404 Pitch = 80 Drive Links) |
| CSB-S2-29-50-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, S2 Mount, 29 Inches, .050 Gauge (0.325 Pitch = 115 Drive Links, 0.375 Pitch = 102 Drive Links, 0.404 Pitch = 92 Drive Links) |
| CSB-S2-29-58-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, S2 Mount, 29 Inches, .058 Gauge (0.325 Pitch = 115 Drive Links, 0.375 Pitch = 102 Drive Links, 0.404 Pitch = 92 Drive Links) |
| CSB-S2-29-63-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, S2 Mount, 29 Inches, .063 Gauge (0.325 Pitch = 115 Drive Links, 0.375 Pitch = 102 Drive Links, 0.404 Pitch = 92 Drive Links) |
| CSB-S2-32-50-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, S2 Mount, 32 Inches, .050 Gauge (0.325 Pitch = 119 Drive Links, 0.375 Pitch = 105 Drive Links, 0.404 Pitch = 95 Drive Links) |
| CSB-S2-32-58-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, S2 Mount, 32 Inches, .058 Gauge (0.325 Pitch = 119 Drive Links, 0.375 Pitch = 105 Drive Links, 0.404 Pitch = 95 Drive Links) |
| CSB-S2-32-63-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, S2 Mount, 32 Inches, .063 Gauge (0.325 Pitch = 119 Drive Links, 0.375 Pitch = 105 Drive Links, 0.404 Pitch = 95 Drive Links) |
| CSB-S2-33-50-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, S2 Mount, 33 Inches, .050 Gauge (0.325 Pitch = 124 Drive Links, 0.375 Pitch = 110 Drive Links, 0.404 Pitch = 99 Drive Links) |
| CSB-S2-33-58-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, S2 Mount, 33 Inches, .058 Gauge (0.325 Pitch = 124 Drive Links, 0.375 Pitch = 110 Drive Links, 0.404 Pitch = 99 Drive Links) |
| CSB-S2-33-63-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, S2 Mount, 33 Inches, .063 Gauge (0.325 Pitch = 124 Drive Links, 0.375 Pitch = 110 Drive Links, 0.404 Pitch = 99 Drive Links) |
| CSB-S2-36-50-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, S2 Mount, 36 Inches, .050 Gauge (0.325 Pitch = 115 Drive Links, 0.375 Pitch = 123 Drive Links, 0.404 Pitch = 111 Drive Links) |
| CSB-S2-36-58-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, S2 Mount, 36 Inches, .058 Gauge (0.325 Pitch = 115 Drive Links, 0.375 Pitch = 123 Drive Links, 0.404 Pitch = 111 Drive Links) |
| CSB-S2-36-63-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, S2 Mount, 36 Inches, .063 Gauge (0.325 Pitch = 115 Drive Links, 0.375 Pitch = 123 Drive Links, 0.404 Pitch = 111 Drive Links) |
| CSB-S2-41-50-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, S2 Mount, 41 Inches, .050 Gauge (0.325 Pitch = 153 Drive Links, 0.375 Pitch = 135 Drive Links, 0.404 Pitch = 122 Drive Links) |
| CSB-S2-41-58-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, S2 Mount, 41 Inches, .058 Gauge (0.325 Pitch = 153 Drive Links, 0.375 Pitch = 135 Drive Links, 0.404 Pitch = 122 Drive Links) |
| CSB-S2-41-63-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, S2 Mount, 41 Inches, .063 Gauge (0.325 Pitch = 153 Drive Links, 0.375 Pitch = 135 Drive Links, 0.404 Pitch = 122 Drive Links) |
| CSB-S2-50-50-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, S2 Mount, 50 Inches, .050 Gauge (0.325 Pitch = 178 Drive Links, 0.375 Pitch = 157 Drive Links, 0.404 Pitch = 142 Drive Links) |
| CSB-S2-50-58-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, S2 Mount, 50 Inches, .058 Gauge (0.325 Pitch = 178 Drive Links, 0.375 Pitch = 157 Drive Links, 0.404 Pitch = 142 Drive Links) |
| CSB-S2-50-63-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, S2 Mount, 50 Inches, .063 Gauge (0.325 Pitch = 178 Drive Links, 0.375 Pitch = 157 Drive Links, 0.404 Pitch = 142 Drive Links) |
| CSB-S2-60-50-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, S2 Mount, 60 Inches, .050 Gauge (0.325 Pitch = 215 Drive Links, 0.375 Pitch = 190 Drive Links, 0.404 Pitch = 172 Drive Links) |
| CSB-S2-60-58-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, S2 Mount, 60 Inches, .058 Gauge (0.325 Pitch = 215 Drive Links, 0.375 Pitch = 190 Drive Links, 0.404 Pitch = 172 Drive Links) |
| CSB-S2-60-63-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, S2 Mount, 60 Inches, .063 Gauge (0.325 Pitch = 215 Drive Links, 0.375 Pitch = 190 Drive Links, 0.404 Pitch = 172 Drive Links) |
| CSB-S2-72-50-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, S2 Mount, 72 Inches, .050 Gauge (0.325 Pitch = 246 Drive Links, 0.375 Pitch = 217 Drive Links, 0.404 Pitch = 196 Drive Links) |
| CSB-S2-72-58-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, S2 Mount, 72 Inches, .058 Gauge (0.325 Pitch = 246 Drive Links, 0.375 Pitch = 217 Drive Links, 0.404 Pitch = 196 Drive Links) |
| CSB-S2-72-63-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, S2 Mount, 72 Inches, .063 Gauge (0.325 Pitch = 246 Drive Links, 0.375 Pitch = 217 Drive Links, 0.404 Pitch = 196 Drive Links) |
| CSB-S2-84-50-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, S2 Mount, 84 Inches, .050 Gauge (0.325 Pitch = 282 Drive Links, 0.375 Pitch = 249 Drive Links, 0.404 Pitch = 225 Drive Links) |
| CSB-S2-84-58-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, S2 Mount, 84 Inches, .058 Gauge (0.325 Pitch = 282 Drive Links, 0.375 Pitch = 249 Drive Links, 0.404 Pitch = 225 Drive Links) |
| CSB-S2-84-63-H | CHAINSAW | CANNON SUPERBAR, REPLACEABLE HARD NOSE, S2 Mount, 84 Inches, .063 Gauge (0.325 Pitch = 282 Drive Links, 0.375 Pitch = 249 Drive Links, 0.404 Pitch = 225 Drive Links) |
| CSB-C1-12-50-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, C1 Mount, 12 Inches, .050 Gauge, 0.325 Pitch, 56 Drive Links |
| CSB-C1-12-50-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, C1 Mount, 12 Inches, .050 Gauge, 0.375 Pitch, 49 Drive Links |
| CSB-C1-12-58-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, C1 Mount, 12 Inches, .058 Gauge, 0.325 Pitch, 56 Drive Links |
| CSB-C1-12-58-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, C1 Mount, 12 Inches, .058 Gauge, 0.375 Pitch, 44 Drive Links |
| CSB-C1-12-58-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, C1 Mount, 12 Inches, .058 Gauge, 0.404 Pitch, 49 Drive Links |
| CSB-C1-12-63-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, C1 Mount, 12 Inches, .063 Gauge, 0.325 Pitch, 56 Drive Links |
| CSB-C1-12-63-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, C1 Mount, 12 Inches, .063 Gauge, 0.375 Pitch, 44 Drive Links |
| CSB-C1-12-63-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, C1 Mount, 12 Inches, .063 Gauge, 0.404 Pitch, 49 Drive Links |
| CSB-C1-15-50-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, C1 Mount, 15 Inches, .050 Gauge, 0.325 Pitch, 64 Drive Links |
| CSB-C1-15-50-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, C1 Mount, 15 Inches, .050 Gauge, 0.375 Pitch, 56 Drive Links |
| CSB-C1-15-58-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, C1 Mount, 15 Inches, .058 Gauge, 0.325 Pitch, 64 Drive Links |
| CSB-C1-15-58-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, C1 Mount, 15 Inches, .058 Gauge, 0.375 Pitch, 56 Drive Links |
| CSB-C1-15-58-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, C1 Mount, 15 Inches, .058 Gauge, 0.404 Pitch, 51 Drive Links |
| CSB-C1-15-63-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, C1 Mount, 15 Inches, .063 Gauge, 0.325 Pitch, 64 Drive Links |
| CSB-C1-15-63-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, C1 Mount, 15 Inches, .063 Gauge, 0.375 Pitch, 56 Drive Links |
| CSB-C1-15-63-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, C1 Mount, 15 Inches, .063 Gauge, 0.404 Pitch, 51 Drive Links |
| CSB-C1-16-50-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, C1 Mount, 16 Inches, .050 Gauge, 0.325 Pitch, 68 Drive Links |
| CSB-C1-16-50-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, C1 Mount, 16 Inches, .050 Gauge, 0.375 Pitch, 60 Drive Links |
| CSB-C1-16-58-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, C1 Mount, 16 Inches, .058 Gauge, 0.325 Pitch, 68 Drive Links |
| CSB-C1-16-58-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, C1 Mount, 16 Inches, .058 Gauge, 0.375 Pitch, 60 Drive Links |
| CSB-C1-16-58-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, C1 Mount, 16 Inches, .058 Gauge, 0.404 Pitch, 55 Drive Links |
| CSB-C1-16-63-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, C1 Mount, 16 Inches, .063 Gauge, 0.325 Pitch, 68 Drive Links |
| CSB-C1-16-63-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, C1 Mount, 16 Inches, .063 Gauge, 0.375 Pitch, 60 Drive Links |
| CSB-C1-16-63-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, C1 Mount, 16 Inches, .063 Gauge, 0.404 Pitch, 55 Drive Links |
| CSB-C1-18-50-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, C1 Mount, 18 Inches, .050 Gauge, 0.325 Pitch, 77 Drive Links |
| CSB-C1-18-50-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, C1 Mount, 18 Inches, .050 Gauge, 0.375 Pitch, 68 Drive Links |
| CSB-C1-18-58-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, C1 Mount, 18 Inches, .058 Gauge, 0.325 Pitch, 77 Drive Links |
| CSB-C1-18-58-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, C1 Mount, 18 Inches, .058 Gauge, 0.375 Pitch, 68 Drive Links |
| CSB-C1-18-58-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, C1 Mount, 18 Inches, .058 Gauge, 0.404 Pitch, 62 Drive Links |
| CSB-C1-18-63-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, C1 Mount, 18 Inches, .063 Gauge, 0.325 Pitch, 77 Drive Links |
| CSB-C1-18-63-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, C1 Mount, 18 Inches, .063 Gauge, 0.375 Pitch, 68 Drive Links |
| CSB-C1-18-63-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, C1 Mount, 18 Inches, .063 Gauge, 0.404 Pitch, 62 Drive Links |
| CSB-C1-20-50-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, C1 Mount, 20 Inches, .050 Gauge, 0.325 Pitch, 81 Drive Links |
| CSB-C1-20-50-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, C1 Mount, 20 Inches, .050 Gauge, 0.375 Pitch, 72 Drive Links |
| CSB-C1-20-58-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, C1 Mount, 20 Inches, .058 Gauge, 0.325 Pitch, 81 Drive Links |
| CSB-C1-20-58-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, C1 Mount, 20 Inches, .058 Gauge, 0.375 Pitch, 72 Drive Links |
| CSB-C1-20-58-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, C1 Mount, 20 Inches, .058 Gauge, 0.404 Pitch, 66 Drive Links |
| CSB-C1-20-63-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, C1 Mount, 20 Inches, .063 Gauge, 0.325 Pitch, 81 Drive Links |
| CSB-C1-20-63-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, C1 Mount, 20 Inches, .063 Gauge, 0.375 Pitch, 72 Drive Links |
| CSB-C1-20-63-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, C1 Mount, 20 Inches, .063 Gauge, 0.404 Pitch, 66 Drive Links |
| CSB-C1-24-50-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, C1 Mount, 24 Inches, .050 Gauge, 0.325 Pitch, 95 Drive Links |
| CSB-C1-24-50-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, C1 Mount, 24 Inches, .050 Gauge, 0.375 Pitch, 84 Drive Links |
| CSB-C1-24-58-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, C1 Mount, 24 Inches, .058 Gauge, 0.325 Pitch, 95 Drive Links |
| CSB-C1-24-58-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, C1 Mount, 24 Inches, .058 Gauge, 0.375 Pitch, 84 Drive Links |
| CSB-C1-24-58-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, C1 Mount, 24 Inches, .058 Gauge, 0.404 Pitch, 76 Drive Links |
| CSB-C1-24-63-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, C1 Mount, 24 Inches, .063 Gauge, 0.325 Pitch, 95 Drive Links |
| CSB-C1-24-63-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, C1 Mount, 24 Inches, .063 Gauge, 0.375 Pitch, 84 Drive Links |
| CSB-C1-24-63-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, C1 Mount, 24 Inches, .063 Gauge, 0.404 Pitch, 76 Drive Links |
| CSB-H1-12-50-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 12 Inches, .050 Gauge, 0.325 Pitch, 56 Drive Links |
| CSB-H1-12-50-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 12 Inches, .050 Gauge, 0.375 Pitch, 49 Drive Links |
| CSB-H1-12-58-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 12 Inches, .058 Gauge, 0.325 Pitch, 56 Drive Links |
| CSB-H1-12-58-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 12 Inches, .058 Gauge, 0.375 Pitch, 49 Drive Links |
| CSB-H1-12-58-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 12 Inches, .058 Gauge, 0.404 Pitch, 44 Drive Links |

| | | |
|---|---|---|
| CSB-H1-12-63-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 12 Inches, .063 Gauge, 0.325 Pitch, 56 Drive Links |
| CSB-H1-12-63-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 12 Inches, .063 Gauge, 0.375 Pitch, 49 Drive Links |
| CSB-H1-12-63-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 12 Inches, .063 Gauge, 0.404 Pitch, 44 Drive Links |
| CSB-H1-15-50-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 15 Inches, .050 Gauge, 0.325 Pitch, 64 Drive Links |
| CSB-H1-15-50-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 15 Inches, .050 Gauge, 0.375 Pitch, 56 Drive Links |
| CSB-H1-15-58-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 15 Inches, .058 Gauge, 0.325 Pitch, 64 Drive Links |
| CSB-H1-15-58-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 15 Inches, .058 Gauge, 0.375 Pitch, 56 Drive Links |
| CSB-H1-15-58-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 15 Inches, .058 Gauge, 0.404 Pitch, 51 Drive Links |
| CSB-H1-15-63-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 15 Inches, .063 Gauge, 0.325 Pitch, 64 Drive Links |
| CSB-H1-15-63-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 15 Inches, .063 Gauge, 0.375 Pitch, 56 Drive Links |
| CSB-H1-15-63-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 15 Inches, .063 Gauge, 0.404 Pitch, 51 Drive Links |
| CSB-H1-16-50-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 16 Inches, .050 Gauge, 0.325 Pitch, 68 Drive Links |
| CSB-H1-16-50-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 16 Inches, .050 Gauge, 0.375 Pitch, 60 Drive Links |
| CSB-H1-16-58-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 16 Inches, .058 Gauge, 0.325 Pitch, 68 Drive Links |
| CSB-H1-16-58-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 16 Inches, .058 Gauge, 0.375 Pitch, 60 Drive Links |
| CSB-H1-16-58-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 16 Inches, .058 Gauge, 0.404 Pitch, 55 Drive Links |
| CSB-H1-16-63-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 16 Inches, .063 Gauge, 0.325 Pitch, 68 Drive Links |
| CSB-H1-16-63-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 16 Inches, .063 Gauge, 0.375 Pitch, 60 Drive Links |
| CSB-H1-16-63-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 16 Inches, .063 Gauge, 0.404 Pitch, 55 Drive Links |
| CSB-H1-17-50-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 17 Inches, .050 Gauge, 0.325 Pitch, 72 Drive Links |
| CSB-H1-17-50-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 17 Inches, .050 Gauge, 0.375 Pitch, 64 Drive Links |
| CSB-H1-17-58-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 17 Inches, .058 Gauge, 0.325 Pitch, 72 Drive Links |
| CSB-H1-17-58-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 17 Inches, .058 Gauge, 0.375 Pitch, 64 Drive Links |
| CSB-H1-17-58-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 17 Inches, .058 Gauge, 0.404 Pitch, 58 Drive Links |
| CSB-H1-17-63-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 17 Inches, .063 Gauge, 0.325 Pitch, 72 Drive Links |
| CSB-H1-17-63-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 17 Inches, .063 Gauge, 0.375 Pitch, 64 Drive Links |
| CSB-H1-17-63-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 17 Inches, .063 Gauge, 0.404 Pitch, 58 Drive Links |
| CSB-H1-18-50-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 18 Inches, .050 Gauge, 0.325 Pitch, 77 Drive Links |
| CSB-H1-18-50-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 18 Inches, .050 Gauge, 0.375 Pitch, 68 Drive Links |
| CSB-H1-18-58-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 18 Inches, .058 Gauge, 0.325 Pitch, 77 Drive Links |
| CSB-H1-18-58-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 18 Inches, .058 Gauge, 0.375 Pitch, 68 Drive Links |
| CSB-H1-18-58-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 18 Inches, .058 Gauge, 0.404 Pitch, 62 Drive Links |
| CSB-H1-18-63-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 18 Inches, .063 Gauge, 0.325 Pitch, 77 Drive Links |
| CSB-H1-18-63-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 18 Inches, .063 Gauge, 0.375 Pitch, 68 Drive Links |
| CSB-H1-18-63-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 18 Inches, .063 Gauge, 0.404 Pitch, 62 Drive Links |
| CSB-H1-20-50-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 20 Inches, .050 Gauge, 0.325 Pitch, 81 Drive Links |
| CSB-H1-20-50-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 20 Inches, .050 Gauge, 0.375 Pitch, 72 Drive Links |
| CSB-H1-20-58-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 20 Inches, .058 Gauge, 0.325 Pitch, 81 Drive Links |
| CSB-H1-20-58-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 20 Inches, .058 Gauge, 0.375 Pitch, 72 Drive Links |
| CSB-H1-20-58-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 20 Inches, .058 Gauge, 0.404 Pitch, 66 Drive Links |
| CSB-H1-20-63-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 20 Inches, .063 Gauge, 0.325 Pitch, 81 Drive Links |
| CSB-H1-20-63-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 20 Inches, .063 Gauge, 0.375 Pitch, 72 Drive Links |
| CSB-H1-20-63-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 20 Inches, .063 Gauge, 0.404 Pitch, 66 Drive Links |
| CSB-H1-22-50-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 22 Inches, .050 Gauge, 0.325 Pitch, 86 Drive Links |
| CSB-H1-22-50-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 22 Inches, .050 Gauge, 0.375 Pitch, 76 Drive Links |
| CSB-H1-22-58-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 22 Inches, .058 Gauge, 0.325 Pitch, 86 Drive Links |
| CSB-H1-22-58-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 22 Inches, .058 Gauge, 0.375 Pitch, 76 Drive Links |
| CSB-H1-22-58-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 22 Inches, .058 Gauge, 0.404 Pitch, 69 Drive Links |
| CSB-H1-22-63-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 22 Inches, .063 Gauge, 0.325 Pitch, 86 Drive Links |
| CSB-H1-22-63-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 22 Inches, .063 Gauge, 0.375 Pitch, 76 Drive Links |
| CSB-H1-22-63-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 22 Inches, .063 Gauge, 0.404 Pitch, 69 Drive Links |
| CSB-H1-24-50-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 24 Inches, .050 Gauge, 0.325 Pitch, 95 Drive Links |
| CSB-H1-24-50-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 24 Inches, .050 Gauge, 0.375 Pitch, 84 Drive Links |
| CSB-H1-24-58-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 24 Inches, .058 Gauge, 0.325 Pitch, 95 Drive Links |
| CSB-H1-24-58-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 24 Inches, .058 Gauge, 0.375 Pitch, 84 Drive Links |
| CSB-H1-24-58-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 24 Inches, .058 Gauge, 0.404 Pitch, 76 Drive Links |
| CSB-H1-24-63-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 24 Inches, .063 Gauge, 0.325 Pitch, 95 Drive Links |
| CSB-H1-24-63-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 24 Inches, .063 Gauge, 0.375 Pitch, 84 Drive Links |
| CSB-H1-24-63-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 24 Inches, .063 Gauge, 0.404 Pitch, 76 Drive Links |
| CSB-H1-26-50-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 26 Inches, .050 Gauge, 0.325 Pitch, 101 Drive Links |
| CSB-H1-26-50-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 26 Inches, .050 Gauge, 0.375 Pitch, 89 Drive Links |
| CSB-H1-26-58-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 26 Inches, .058 Gauge, 0.325 Pitch, 101 Drive Links |
| CSB-H1-26-58-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 26 Inches, .058 Gauge, 0.375 Pitch, 89 Drive Links |
| CSB-H1-26-58-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 26 Inches, .058 Gauge, 0.404 Pitch, 81 Drive Links |
| CSB-H1-26-63-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 26 Inches, .063 Gauge, 0.325 Pitch, 101 Drive Links |
| CSB-H1-26-63-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 26 Inches, .063 Gauge, 0.375 Pitch, 89 Drive Links |
| CSB-H1-26-63-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 26 Inches, .063 Gauge, 0.404 Pitch, 81 Drive Links |
| CSB-H1-28-50-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 28 Inches, .050 Gauge, 0.325 Pitch, 105 Drive Links |
| CSB-H1-28-50-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 28 Inches, .050 Gauge, 0.375 Pitch, 93 Drive Links |
| CSB-H1-28-58-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 28 Inches, .058 Gauge, 0.325 Pitch, 105 Drive Links |
| CSB-H1-28-58-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 28 Inches, .058 Gauge, 0.375 Pitch, 93 Drive Links |
| CSB-H1-28-58-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 28 Inches, .058 Gauge, 0.404 Pitch, 85 Drive Links |
| CSB-H1-28-63-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 28 Inches, .063 Gauge, 0.325 Pitch, 105 Drive Links |
| CSB-H1-28-63-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 28 Inches, .063 Gauge, 0.375 Pitch, 93 Drive Links |
| CSB-H1-28-63-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 28 Inches, .063 Gauge, 0.404 Pitch, 85 Drive Links |
| CSB-H1-30-50-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 30 Inches, .050 Gauge, 0.325 Pitch, 115 Drive Links |
| CSB-H1-30-50-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 30 Inches, .050 Gauge, 0.375 Pitch, 102 Drive Links |
| CSB-H1-30-58-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 30 Inches, .058 Gauge, 0.325 Pitch, 115 Drive Links |
| CSB-H1-30-58-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 30 Inches, .058 Gauge, 0.375 Pitch, 102 Drive Links |
| CSB-H1-30-58-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 30 Inches, .058 Gauge, 0.404 Pitch, 92 Drive Links |
| CSB-H1-30-63-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 30 Inches, .063 Gauge, 0.325 Pitch, 115 Drive Links |
| CSB-H1-30-63-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 30 Inches, .063 Gauge, 0.375 Pitch, 102 Drive Links |
| CSB-H1-30-63-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 30 Inches, .063 Gauge, 0.404 Pitch, 92 Drive Links |
| CSB-H1-32-50-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 32 Inches, .050 Gauge, 0.325 Pitch, 119 Drive Links |
| CSB-H1-32-50-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 32 Inches, .050 Gauge, 0.375 Pitch, 105 Drive Links |
| CSB-H1-32-58-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 32 Inches, .058 Gauge, 0.325 Pitch, 119 Drive Links |
| CSB-H1-32-58-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 32 Inches, .058 Gauge, 0.375 Pitch, 105 Drive Links |
| CSB-H1-32-58-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 32 Inches, .058 Gauge, 0.404 Pitch, 95 Drive Links |
| CSB-H1-32-63-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 32 Inches, .063 Gauge, 0.325 Pitch, 119 Drive Links |
| CSB-H1-32-63-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 32 Inches, .063 Gauge, 0.375 Pitch, 105 Drive Links |
| CSB-H1-32-63-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 32 Inches, .063 Gauge, 0.404 Pitch, 95 Drive Links |
| CSB-H1-33-50-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 33 Inches, .050 Gauge, 0.325 Pitch, 125 Drive Links |
| CSB-H1-33-50-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 33 Inches, .050 Gauge, 0.375 Pitch, 110 Drive Links |
| CSB-H1-33-58-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 33 Inches, .058 Gauge, 0.325 Pitch, 125 Drive Links |
| CSB-H1-33-58-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 33 Inches, .058 Gauge, 0.375 Pitch, 110 Drive Links |
| CSB-H1-33-58-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 33 Inches, .058 Gauge, 0.404 Pitch, 100 Drive Links |
| CSB-H1-33-63-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 33 Inches, .063 Gauge, 0.325 Pitch, 125 Drive Links |
| CSB-H1-33-63-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 33 Inches, .063 Gauge, 0.375 Pitch, 110 Drive Links |
| CSB-H1-33-63-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 33 Inches, .063 Gauge, 0.404 Pitch, 100 Drive Links |
| CSB-H1-34-50-2 | | ORDER AS CSB-H1-33-50-2 (SAME BAR) |
| CSB-H1-34-50-3 | | ORDER AS CSB-H1-33-50-3 (SAME BAR) |
| CSB-H1-34-58-2 | | ORDER AS CSB-H1-33-58-2 (SAME BAR) |
| CSB-H1-34-58-3 | | ORDER AS CSB-H1-33-58-3 (SAME BAR) |
| CSB-H1-34-58-4 | | ORDER AS CSB-H1-33-58-4 (SAME BAR) |
| CSB-H1-34-63-2 | | ORDER AS CSB-H1-33-63-2 (SAME BAR) |
| CSB-H1-34-63-3 | | ORDER AS CSB-H1-33-63-3 (SAME BAR) |
| CSB-H1-34-63-4 | | ORDER AS CSB-H1-33-63-4 (SAME BAR) |
| CSB-H1-36-50-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 36 Inches, .050 Gauge, 0.325 Pitch, 130 Drive Links |
| CSB-H1-36-50-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 36 Inches, .050 Gauge, 0.375 Pitch, 115 Drive Links |
| CSB-H1-36-58-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 36 Inches, .058 Gauge, 0.325 Pitch, 130 Drive Links |
| CSB-H1-36-58-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 36 Inches, .058 Gauge, 0.375 Pitch, 115 Drive Links |
| CSB-H1-36-58-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 36 Inches, .058 Gauge, 0.404 Pitch, 104 Drive Links |
| CSB-H1-36-63-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 36 Inches, .063 Gauge, 0.325 Pitch, 130 Drive Links |
| CSB-H1-36-63-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 36 Inches, .063 Gauge, 0.375 Pitch, 115 Drive Links |
| CSB-H1-36-63-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 36 Inches, .063 Gauge, 0.404 Pitch, 104 Drive Links |
| CSB-H1-37-50-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 37 Inches, .050 Gauge, 0.325 Pitch, 135 Drive Links |
| CSB-H1-37-50-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 37 Inches, .050 Gauge, 0.375 Pitch, 119 Drive Links |
| CSB-H1-37-58-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 37 Inches, .058 Gauge, 0.325 Pitch, 135 Drive Links |
| CSB-H1-37-58-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 37 Inches, .058 Gauge, 0.375 Pitch, 119 Drive Links |
| CSB-H1-37-58-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 37 Inches, .058 Gauge, 0.404 Pitch, 108 Drive Links |
| CSB-H1-37-63-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 37 Inches, .063 Gauge, 0.325 Pitch, 135 Drive Links |
| CSB-H1-37-63-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 37 Inches, .063 Gauge, 0.375 Pitch, 119 Drive Links |
| CSB-H1-37-63-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 37 Inches, .063 Gauge, 0.404 Pitch, 108 Drive Links |
| CSB-H1-42-50-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 42 Inches, .050 Gauge, 0.325 Pitch, 153 Drive Links |
| CSB-H1-42-50-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 42 Inches, .050 Gauge, 0.375 Pitch, 135 Drive Links |
| CSB-H1-42-58-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 42 Inches, .058 Gauge, 0.325 Pitch, 153 Drive Links |
| CSB-H1-42-58-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 42 Inches, .058 Gauge, 0.375 Pitch, 135 Drive Links |
| CSB-H1-42-58-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 42 Inches, .058 Gauge, 0.404 Pitch, 122 Drive Links |
| CSB-H1-42-63-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 42 Inches, .063 Gauge, 0.325 Pitch, 153 Drive Links |
| CSB-H1-42-63-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 42 Inches, .063 Gauge, 0.375 Pitch, 135 Drive Links |
| CSB-H1-42-63-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 42 Inches, .063 Gauge, 0.404 Pitch, 122 Drive Links |
| CSB-H1-50-50-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 50 Inches, .050 Gauge, 0.325 Pitch, 177 Drive Links |
| CSB-H1-50-50-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 50 Inches, .050 Gauge, 0.375 Pitch, 156 Drive Links |
| CSB-H1-50-58-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 50 Inches, .058 Gauge, 0.325 Pitch, 177 Drive Links |
| CSB-H1-50-58-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 50 Inches, .058 Gauge, 0.375 Pitch, 156 Drive Links |
| CSB-H1-50-58-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 50 Inches, .058 Gauge, 0.404 Pitch, 141 Drive Links |
| CSB-H1-50-63-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 50 Inches, .063 Gauge, 0.325 Pitch, 177 Drive Links |
| CSB-H1-50-63-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 50 Inches, .063 Gauge, 0.375 Pitch, 156 Drive Links |

| | | |
|---|---|---|
| CSB-H1-50-63-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 50 Inches, .063 Gauge, 0.404 Pitch, 142 Drive Links |
| CSB-H1-60-50-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 60 Inches, .050 Gauge, 0.325 Pitch, 209 Drive Links |
| CSB-H1-60-50-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 60 Inches, .050 Gauge, 0.375 Pitch, 185 Drive Links |
| CSB-H1-60-58-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 60 Inches, .058 Gauge, 0.325 Pitch, 209 Drive Links |
| CSB-H1-60-58-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 60 Inches, .058 Gauge, 0.375 Pitch, 185 Drive Links |
| CSB-H1-60-58-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 60 Inches, .058 Gauge, 0.404 Pitch, 167 Drive Links |
| CSB-H1-60-63-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 60 Inches, .063 Gauge, 0.325 Pitch, 209 Drive Links |
| CSB-H1-60-63-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 60 Inches, .063 Gauge, 0.375 Pitch, 185 Drive Links |
| CSB-H1-60-63-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 60 Inches, .063 Gauge, 0.404 Pitch, 167 Drive Links |
| CSB-H1-72-50-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 72 Inches, .050 Gauge, 0.325 Pitch, 247 Drive Links |
| CSB-H1-72-50-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 72 Inches, .050 Gauge, 0.375 Pitch, 218 Drive Links |
| CSB-H1-72-58-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 72 Inches, .058 Gauge, 0.325 Pitch, 247 Drive Links |
| CSB-H1-72-58-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 72 Inches, .058 Gauge, 0.375 Pitch, 218 Drive Links |
| CSB-H1-72-58-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 72 Inches, .058 Gauge, 0.404 Pitch, 196 Drive Links |
| CSB-H1-72-63-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 72 Inches, .063 Gauge, 0.325 Pitch, 247 Drive Links |
| CSB-H1-72-63-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 72 Inches, .063 Gauge, 0.375 Pitch, 218 Drive Links |
| CSB-H1-72-63-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 72 Inches, .063 Gauge, 0.404 Pitch, 196 Drive Links |
| CSB-H1-84-50-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 84 Inches, .050 Gauge, 0.325 Pitch, 281 Drive Links |
| CSB-H1-84-50-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 84 Inches, .050 Gauge, 0.375 Pitch, 249 Drive Links |
| CSB-H1-84-58-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 84 Inches, .058 Gauge, 0.325 Pitch, 281 Drive Links |
| CSB-H1-84-58-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 84 Inches, .058 Gauge, 0.375 Pitch, 249 Drive Links |
| CSB-H1-84-58-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 84 Inches, .058 Gauge, 0.404 Pitch, 226 Drive Links |
| CSB-H1-84-63-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 84 Inches, .063 Gauge, 0.325 Pitch, 281 Drive Links |
| CSB-H1-84-63-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 84 Inches, .063 Gauge, 0.375 Pitch, 249 Drive Links |
| CSB-H1-84-63-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, H1 Mount, 84 Inches, .063 Gauge, 0.404 Pitch, 226 Drive Links |
| CSB-P4-16-50-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, P4 Mount, 16 Inches, .050 Gauge, 0.325 Pitch, 68 Drive Links |
| CSB-P4-16-50-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, P4 Mount, 16 Inches, .050 Gauge, 0.375 Pitch, 60 Drive Links |
| CSB-P4-16-58-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, P4 Mount, 16 Inches, .058 Gauge, 0.325 Pitch, 68 Drive Links |
| CSB-P4-16-58-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, P4 Mount, 16 Inches, .058 Gauge, 0.375 Pitch, 60 Drive Links |
| CSB-P4-16-58-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, P4 Mount, 16 Inches, .058 Gauge, 0.404 Pitch, 55 Drive Links |
| CSB-P4-16-63-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, P4 Mount, 16 Inches, .063 Gauge, 0.325 Pitch, 68 Drive Links |
| CSB-P4-16-63-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, P4 Mount, 16 Inches, .063 Gauge, 0.375 Pitch, 60 Drive Links |
| CSB-P4-16-63-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, P4 Mount, 16 Inches, .063 Gauge, 0.404 Pitch, 55 Drive Links |
| CSB-P4-20-50-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, P4 Mount, 20 Inches, .050 Gauge, 0.325 Pitch, 79 Drive Links |
| CSB-P4-20-50-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, P4 Mount, 20 Inches, .050 Gauge, 0.375 Pitch, 70 Drive Links |
| CSB-P4-20-58-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, P4 Mount, 20 Inches, .058 Gauge, 0.325 Pitch, 79 Drive Links |
| CSB-P4-20-58-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, P4 Mount, 20 Inches, .058 Gauge, 0.375 Pitch, 70 Drive Links |
| CSB-P4-20-58-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, P4 Mount, 20 Inches, .058 Gauge, 0.404 Pitch, 64 Drive Links |
| CSB-P4-20-63-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, P4 Mount, 20 Inches, .063 Gauge, 0.325 Pitch, 79 Drive Links |
| CSB-P4-20-63-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, P4 Mount, 20 Inches, .063 Gauge, 0.375 Pitch, 70 Drive Links |
| CSB-P4-20-63-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, P4 Mount, 20 Inches, .063 Gauge, 0.404 Pitch, 64 Drive Links |
| CSB-P4-24-50-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, P4 Mount, 24 Inches, .050 Gauge, 0.325 Pitch, 92 Drive Links |
| CSB-P4-24-50-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, P4 Mount, 24 Inches, .050 Gauge, 0.375 Pitch, 81 Drive Links |
| CSB-P4-24-58-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, P4 Mount, 24 Inches, .058 Gauge, 0.325 Pitch, 92 Drive Links |
| CSB-P4-24-58-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, P4 Mount, 24 Inches, .058 Gauge, 0.375 Pitch, 81 Drive Links |
| CSB-P4-24-58-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, P4 Mount, 24 Inches, .058 Gauge, 0.404 Pitch, 74 Drive Links |
| CSB-P4-24-63-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, P4 Mount, 24 Inches, .063 Gauge, 0.325 Pitch, 92 Drive Links |
| CSB-P4-24-63-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, P4 Mount, 24 Inches, .063 Gauge, 0.375 Pitch, 81 Drive Links |
| CSB-P4-24-63-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, P4 Mount, 24 Inches, .063 Gauge, 0.404 Pitch, 74 Drive Links |
| CSB-P4-28-50-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, P4 Mount, 28 Inches, .050 Gauge, 0.325 Pitch, 105 Drive Links |
| CSB-P4-28-50-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, P4 Mount, 28 Inches, .050 Gauge, 0.375 Pitch, 93 Drive Links |
| CSB-P4-28-58-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, P4 Mount, 28 Inches, .058 Gauge, 0.325 Pitch, 105 Drive Links |
| CSB-P4-28-58-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, P4 Mount, 28 Inches, .058 Gauge, 0.375 Pitch, 93 Drive Links |
| CSB-P4-28-58-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, P4 Mount, 28 Inches, .058 Gauge, 0.404 Pitch, 84 Drive Links |
| CSB-P4-28-63-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, P4 Mount, 28 Inches, .063 Gauge, 0.325 Pitch, 105 Drive Links |
| CSB-P4-28-63-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, P4 Mount, 28 Inches, .063 Gauge, 0.375 Pitch, 93 Drive Links |
| CSB-P4-28-63-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, P4 Mount, 28 Inches, .063 Gauge, 0.404 Pitch, 84 Drive Links |
| CSB-P4-32-50-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, P4 Mount, 32 Inches, .050 Gauge, 0.325 Pitch, 119 Drive Links |
| CSB-P4-32-50-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, P4 Mount, 32 Inches, .050 Gauge, 0.375 Pitch, 105 Drive Links |
| CSB-P4-32-58-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, P4 Mount, 32 Inches, .058 Gauge, 0.325 Pitch, 119 Drive Links |
| CSB-P4-32-58-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, P4 Mount, 32 Inches, .058 Gauge, 0.375 Pitch, 105 Drive Links |
| CSB-P4-32-58-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, P4 Mount, 32 Inches, .058 Gauge, 0.404 Pitch, 95 Drive Links |
| CSB-P4-32-63-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, P4 Mount, 32 Inches, .063 Gauge, 0.325 Pitch, 119 Drive Links |
| CSB-P4-32-63-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, P4 Mount, 32 Inches, .063 Gauge, 0.375 Pitch, 105 Drive Links |
| CSB-P4-32-63-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, P4 Mount, 32 Inches, .063 Gauge, 0.404 Pitch, 95 Drive Links |
| CSB-S1-12-50-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 12 Inches, .050 Gauge, 0.325 Pitch, 56 Drive Links |
| CSB-S1-12-50-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 12 Inches, .050 Gauge, 0.375 Pitch, 49 Drive Links |
| CSB-S1-12-58-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 12 Inches, .058 Gauge, 0.325 Pitch, 56 Drive Links |
| CSB-S1-12-58-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 12 Inches, .058 Gauge, 0.375 Pitch, 49 Drive Links |
| CSB-S1-12-58-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 12 Inches, .058 Gauge, 0.404 Pitch, 44 Drive Links |
| CSB-S1-12-63-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 12 Inches, .063 Gauge, 0.325 Pitch, 56 Drive Links |
| CSB-S1-12-63-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 12 Inches, .063 Gauge, 0.375 Pitch, 49 Drive Links |
| CSB-S1-12-63-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 12 Inches, .063 Gauge, 0.404 Pitch, 44 Drive Links |
| CSB-S1-16-50-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 16 Inches, .050 Gauge, 0.325 Pitch, 67 Drive Links |
| CSB-S1-16-50-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 16 Inches, .050 Gauge, 0.375 Pitch, 60 Drive Links |
| CSB-S1-16-58-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 16 Inches, .058 Gauge, 0.325 Pitch, 67 Drive Links |
| CSB-S1-16-58-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 16 Inches, .058 Gauge, 0.375 Pitch, 60 Drive Links |
| CSB-S1-16-58-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 16 Inches, .058 Gauge, 0.404 Pitch, 55 Drive Links |
| CSB-S1-16-63-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 16 Inches, .063 Gauge, 0.325 Pitch, 67 Drive Links |
| CSB-S1-16-63-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 16 Inches, .063 Gauge, 0.375 Pitch, 60 Drive Links |
| CSB-S1-16-63-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 16 Inches, .063 Gauge, 0.404 Pitch, 55 Drive Links |
| CSB-S1-18-50-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 18 Inches, .050 Gauge, 0.325 Pitch, 74 Drive Links |
| CSB-S1-18-50-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 18 Inches, .050 Gauge, 0.375 Pitch, 66 Drive Links |
| CSB-S1-18-58-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 18 Inches, .058 Gauge, 0.325 Pitch, 74 Drive Links |
| CSB-S1-18-58-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 18 Inches, .058 Gauge, 0.375 Pitch, 66 Drive Links |
| CSB-S1-18-58-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 18 Inches, .058 Gauge, 0.404 Pitch, 60 Drive Links |
| CSB-S1-18-63-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 18 Inches, .063 Gauge, 0.325 Pitch, 74 Drive Links |
| CSB-S1-18-63-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 18 Inches, .063 Gauge, 0.375 Pitch, 66 Drive Links |
| CSB-S1-18-63-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 18 Inches, .063 Gauge, 0.404 Pitch, 60 Drive Links |
| CSB-S1-20-50-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 20 Inches, .050 Gauge, 0.325 Pitch, 81 Drive Links |
| CSB-S1-20-50-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 20 Inches, .050 Gauge, 0.375 Pitch, 72 Drive Links |
| CSB-S1-20-58-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 20 Inches, .058 Gauge, 0.325 Pitch, 81 Drive Links |
| CSB-S1-20-58-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 20 Inches, .058 Gauge, 0.375 Pitch, 72 Drive Links |
| CSB-S1-20-58-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 20 Inches, .058 Gauge, 0.404 Pitch, 66 Drive Links |
| CSB-S1-20-63-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 20 Inches, .063 Gauge, 0.325 Pitch, 81 Drive Links |
| CSB-S1-20-63-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 20 Inches, .063 Gauge, 0.375 Pitch, 72 Drive Links |
| CSB-S1-20-63-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 20 Inches, .063 Gauge, 0.404 Pitch, 66 Drive Links |
| CSB-S1-22-50-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 22 Inches, .050 Gauge, 0.325 Pitch, 87 Drive Links |
| CSB-S1-22-50-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 22 Inches, .050 Gauge, 0.375 Pitch, 77 Drive Links |
| CSB-S1-22-58-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 22 Inches, .058 Gauge, 0.325 Pitch, 87 Drive Links |
| CSB-S1-22-58-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 22 Inches, .058 Gauge, 0.375 Pitch, 77 Drive Links |
| CSB-S1-22-58-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 22 Inches, .058 Gauge, 0.404 Pitch, 70 Drive Links |
| CSB-S1-22-63-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 22 Inches, .063 Gauge, 0.325 Pitch, 87 Drive Links |
| CSB-S1-22-63-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 22 Inches, .063 Gauge, 0.375 Pitch, 77 Drive Links |
| CSB-S1-22-63-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 22 Inches, .063 Gauge, 0.404 Pitch, 70 Drive Links |
| CSB-S1-24-50-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 24 Inches, .050 Gauge, 0.325 Pitch, 95 Drive Links |
| CSB-S1-24-50-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 24 Inches, .050 Gauge, 0.375 Pitch, 84 Drive Links |
| CSB-S1-24-58-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 24 Inches, .058 Gauge, 0.325 Pitch, 95 Drive Links |
| CSB-S1-24-58-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 24 Inches, .058 Gauge, 0.375 Pitch, 84 Drive Links |
| CSB-S1-24-58-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 24 Inches, .058 Gauge, 0.404 Pitch, 76 Drive Links |
| CSB-S1-24-63-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 24 Inches, .063 Gauge, 0.325 Pitch, 95 Drive Links |
| CSB-S1-24-63-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 24 Inches, .063 Gauge, 0.375 Pitch, 84 Drive Links |
| CSB-S1-24-63-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 24 Inches, .063 Gauge, 0.404 Pitch, 76 Drive Links |
| CSB-S1-28-50-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 28 Inches, .050 Gauge, 0.325 Pitch, 104 Drive Links |
| CSB-S1-28-50-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 28 Inches, .050 Gauge, 0.375 Pitch, 91 Drive Links |
| CSB-S1-28-58-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 28 Inches, .058 Gauge, 0.325 Pitch, 104 Drive Links |
| CSB-S1-28-58-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 28 Inches, .058 Gauge, 0.375 Pitch, 91 Drive Links |
| CSB-S1-28-58-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 28 Inches, .058 Gauge, 0.404 Pitch, 83 Drive Links |
| CSB-S1-28-63-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 28 Inches, .063 Gauge, 0.325 Pitch, 104 Drive Links |
| CSB-S1-28-63-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 28 Inches, .063 Gauge, 0.375 Pitch, 91 Drive Links |
| CSB-S1-28-63-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 28 Inches, .063 Gauge, 0.404 Pitch, 83 Drive Links |
| CSB-S1-30-50-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 30 Inches, .050 Gauge, 0.325 Pitch, 111 Drive Links |
| CSB-S1-30-50-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 30 Inches, .050 Gauge, 0.375 Pitch, 98 Drive Links |
| CSB-S1-30-58-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 30 Inches, .058 Gauge, 0.325 Pitch, 111 Drive Links |
| CSB-S1-30-58-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 30 Inches, .058 Gauge, 0.375 Pitch, 98 Drive Links |
| CSB-S1-30-58-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 30 Inches, .058 Gauge, 0.404 Pitch, 89 Drive Links |
| CSB-S1-30-63-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 30 Inches, .063 Gauge, 0.325 Pitch, 111 Drive Links |
| CSB-S1-30-63-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 30 Inches, .063 Gauge, 0.375 Pitch, 98 Drive Links |
| CSB-S1-30-63-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 30 Inches, .063 Gauge, 0.404 Pitch, 89 Drive Links |
| CSB-S1-32-50-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 32 Inches, .050 Gauge, 0.325 Pitch, 119 Drive Links |
| CSB-S1-32-50-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 32 Inches, .050 Gauge, 0.375 Pitch, 105 Drive Links |
| CSB-S1-32-58-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 32 Inches, .058 Gauge, 0.325 Pitch, 119 Drive Links |
| CSB-S1-32-58-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 32 Inches, .058 Gauge, 0.375 Pitch, 105 Drive Links |
| CSB-S1-32-58-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 32 Inches, .058 Gauge, 0.404 Pitch, 95 Drive Links |
| CSB-S1-32-63-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 32 Inches, .063 Gauge, 0.325 Pitch, 119 Drive Links |
| CSB-S1-32-63-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 32 Inches, .063 Gauge, 0.375 Pitch, 105 Drive Links |
| CSB-S1-32-63-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 32 Inches, .063 Gauge, 0.404 Pitch, 95 Drive Links |
| CSB-S1-34-50-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 34 Inches, .050 Gauge, 0.325 Pitch, 125 Drive Links |

| | | |
|---|---|---|
| CSB-S1-34-50-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 34 Inches, .050 Gauge, 0.375 Pitch, 110 Drive Links |
| CSB-S1-34-58-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 34 Inches, .058 Gauge, 0.325 Pitch, 125 Drive Links |
| CSB-S1-34-58-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 34 Inches, .058 Gauge, 0.375 Pitch, 110 Drive Links |
| CSB-S1-34-58-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 34 Inches, .058 Gauge, 0.404 Pitch, 100 Drive Links |
| CSB-S1-34-63-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 34 Inches, .063 Gauge, 0.325 Pitch, 125 Drive Links |
| CSB-S1-34-63-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 34 Inches, .063 Gauge, 0.375 Pitch, 110 Drive Links |
| CSB-S1-34-63-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 34 Inches, .063 Gauge, 0.404 Pitch, 100 Drive Links |
| CSB-S1-36-50-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 36 Inches, .050 Gauge, 0.325 Pitch, 129 Drive Links |
| CSB-S1-36-50-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 36 Inches, .050 Gauge, 0.375 Pitch, 114 Drive Links |
| CSB-S1-36-58-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 36 Inches, .058 Gauge, 0.325 Pitch, 129 Drive Links |
| CSB-S1-36-58-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 36 Inches, .058 Gauge, 0.375 Pitch, 114 Drive Links |
| CSB-S1-36-58-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 36 Inches, .058 Gauge, 0.404 Pitch, 104 Drive Links |
| CSB-S1-36-63-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 36 Inches, .063 Gauge, 0.325 Pitch, 129 Drive Links |
| CSB-S1-36-63-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 36 Inches, .063 Gauge, 0.375 Pitch, 114 Drive Links |
| CSB-S1-36-63-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 36 Inches, .063 Gauge, 0.404 Pitch, 104 Drive Links |
| CSB-S1-41-50-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 41 Inches, .050 Gauge, 0.325 Pitch, 147 Drive Links |
| CSB-S1-41-50-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 41 Inches, .050 Gauge, 0.375 Pitch, 129 Drive Links |
| CSB-S1-41-58-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 41 Inches, .058 Gauge, 0.325 Pitch, 147 Drive Links |
| CSB-S1-41-58-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 41 Inches, .058 Gauge, 0.375 Pitch, 129 Drive Links |
| CSB-S1-41-58-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 41 Inches, .058 Gauge, 0.404 Pitch, 117 Drive Links |
| CSB-S1-41-63-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 41 Inches, .063 Gauge, 0.325 Pitch, 147 Drive Links |
| CSB-S1-41-63-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 41 Inches, .063 Gauge, 0.375 Pitch, 129 Drive Links |
| CSB-S1-41-63-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 41 Inches, .063 Gauge, 0.404 Pitch, 117 Drive Links |
| CSB-S1-50-50-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 50 Inches, .050 Gauge, 0.325 Pitch, 176 Drive Links |
| CSB-S1-50-50-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 50 Inches, .050 Gauge, 0.375 Pitch, 156 Drive Links |
| CSB-S1-50-58-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 50 Inches, .058 Gauge, 0.325 Pitch, 176 Drive Links |
| CSB-S1-50-58-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 50 Inches, .058 Gauge, 0.375 Pitch, 156 Drive Links |
| CSB-S1-50-58-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 50 Inches, .058 Gauge, 0.404 Pitch, 142 Drive Links |
| CSB-S1-50-63-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 50 Inches, .063 Gauge, 0.325 Pitch, 176 Drive Links |
| CSB-S1-50-63-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 50 Inches, .063 Gauge, 0.375 Pitch, 156 Drive Links |
| CSB-S1-50-63-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 50 Inches, .063 Gauge, 0.404 Pitch, 142 Drive Links |
| CSB-S1-60-50-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 60 Inches, .050 Gauge, 0.325 Pitch, 209 Drive Links |
| CSB-S1-60-50-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 60 Inches, .050 Gauge, 0.375 Pitch, 185 Drive Links |
| CSB-S1-60-58-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 60 Inches, .058 Gauge, 0.325 Pitch, 209 Drive Links |
| CSB-S1-60-58-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 60 Inches, .058 Gauge, 0.375 Pitch, 185 Drive Links |
| CSB-S1-60-58-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 60 Inches, .058 Gauge, 0.404 Pitch, 167 Drive Links |
| CSB-S1-60-63-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 60 Inches, .063 Gauge, 0.325 Pitch, 209 Drive Links |
| CSB-S1-60-63-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 60 Inches, .063 Gauge, 0.375 Pitch, 185 Drive Links |
| CSB-S1-60-63-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S1 Mount, 60 Inches, .063 Gauge, 0.404 Pitch, 167 Drive Links |
| CSB-S2-16-50-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 16 Inches, .050 Gauge, 0.325 Pitch, 74 Drive Links |
| CSB-S2-16-50-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 16 Inches, .050 Gauge, 0.375 Pitch, 66 Drive Links |
| CSB-S2-16-58-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 16 Inches, .058 Gauge, 0.325 Pitch, 74 Drive Links |
| CSB-S2-16-58-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 16 Inches, .058 Gauge, 0.375 Pitch, 66 Drive Links |
| CSB-S2-16-58-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 16 Inches, .058 Gauge, 0.404 Pitch, 59 Drive Links |
| CSB-S2-16-63-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 16 Inches, .063 Gauge, 0.325 Pitch, 74 Drive Links |
| CSB-S2-16-63-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 16 Inches, .063 Gauge, 0.375 Pitch, 66 Drive Links |
| CSB-S2-16-63-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 16 Inches, .063 Gauge, 0.404 Pitch, 59 Drive Links |
| CSB-S2-18-50-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 18 Inches, .050 Gauge, 0.325 Pitch, 80 Drive Links |
| CSB-S2-18-50-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 18 Inches, .050 Gauge, 0.375 Pitch, 72 Drive Links |
| CSB-S2-18-58-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 18 Inches, .058 Gauge, 0.325 Pitch, 80 Drive Links |
| CSB-S2-18-58-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 18 Inches, .058 Gauge, 0.375 Pitch, 72 Drive Links |
| CSB-S2-18-58-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 18 Inches, .058 Gauge, 0.404 Pitch, 64 Drive Links |
| CSB-S2-18-63-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 18 Inches, .063 Gauge, 0.325 Pitch, 80 Drive Links |
| CSB-S2-18-63-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 18 Inches, .063 Gauge, 0.375 Pitch, 72 Drive Links |
| CSB-S2-18-63-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 18 Inches, .063 Gauge, 0.404 Pitch, 64 Drive Links |
| CSB-S2-21-50-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 21 Inches, .050 Gauge, 0.325 Pitch, 85 Drive Links |
| CSB-S2-21-50-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 21 Inches, .050 Gauge, 0.375 Pitch, 75 Drive Links |
| CSB-S2-21-58-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 21 Inches, .058 Gauge, 0.325 Pitch, 85 Drive Links |
| CSB-S2-21-58-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 21 Inches, .058 Gauge, 0.375 Pitch, 75 Drive Links |
| CSB-S2-21-58-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 21 Inches, .058 Gauge, 0.404 Pitch, 68 Drive Links |
| CSB-S2-21-63-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 21 Inches, .063 Gauge, 0.325 Pitch, 85 Drive Links |
| CSB-S2-21-63-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 21 Inches, .063 Gauge, 0.375 Pitch, 75 Drive Links |
| CSB-S2-21-63-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 21 Inches, .063 Gauge, 0.404 Pitch, 68 Drive Links |
| CSB-S2-25-50-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 25 Inches, .050 Gauge, 0.325 Pitch, 100 Drive Links |
| CSB-S2-25-50-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 25 Inches, .050 Gauge, 0.375 Pitch, 89 Drive Links |
| CSB-S2-25-58-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 25 Inches, .058 Gauge, 0.325 Pitch, 100 Drive Links |
| CSB-S2-25-58-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 25 Inches, .058 Gauge, 0.375 Pitch, 89 Drive Links |
| CSB-S2-25-58-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 25 Inches, .058 Gauge, 0.404 Pitch, 80 Drive Links |
| CSB-S2-25-63-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 25 Inches, .063 Gauge, 0.325 Pitch, 100 Drive Links |
| CSB-S2-25-63-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 25 Inches, .063 Gauge, 0.375 Pitch, 89 Drive Links |
| CSB-S2-25-63-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 25 Inches, .063 Gauge, 0.404 Pitch, 80 Drive Links |
| CSB-S2-29-50-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 29 Inches, .050 Gauge, 0.325 Pitch, 115 Drive Links |
| CSB-S2-29-50-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 29 Inches, .050 Gauge, 0.375 Pitch, 102 Drive Links |
| CSB-S2-29-58-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 29 Inches, .058 Gauge, 0.325 Pitch, 115 Drive Links |
| CSB-S2-29-58-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 29 Inches, .058 Gauge, 0.375 Pitch, 102 Drive Links |
| CSB-S2-29-58-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 29 Inches, .058 Gauge, 0.404 Pitch, 92 Drive Links |
| CSB-S2-29-63-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 29 Inches, .063 Gauge, 0.325 Pitch, 115 Drive Links |
| CSB-S2-29-63-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 29 Inches, .063 Gauge, 0.375 Pitch, 102 Drive Links |
| CSB-S2-29-63-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 29 Inches, .063 Gauge, 0.404 Pitch, 92 Drive Links |
| CSB-S2-32-50-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 32 Inches, .050 Gauge, 0.325 Pitch, 119 Drive Links |
| CSB-S2-32-50-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 32 Inches, .050 Gauge, 0.375 Pitch, 105 Drive Links |
| CSB-S2-32-58-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 32 Inches, .058 Gauge, 0.325 Pitch, 119 Drive Links |
| CSB-S2-32-58-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 32 Inches, .058 Gauge, 0.375 Pitch, 105 Drive Links |
| CSB-S2-32-58-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 32 Inches, .058 Gauge, 0.404 Pitch, 95 Drive Links |
| CSB-S2-32-63-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 32 Inches, .063 Gauge, 0.325 Pitch, 119 Drive Links |
| CSB-S2-32-63-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 32 Inches, .063 Gauge, 0.375 Pitch, 105 Drive Links |
| CSB-S2-32-63-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 32 Inches, .063 Gauge, 0.404 Pitch, 95 Drive Links |
| CSB-S2-33-50-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 33 Inches, .050 Gauge, 0.325 Pitch, 124 Drive Links |
| CSB-S2-33-50-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 33 Inches, .050 Gauge, 0.375 Pitch, 110 Drive Links |
| CSB-S2-33-58-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 33 Inches, .058 Gauge, 0.325 Pitch, 124 Drive Links |
| CSB-S2-33-58-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 33 Inches, .058 Gauge, 0.375 Pitch, 110 Drive Links |
| CSB-S2-33-58-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 33 Inches, .058 Gauge, 0.404 Pitch, 99 Drive Links |
| CSB-S2-33-63-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 33 Inches, .063 Gauge, 0.325 Pitch, 124 Drive Links |
| CSB-S2-33-63-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 33 Inches, .063 Gauge, 0.375 Pitch, 110 Drive Links |
| CSB-S2-33-63-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 33 Inches, .063 Gauge, 0.404 Pitch, 99 Drive Links |
| CSB-S2-36-50-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 36 Inches, .050 Gauge, 0.325 Pitch, 115 Drive Links |
| CSB-S2-36-50-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 36 Inches, .050 Gauge, 0.375 Pitch, 123 Drive Links |
| CSB-S2-36-58-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 36 Inches, .058 Gauge, 0.325 Pitch, 115 Drive Links |
| CSB-S2-36-58-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 36 Inches, .058 Gauge, 0.375 Pitch, 123 Drive Links |
| CSB-S2-36-58-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 36 Inches, .058 Gauge, 0.404 Pitch, 111 Drive Links |
| CSB-S2-36-63-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 36 Inches, .063 Gauge, 0.325 Pitch, 115 Drive Links |
| CSB-S2-36-63-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 36 Inches, .063 Gauge, 0.375 Pitch, 123 Drive Links |
| CSB-S2-36-63-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 36 Inches, .063 Gauge, 0.404 Pitch, 111 Drive Links |
| CSB-S2-41-50-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 41 Inches, .050 Gauge, 0.325 Pitch, 153 Drive Links |
| CSB-S2-41-50-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 41 Inches, .050 Gauge, 0.375 Pitch, 135 Drive Links |
| CSB-S2-41-58-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 41 Inches, .058 Gauge, 0.325 Pitch, 153 Drive Links |
| CSB-S2-41-58-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 41 Inches, .058 Gauge, 0.375 Pitch, 135 Drive Links |
| CSB-S2-41-58-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 41 Inches, .058 Gauge, 0.404 Pitch, 122 Drive Links |
| CSB-S2-41-63-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 41 Inches, .063 Gauge, 0.325 Pitch, 153 Drive Links |
| CSB-S2-41-63-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 41 Inches, .063 Gauge, 0.375 Pitch, 135 Drive Links |
| CSB-S2-41-63-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 41 Inches, .063 Gauge, 0.404 Pitch, 122 Drive Links |
| CSB-S2-50-50-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 50 Inches, .050 Gauge, 0.325 Pitch, 178 Drive Links |
| CSB-S2-50-50-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 50 Inches, .050 Gauge, 0.375 Pitch, 157 Drive Links |
| CSB-S2-50-58-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 50 Inches, .058 Gauge, 0.325 Pitch, 178 Drive Links |
| CSB-S2-50-58-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 50 Inches, .058 Gauge, 0.375 Pitch, 157 Drive Links |
| CSB-S2-50-58-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 50 Inches, .058 Gauge, 0.404 Pitch, 142 Drive Links |
| CSB-S2-50-63-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 50 Inches, .063 Gauge, 0.325 Pitch, 178 Drive Links |
| CSB-S2-50-63-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 50 Inches, .063 Gauge, 0.375 Pitch, 157 Drive Links |
| CSB-S2-50-63-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 50 Inches, .063 Gauge, 0.404 Pitch, 142 Drive Links |
| CSB-S2-60-50-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 60 Inches, .050 Gauge, 0.325 Pitch, 215 Drive Links |
| CSB-S2-60-50-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 60 Inches, .050 Gauge, 0.375 Pitch, 190 Drive Links |
| CSB-S2-60-58-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 60 Inches, .058 Gauge, 0.325 Pitch, 215 Drive Links |
| CSB-S2-60-58-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 60 Inches, .058 Gauge, 0.375 Pitch, 190 Drive Links |
| CSB-S2-60-58-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 60 Inches, .058 Gauge, 0.404 Pitch, 172 Drive Links |
| CSB-S2-60-63-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 60 Inches, .063 Gauge, 0.325 Pitch, 215 Drive Links |
| CSB-S2-60-63-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 60 Inches, .063 Gauge, 0.375 Pitch, 190 Drive Links |
| CSB-S2-60-63-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 60 Inches, .063 Gauge, 0.404 Pitch, 172 Drive Links |
| CSB-S2-72-50-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 72 Inches, .050 Gauge, 0.325 Pitch, 246 Drive Links |
| CSB-S2-72-50-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 72 Inches, .050 Gauge, 0.375 Pitch, 217 Drive Links |
| CSB-S2-72-58-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 72 Inches, .058 Gauge, 0.325 Pitch, 246 Drive Links |
| CSB-S2-72-58-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 72 Inches, .058 Gauge, 0.375 Pitch, 217 Drive Links |
| CSB-S2-72-58-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 72 Inches, .058 Gauge, 0.404 Pitch, 196 Drive Links |
| CSB-S2-72-63-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 72 Inches, .063 Gauge, 0.325 Pitch, 246 Drive Links |
| CSB-S2-72-63-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 72 Inches, .063 Gauge, 0.375 Pitch, 217 Drive Links |
| CSB-S2-72-63-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 72 Inches, .063 Gauge, 0.404 Pitch, 196 Drive Links |
| CSB-S2-84-50-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 84 Inches, .050 Gauge, 0.325 Pitch, 282 Drive Links |
| CSB-S2-84-50-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 84 Inches, .050 Gauge, 0.375 Pitch, 249 Drive Links |
| CSB-S2-84-58-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 84 Inches, .058 Gauge, 0.325 Pitch, 282 Drive Links |

| | | | |
|---|---|---|---|
| CSB-S2-84-58-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 84 Inches, .058 Gauge, 0.375 Pitch, 249 Drive Links | |
| CSB-S2-84-58-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 84 Inches, .058 Gauge, 0.404 Pitch, 225 Drive Links | |
| CSB-S2-84-63-2 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 84 Inches, .063 Gauge, 0.325 Pitch, 282 Drive Links | |
| CSB-S2-84-63-3 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 84 Inches, .063 Gauge, 0.375 Pitch, 249 Drive Links | |
| CSB-S2-84-63-4 | CHAINSAW | CANNON SUPERBAR, SPROCKET NOSE, S2 Mount, 84 Inches, .063 Gauge, 0.404 Pitch, 225 Drive Links | |
| CSB-S1-24-50-DL-2 | CHAINSAW | CANNON DURALITE SUPERBAR, SPROCKET NOSE, S1 Mount, 24 Inches, .050 Gauge, 0.325 Pitch, 95 Drive Links | |
| CSB-S1-24-50-DL-3 | CHAINSAW | CANNON DURALITE SUPERBAR, SPROCKET NOSE, S1 Mount, 24 Inches, .050 Gauge, 0.375 Pitch, 84 Drive Links | |
| CSB-S1-24-58-DL-2 | CHAINSAW | CANNON DURALITE SUPERBAR, SPROCKET NOSE, S1 Mount, 24 Inches, .058 Gauge, 0.325 Pitch, 95 Drive Links | |
| CSB-S1-24-58-DL-3 | CHAINSAW | CANNON DURALITE SUPERBAR, SPROCKET NOSE, S1 Mount, 24 Inches, .058 Gauge, 0.375 Pitch, 84 Drive Links | |
| CSB-S1-24-58-DL-4 | CHAINSAW | CANNON DURALITE SUPERBAR, SPROCKET NOSE, S1 Mount, 24 Inches, .058 Gauge, 0.404 Pitch, 76 Drive Links | |
| CSB-S1-24-63-DL-2 | CHAINSAW | CANNON DURALITE SUPERBAR, SPROCKET NOSE, S1 Mount, 24 Inches, .063 Gauge, 0.325 Pitch, 95 Drive Links | |
| CSB-S1-24-63-DL-3 | CHAINSAW | CANNON DURALITE SUPERBAR, SPROCKET NOSE, S1 Mount, 24 Inches, .063 Gauge, 0.375 Pitch, 84 Drive Links | |
| CSB-S1-24-63-DL-4 | CHAINSAW | CANNON DURALITE SUPERBAR, SPROCKET NOSE, S1 Mount, 24 Inches, .063 Gauge, 0.404 Pitch, 76 Drive Links | |
| CSB-S1-28-50-DL-2 | CHAINSAW | CANNON DURALITE SUPERBAR, SPROCKET NOSE, S1 Mount, 28 Inches, .050 Gauge, 0.325 Pitch, 104 Drive Links | |
| CSB-S1-28-50-DL-3 | CHAINSAW | CANNON DURALITE SUPERBAR, SPROCKET NOSE, S1 Mount, 28 Inches, .050 Gauge, 0.375 Pitch, 91 Drive Links | |
| CSB-S1-28-58-DL-2 | CHAINSAW | CANNON DURALITE SUPERBAR, SPROCKET NOSE, S1 Mount, 28 Inches, .058 Gauge, 0.325 Pitch, 104 Drive Links | |
| CSB-S1-28-58-DL-3 | CHAINSAW | CANNON DURALITE SUPERBAR, SPROCKET NOSE, S1 Mount, 28 Inches, .058 Gauge, 0.375 Pitch, 91 Drive Links | |
| CSB-S1-28-58-DL-4 | CHAINSAW | CANNON DURALITE SUPERBAR, SPROCKET NOSE, S1 Mount, 28 Inches, .058 Gauge, 0.404 Pitch, 83 Drive Links | |
| CSB-S1-28-63-DL-2 | CHAINSAW | CANNON DURALITE SUPERBAR, SPROCKET NOSE, S1 Mount, 28 Inches, .063 Gauge, 0.325 Pitch, 104 Drive Links | |
| CSB-S1-28-63-DL-3 | CHAINSAW | CANNON DURALITE SUPERBAR, SPROCKET NOSE, S1 Mount, 28 Inches, .063 Gauge, 0.375 Pitch, 91 Drive Links | |
| CSB-S1-28-63-DL-4 | CHAINSAW | CANNON DURALITE SUPERBAR, SPROCKET NOSE, S1 Mount, 28 Inches, .063 Gauge, 0.404 Pitch, 83 Drive Links | |
| CSB-S1-32-50-DL-2 | CHAINSAW | CANNON DURALITE SUPERBAR, SPROCKET NOSE, S1 Mount, 32 Inches, .050 Gauge, 0.325 Pitch, 119 Drive Links | |
| CSB-S1-32-50-DL-3 | CHAINSAW | CANNON DURALITE SUPERBAR, SPROCKET NOSE, S1 Mount, 32 Inches, .050 Gauge, 0.375 Pitch, 105 Drive Links | |
| CSB-S1-32-58-DL-2 | CHAINSAW | CANNON DURALITE SUPERBAR, SPROCKET NOSE, S1 Mount, 32 Inches, .058 Gauge, 0.325 Pitch, 119 Drive Links | |
| CSB-S1-32-58-DL-3 | CHAINSAW | CANNON DURALITE SUPERBAR, SPROCKET NOSE, S1 Mount, 32 Inches, .058 Gauge, 0.375 Pitch, 105 Drive Links | |
| CSB-S1-32-58-DL-4 | CHAINSAW | CANNON DURALITE SUPERBAR, SPROCKET NOSE, S1 Mount, 32 Inches, .058 Gauge, 0.404 Pitch, 95 Drive Links | |
| CSB-S1-32-63-DL-2 | CHAINSAW | CANNON DURALITE SUPERBAR, SPROCKET NOSE, S1 Mount, 32 Inches, .063 Gauge, 0.325 Pitch, 119 Drive Links | |
| CSB-S1-32-63-DL-3 | CHAINSAW | CANNON DURALITE SUPERBAR, SPROCKET NOSE, S1 Mount, 32 Inches, .063 Gauge, 0.375 Pitch, 105 Drive Links | |
| CSB-S1-32-63-DL-4 | CHAINSAW | CANNON DURALITE SUPERBAR, SPROCKET NOSE, S1 Mount, 32 Inches, .063 Gauge, 0.404 Pitch, 95 Drive Links | |
| CSB-S1-36-50-DL-2 | CHAINSAW | CANNON DURALITE SUPERBAR, SPROCKET NOSE, S1 Mount, 36 Inches, .050 Gauge, 0.325 Pitch, 129 Drive Links | |
| CSB-S1-36-50-DL-3 | CHAINSAW | CANNON DURALITE SUPERBAR, SPROCKET NOSE, S1 Mount, 36 Inches, .050 Gauge, 0.375 Pitch, 114 Drive Links | |
| CSB-S1-36-58-DL-2 | CHAINSAW | CANNON DURALITE SUPERBAR, SPROCKET NOSE, S1 Mount, 36 Inches, .058 Gauge, 0.325 Pitch, 129 Drive Links | |
| CSB-S1-36-58-DL-3 | CHAINSAW | CANNON DURALITE SUPERBAR, SPROCKET NOSE, S1 Mount, 36 Inches, .058 Gauge, 0.375 Pitch, 114 Drive Links | |
| CSB-S1-36-58-DL-4 | CHAINSAW | CANNON DURALITE SUPERBAR, SPROCKET NOSE, S1 Mount, 36 Inches, .058 Gauge, 0.404 Pitch, 104 Drive Links | |
| CSB-S1-36-63-DL-2 | CHAINSAW | CANNON DURALITE SUPERBAR, SPROCKET NOSE, S1 Mount, 36 Inches, .063 Gauge, 0.325 Pitch, 129 Drive Links | |
| CSB-S1-36-63-DL-3 | CHAINSAW | CANNON DURALITE SUPERBAR, SPROCKET NOSE, S1 Mount, 36 Inches, .063 Gauge, 0.375 Pitch, 114 Drive Links | |
| CSB-S1-36-63-DL-4 | CHAINSAW | CANNON DURALITE SUPERBAR, SPROCKET NOSE, S1 Mount, 36 Inches, .063 Gauge, 0.404 Pitch, 104 Drive Links | |
| CSM-C1-12-50-2 | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, C1 Mount, 12 Inches, .050 Gauge, 0.325 Pitch, 52 Drive Links | For use on saws less than 60cc displacement |
| CSM-C1-12-50-3LM | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, C1 Mount, 12 Inches, .050 Gauge, 0.370 Pitch (Low Profile), 46 Drive Links | For use on saws less than 60cc displacement |
| CSM-C1-12-58-2 | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, C1 Mount, 12 Inches, .058 Gauge, 0.325 Pitch, 52 Drive Links | For use on saws less than 60cc displacement |
| CSM-C1-14-50-2 | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, C1 Mount, 14 Inches, .050 Gauge, 0.325 Pitch, 58 Drive Links | For use on saws less than 60cc displacement |
| CSM-C1-14-50-3LM | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, C1 Mount, 14 Inches, .050 Gauge, 0.370 Pitch (Low Profile), 51 Drive Links | For use on saws less than 60cc displacement |
| CSM-C1-14-58-2 | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, C1 Mount, 14 Inches, .058 Gauge, 0.325 Pitch, 58 Drive Links | For use on saws less than 60cc displacement |
| CSM-C1-15-50-2 | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, C1 Mount, 15 Inches, .050 Gauge, 0.325 Pitch, 64 Drive Links | For use on saws less than 60cc displacement |
| CSM-C1-15-50-3LM | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, C1 Mount, 15 Inches, .050 Gauge, 0.370 Pitch (Low Profile), 56 Drive Links | For use on saws less than 60cc displacement |
| CSM-C1-15-58-2 | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, C1 Mount, 15 Inches, .058 Gauge, 0.325 Pitch, 64 Drive Links | For use on saws less than 60cc displacement |
| CSM-C1-16-50-2 | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, C1 Mount, 16 Inches, .050 Gauge, 0.325 Pitch, 69 Drive Links | For use on saws less than 60cc displacement |
| CSM-C1-16-50-3LM | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, C1 Mount, 16 Inches, .050 Gauge, 0.370 Pitch (Low Profile), 61 Drive Links | For use on saws less than 60cc displacement |
| CSM-C1-16-58-2 | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, C1 Mount, 16 Inches, .058 Gauge, 0.325 Pitch, 69 Drive Links | For use on saws less than 60cc displacement |
| CSM-C1-18-50-2 | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, C1 Mount, 18 Inches, .050 Gauge, 0.325 Pitch, 75 Drive Links | For use on saws less than 60cc displacement |
| CSM-C1-18-50-3LM | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, C1 Mount, 18 Inches, .050 Gauge, 0.370 Pitch (Low Profile), 66 Drive Links | For use on saws less than 60cc displacement |
| CSM-C1-18-58-2 | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, C1 Mount, 18 Inches, .058 Gauge, 0.325 Pitch, 75 Drive Links | For use on saws less than 60cc displacement |
| CSM-C1-20-50-2 | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, C1 Mount, 20 Inches, .050 Gauge, 0.325 Pitch, 81 Drive Links | For use on saws less than 60cc displacement |
| CSM-C1-20-50-3LM | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, C1 Mount, 20 Inches, .050 Gauge, 0.370 Pitch (Low Profile), 72 Drive Links | For use on saws less than 60cc displacement |
| CSM-C1-20-58-2 | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, C1 Mount, 20 Inches, .058 Gauge, 0.325 Pitch, 81 Drive Links | For use on saws less than 60cc displacement |
| CSM-C1-24-50-2 | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, C1 Mount, 24 Inches, .050 Gauge, 0.325 Pitch, 90 Drive Links *Approx. Cutting Length 23" | For use on saws less than 60cc displacement |
| CSM-C1-24-50-3LM | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, C1 Mount, 24 Inches, .050 Gauge, 0.370 Pitch (Low Profile), 80 Drive Links *Approx. Cutting Length 23" | For use on saws less than 60cc displacement |
| CSM-C1-24-58-2 | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, C1 Mount, 24 Inches, .058 Gauge, 0.325 Pitch, 90 Drive Links *Approx. Cutting Length 23" | For use on saws less than 60cc displacement |
| CSM-C1-28-50-2 | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, C1 Mount, 28 Inches, .050 Gauge, 0.325 Pitch, 98 Drive Links *Approx. Cutting Length 26" | For use on saws less than 60cc displacement |
| CSM-C1-28-50-3LM | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, C1 Mount, 28 Inches, .050 Gauge, 0.370 Pitch (Low Profile), 86 Drive Links *Approx. Cutting Length 26" | For use on saws less than 60cc displacement |
| CSM-C1-28-58-2 | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, C1 Mount, 28 Inches, .058 Gauge, 0.325 Pitch, 98 Drive Links *Approx. Cutting Length 26" | For use on saws less than 60cc displacement |
| CSM-C1-32-50-2 | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, C1 Mount, 32 Inches, .050 Gauge, 0.325 Pitch, 115 Drive Links *Approx. Cutting Length 31" | For use on saws less than 60cc displacement |
| CSM-C1-32-50-3LM | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, C1 Mount, 32 Inches, .050 Gauge, 0.370 Pitch (Low Profile), 102 Drive Links *Approx. Cutting Length 31" | For use on saws less than 60cc displacement |
| CSM-C1-32-58-2 | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, C1 Mount, 32 Inches, .058 Gauge, 0.325 Pitch, 115 Drive Links *Approx. Cutting Length 31" | For use on saws less than 60cc displacement |
| CSM-H1-16-50-2 | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, H1 Mount, 16 Inches, .050 Gauge, 0.325 Pitch, 69 Drive Links | For use on saws less than 60cc displacement |
| CSM-H1-16-50-3LM | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, H1 Mount, 16 Inches, .050 Gauge, 0.370 Pitch (Low Profile), 61 Drive Links | For use on saws less than 60cc displacement |
| CSM-H1-16-58-2 | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, H1 Mount, 16 Inches, .058 Gauge, 0.325 Pitch, 69 Drive Links | For use on saws less than 60cc displacement |
| CSM-H1-18-50-2 | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, H1 Mount, 18 Inches, .050 Gauge, 0.325 Pitch, 75 Drive Links | For use on saws less than 60cc displacement |
| CSM-H1-18-50-3LM | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, H1 Mount, 18 Inches, .050 Gauge, 0.370 Pitch (Low Profile), 66 Drive Links | For use on saws less than 60cc displacement |
| CSM-H1-18-58-2 | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, H1 Mount, 18 Inches, .058 Gauge, 0.325 Pitch, 75 Drive Links | For use on saws less than 60cc displacement |
| CSM-H1-20-50-2 | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, H1 Mount, 20 Inches, .050 Gauge, 0.325 Pitch, 81 Drive Links | For use on saws less than 60cc displacement |
| CSM-H1-20-50-3LM | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, H1 Mount, 20 Inches, .050 Gauge, 0.370 Pitch (Low Profile), 72 Drive Links | For use on saws less than 60cc displacement |
| CSM-H1-20-58-2 | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, H1 Mount, 20 Inches, .058 Gauge, 0.325 Pitch, 81 Drive Links | For use on saws less than 60cc displacement |
| CSM-H1-24-50-2 | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, H1 Mount, 24 Inches, .050 Gauge, 0.325 Pitch, 90 Drive Links *Approx. Cutting Length 22" | For use on saws less than 60cc displacement |
| CSM-H1-24-50-3LM | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, H1 Mount, 24 Inches, .050 Gauge, 0.370 Pitch (Low Profile), 80 Drive Links *Approx. Cutting Length 22" | For use on saws less than 60cc displacement |
| CSM-H1-24-58-2 | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, H1 Mount, 24 Inches, .058 Gauge, 0.325 Pitch, 90 Drive Links *Approx. Cutting Length 22" | For use on saws less than 60cc displacement |
| CSM-H1-28-50-2 | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, H1 Mount, 28 Inches, .050 Gauge, 0.325 Pitch, 99 Drive Links *Approx. Cutting Length 25" | For use on saws less than 60cc displacement |
| CSM-H1-28-50-3LM | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, H1 Mount, 28 Inches, .050 Gauge, 0.370 Pitch (Low Profile), 88 Drive Links *Approx. Cutting Length 25" | For use on saws less than 60cc displacement |
| CSM-H1-28-58-2 | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, H1 Mount, 28 Inches, .058 Gauge, 0.325 Pitch, 99 Drive Links *Approx. Cutting Length 25" | For use on saws less than 60cc displacement |
| CSM-H1-32-50-2 | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, H1 Mount, 32 Inches, .050 Gauge, 0.325 Pitch, 114 Drive Links *Approx. Cutting Length 30" | For use on saws less than 60cc displacement |
| CSM-H1-32-50-3LM | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, H1 Mount, 32 Inches, .050 Gauge, 0.370 Pitch (Low Profile), 100 Drive Links *Approx. Cutting Length 30" | For use on saws less than 60cc displacement |
| CSM-H1-32-58-2 | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, H1 Mount, 32 Inches, .058 Gauge, 0.325 Pitch, 114 Drive Links *Approx. Cutting Length 30" | For use on saws less than 60cc displacement |
| CSM-H5-12-50-2 | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, H5 Mount, 12 Inches, .050 Gauge, 0.325 Pitch, 51 Drive Links | For use on saws less than 60cc displacement |
| CSM-H5-12-50-3LM | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, H5 Mount, 12 Inches, .050 Gauge, 0.370 Pitch (Low Profile), 45 Drive Links | For use on saws less than 60cc displacement |
| CSM-H5-12-58-2 | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, H5 Mount, 12 Inches, .058 Gauge, 0.325 Pitch, 51 Drive Links | For use on saws less than 60cc displacement |
| CSM-H5-13-50-2 | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, H5 Mount, 13 Inches, .050 Gauge, 0.325 Pitch, 56 Drive Links | For use on saws less than 60cc displacement |
| CSM-H5-13-50-3LM | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, H5 Mount, 13 Inches, .050 Gauge, 0.370 Pitch (Low Profile), 49 Drive Links | For use on saws less than 60cc displacement |
| CSM-H5-13-58-2 | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, H5 Mount, 13 Inches, .058 Gauge, 0.325 Pitch, 56 Drive Links | For use on saws less than 60cc displacement |
| CSM-H5-15-50-2 | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, H5 Mount, 15 Inches, .050 Gauge, 0.325 Pitch, 64 Drive Links | For use on saws less than 60cc displacement |
| CSM-H5-15-50-3LM | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, H5 Mount, 15 Inches, .050 Gauge, 0.370 Pitch (Low Profile), 56 Drive Links | For use on saws less than 60cc displacement |
| CSM-H5-15-58-2 | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, H5 Mount, 15 Inches, .058 Gauge, 0.325 Pitch, 64 Drive Links | For use on saws less than 60cc displacement |
| CSM-H6-16-50-2 | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, H6 Mount, 16 Inches, .050 Gauge, 0.325 Pitch, 66 Drive Links | For use on saws less than 60cc displacement |
| CSM-H6-16-50-3LM | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, H6 Mount, 16 Inches, .050 Gauge, 0.370 Pitch (Low Profile), 58 Drive Links | For use on saws less than 60cc displacement |
| CSM-H6-16-58-2 | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, H6 Mount, 16 Inches, .058 Gauge, 0.325 Pitch, 66 Drive Links | For use on saws less than 60cc displacement |
| CSM-H6-18-50-2 | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, H6 Mount, 18 Inches, .050 Gauge, 0.325 Pitch, 72 Drive Links | For use on saws less than 60cc displacement |
| CSM-H6-18-50-3LM | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, H6 Mount, 18 Inches, .050 Gauge, 0.370 Pitch (Low Profile), 64 Drive Links | For use on saws less than 60cc displacement |
| CSM-H6-18-58-2 | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, H6 Mount, 18 Inches, .058 Gauge, 0.325 Pitch, 72 Drive Links | For use on saws less than 60cc displacement |
| CSM-H6-20-50-2 | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, H6 Mount, 20 Inches, .050 Gauge, 0.325 Pitch, 78 Drive Links | For use on saws less than 60cc displacement |
| CSM-H6-20-50-3LM | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, H6 Mount, 20 Inches, .050 Gauge, 0.370 Pitch (Low Profile), 69 Drive Links | For use on saws less than 60cc displacement |
| CSM-H6-20-58-2 | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, H6 Mount, 20 Inches, .058 Gauge, 0.325 Pitch, 78 Drive Links | For use on saws less than 60cc displacement |
| CSM-H6-24-50-2 | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, H6 Mount, 24 Inches, .050 Gauge, 0.325 Pitch, 95 Drive Links | For use on saws less than 60cc displacement |
| CSM-H6-24-50-3LM | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, H6 Mount, 24 Inches, .050 Gauge, 0.370 Pitch (Low Profile), 84 Drive Links | For use on saws less than 60cc displacement |
| CSM-H6-24-58-2 | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, H6 Mount, 24 Inches, .058 Gauge, 0.325 Pitch, 95 Drive Links | For use on saws less than 60cc displacement |
| CSM-H6-28-50-2 | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, H6 Mount, 28 Inches, .050 Gauge, 0.325 Pitch, 105 Drive Links | For use on saws less than 60cc displacement |
| CSM-H6-28-50-3LM | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, H6 Mount, 28 Inches, .050 Gauge, 0.370 Pitch (Low Profile), 93 Drive Links | For use on saws less than 60cc displacement |
| CSM-H6-28-58-2 | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, H6 Mount, 28 Inches, .058 Gauge, 0.325 Pitch, 105 Drive Links | For use on saws less than 60cc displacement |
| CSM-H6-32-50-2 | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, H6 Mount, 32 Inches, .050 Gauge, 0.325 Pitch, 118 Drive Links | For use on saws less than 60cc displacement |
| CSM-H6-32-50-3LM | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, H6 Mount, 32 Inches, .050 Gauge, 0.370 Pitch (Low Profile), 105 Drive Links | For use on saws less than 60cc displacement |
| CSM-H6-32-58-2 | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, H6 Mount, 32 Inches, .058 Gauge, 0.325 Pitch, 118 Drive Links | For use on saws less than 60cc displacement |
| CSM-S1-15-50-2 | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, S1 Mount, 15 Inches, .050 Gauge, 0.325 Pitch, 64 Drive Links | For use on saws less than 60cc displacement |
| CSM-S1-15-50-3LM | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, S1 Mount, 15 Inches, .050 Gauge, 0.370 Pitch (Low Profile), 56 Drive Links | For use on saws less than 60cc displacement |
| CSM-S1-15-58-2 | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, S1 Mount, 15 Inches, .058 Gauge, 0.325 Pitch, 64 Drive Links | For use on saws less than 60cc displacement |
| CSM-S1-16-50-2 | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, S1 Mount, 16 Inches, .050 Gauge, 0.325 Pitch, 69 Drive Links | For use on saws less than 60cc displacement |
| CSM-S1-16-50-3LM | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, S1 Mount, 16 Inches, .050 Gauge, 0.370 Pitch (Low Profile), 61 Drive Links | For use on saws less than 60cc displacement |
| CSM-S1-16-58-2 | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, S1 Mount, 16 Inches, .058 Gauge, 0.325 Pitch, 69 Drive Links | For use on saws less than 60cc displacement |
| CSM-S1-18-50-2 | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, S1 Mount, 18 Inches, .050 Gauge, 0.325 Pitch, 75 Drive Links | For use on saws less than 60cc displacement |
| CSM-S1-18-50-3LM | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, S1 Mount, 18 Inches, .050 Gauge, 0.370 Pitch (Low Profile), 66 Drive Links | For use on saws less than 60cc displacement |
| CSM-S1-18-58-2 | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, S1 Mount, 18 Inches, .058 Gauge, 0.325 Pitch, 75 Drive Links | For use on saws less than 60cc displacement |
| CSM-S1-20-50-2 | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, S1 Mount, 20 Inches, .050 Gauge, 0.325 Pitch, 81 Drive Links | For use on saws less than 60cc displacement |
| CSM-S1-20-50-3LM | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, S1 Mount, 20 Inches, .050 Gauge, 0.370 Pitch (Low Profile), 72 Drive Links | For use on saws less than 60cc displacement |
| CSM-S1-20-58-2 | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, S1 Mount, 20 Inches, .058 Gauge, 0.325 Pitch, 81 Drive Links | For use on saws less than 60cc displacement |
| CSM-S1-24-50-2 | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, S1 Mount, 24 Inches, .050 Gauge, 0.325 Pitch, 91 Drive Links *Approx. Cutting Length 22" | For use on saws less than 60cc displacement |
| CSM-S1-24-50-3LM | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, S1 Mount, 24 Inches, .050 Gauge, 0.370 Pitch (Low Profile), 80 Drive Links *Approx. Cutting Length 22" | For use on saws less than 60cc displacement |
| CSM-S1-24-58-2 | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, S1 Mount, 24 Inches, .058 Gauge, 0.325 Pitch, 91 Drive Links *Approx. Cutting Length 22" | For use on saws less than 60cc displacement |
| CSM-S1-28-50-2 | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, S1 Mount, 28 Inches, .050 Gauge, 0.325 Pitch, 98 Drive Links *Approx. Cutting Length 25" | For use on saws less than 60cc displacement |
| CSM-S1-28-50-3LM | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, S1 Mount, 28 Inches, .050 Gauge, 0.370 Pitch (Low Profile), 86 Drive Links *Approx. Cutting Length 25" | For use on saws less than 60cc displacement |
| CSM-S1-28-58-2 | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, S1 Mount, 28 Inches, .058 Gauge, 0.325 Pitch, 98 Drive Links *Approx. Cutting Length 25" | For use on saws less than 60cc displacement |
| CSM-S1-32-50-2 | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, S1 Mount, 32 Inches, .050 Gauge, 0.325 Pitch, 115 Drive Links *Approx. Cutting Length 30" | For use on saws less than 60cc displacement |
| CSM-S1-32-50-3LM | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, S1 Mount, 32 Inches, .050 Gauge, 0.370 Pitch (Low Profile), 102 Drive Links *Approx. Cutting Length 30" | For use on saws less than 60cc displacement |
| CSM-S1-32-58-2 | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, S1 Mount, 32 Inches, .058 Gauge, 0.325 Pitch, 115 Drive Links *Approx. Cutting Length 30" | For use on saws less than 60cc displacement |
| CSM-S5-12-50-2 | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, S5 Mount, 12 Inches, .050 Gauge, 0.325 Pitch, 50 Drive Links | For use on saws less than 60cc displacement |
| CSM-S5-12-50-3LM | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, S5 Mount, 12 Inches, .050 Gauge, 0.370 Pitch (Low Profile), 44 Drive Links | For use on saws less than 60cc displacement |
| CSM-S5-12-58-2 | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, S5 Mount, 12 Inches, .058 Gauge, 0.325 Pitch, 50 Drive Links | For use on saws less than 60cc displacement |
| CSM-S5-14-50-2 | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, S5 Mount, 14 Inches, .050 Gauge, 0.325 Pitch, 57 Drive Links | For use on saws less than 60cc displacement |
| CSM-S5-14-50-3LM | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, S5 Mount, 14 Inches, .050 Gauge, 0.370 Pitch (Low Profile), 50 Drive Links | For use on saws less than 60cc displacement |
| CSM-S5-14-58-2 | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, S5 Mount, 14 Inches, .058 Gauge, 0.325 Pitch, 57 Drive Links | For use on saws less than 60cc displacement |
| CSM-S5-16-50-2 | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, S5 Mount, 16 Inches, .050 Gauge, 0.325 Pitch, 62 Drive Links | For use on saws less than 60cc displacement |
| CSM-S5-16-50-3LM | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, S5 Mount, 16 Inches, .050 Gauge, 0.370 Pitch (Low Profile), 55 Drive Links | For use on saws less than 60cc displacement |
| CSM-S5-16-58-2 | CHAINSAW | CANNON SUPERMINI BAR, NARROW KERF, S5 Mount, 16 Inches, .058 Gauge, 0.325 Pitch, 62 Drive Links | For use on saws less than 60cc displacement |

| | | | |
|---|---|---|---|
| CHA-A1-21-58-4 | HARVESTER | CANNON HARVESTER BAR, A1 Mount, 21 Inches, .058 Gauge, 0.404 Pitch, 65 Drive Links | 54 CM |
| CHA-A1-21-63-4 | HARVESTER | CANNON HARVESTER BAR, A1 Mount, 21 Inches, .063 Gauge, 0.404 Pitch, 65 Drive Links | 54 CM |
| CHA-A1-21-80-4 | HARVESTER | CANNON HARVESTER BAR, A1 Mount, 21 Inches, .080 Gauge, 0.404 Pitch, 65 Drive Links | 54 CM |
| CHA-A1-23-63-4 | HARVESTER | CANNON HARVESTER BAR, A1 Mount, 23 Inches, .063 Gauge, 0.404 Pitch, 70 Drive Links | 59 CM |
| CHA-A1-23-80-4 | HARVESTER | CANNON HARVESTER BAR, A1 Mount, 23 Inches, .080 Gauge, 0.404 Pitch, 70 Drive Links | 59 CM |
| CHA-A1-25-63-4 | HARVESTER | CANNON HARVESTER BAR, A1 Mount, 25 Inches, .063 Gauge, 0.404 Pitch, 74 Drive Links | 64 CM |
| CHA-A1-25-80-4 | HARVESTER | CANNON HARVESTER BAR, A1 Mount, 25 Inches, .080 Gauge, 0.404 Pitch, 74 Drive Links | 64 CM |
| CHA-A1-27-80-4 | HARVESTER | CANNON HARVESTER BAR, A1 Mount, 27 Inches, .080 Gauge, 0.404 Pitch, 80 Drive Links | 68 CM |
| CHA-A1-28-80-4 | HARVESTER | CANNON HARVESTER BAR, A1 Mount, 28 Inches, .080 Gauge, 0.404 Pitch, 82 Drive Links | 71 CM |
| CHA-A1-29-63-4 | HARVESTER | CANNON HARVESTER BAR, A1 Mount, 29 Inches, .063 Gauge, 0.404 Pitch, 87 Drive Links | 75 CM |
| CHA-A1-29-80-4 | HARVESTER | CANNON HARVESTER BAR, A1 Mount, 29 Inches, .080 Gauge, 0.404 Pitch, 87 Drive Links | 75 CM |
| CHA-A1-31-63-4 | HARVESTER | CANNON HARVESTER BAR, A1 Mount, 31 Inches, .063 Gauge, 0.404 Pitch, 93 Drive Links | 80 CM |
| CHA-A1-31-80-4 | HARVESTER | CANNON HARVESTER BAR, A1 Mount, 31 Inches, .080 Gauge, 0.404 Pitch, 93 Drive Links | 80 CM |
| CHA-A1-36-80-4 | HARVESTER | CANNON HARVESTER BAR, A1 Mount, 36 Inches, .080 Gauge, 0.404 Pitch, 101 Drive Links | 90 CM |
| CHA-A1-39-80-4 | HARVESTER | CANNON HARVESTER BAR, A1 Mount, 39 Inches, .080 Gauge, 0.404 Pitch, 110 Drive Links | 100 CM |
| CHA-A1-46-80-4 | HARVESTER | CANNON HARVESTER BAR, A1 Mount, 46 Inches, .080 Gauge, 0.404 Pitch, Check Owners Manual for Drive Links | 117 CM |
| CHA-F1-29-80-4 | HARVESTER | CANNON HARVESTER BAR, F1 Mount, 29 Inches, .080 Gauge, 0.404 Pitch, 87 Drive Links | 75 CM |
| CHA-F1-32-80-4 | HARVESTER | CANNON HARVESTER BAR, F1 Mount, 32 Inches, .080 Gauge, 0.404 Pitch, Check Owners Manual for Drive Links | 82 CM |
| CHA-F1-36-80-4 | HARVESTER | CANNON HARVESTER BAR, F1 Mount, 36 Inches, .080 Gauge, 0.404 Pitch, Check Owners Manual for Drive Links | 90 CM |
| CHA-F2-29-80-4 | HARVESTER | CANNON HARVESTER BAR, F2 Mount, 29 Inches, .080 Gauge, 0.404 Pitch, 86 Drive Links | 75 CM |
| CHA-F2-32-80-4 | HARVESTER | CANNON HARVESTER BAR, F2 Mount, 32 Inches, .080 Gauge, 0.404 Pitch, Check Owners Manual for Drive Links | 82 CM |
| CHA-F4-24-80-4 | HARVESTER | CANNON HARVESTER BAR, F4 Mount, 24 Inches, .080 Gauge, 0.404 Pitch, Check Owners Manual for Drive Links | 60 CM |
| CHA-F4-26-80-4 | HARVESTER | CANNON HARVESTER BAR, F4 Mount, 26 Inches, .080 Gauge, 0.404 Pitch, Check Owners Manual for Drive Links | 67 CM |
| CHA-N1-25-80-4 | HARVESTER | CANNON HARVESTER BAR, N1 Mount, 25 Inches, .080 Gauge, 0.404 Pitch, 74 Drive Links | 64 CM |
| CHA-N1-29-63-4 | HARVESTER | CANNON HARVESTER BAR, N1 Mount, 29 Inches, .063 Gauge, 0.404 Pitch, 87 Drive Links | 75 CM |
| CHA-N1-29-80-4 | HARVESTER | CANNON HARVESTER BAR, N1 Mount, 29 Inches, .080 Gauge, 0.404 Pitch, 87 Drive Links | 75 CM |
| CHA-N1-31-63-4 | HARVESTER | CANNON HARVESTER BAR, N1 Mount, 31 Inches, .063 Gauge, 0.404 Pitch, Check Owners Manual for Drive Links | 80 CM |
| CHA-N1-31-80-4 | HARVESTER | CANNON HARVESTER BAR, N1 Mount, 31 Inches, .080 Gauge, 0.404 Pitch, Check Owners Manual for Drive Links | 80 CM |
| CHA-N1-55-80-4 | HARVESTER | CANNON HARVESTER BAR, N1 Mount, 55 Inches, .080 Gauge, 0.404 Pitch, Check Owners Manual for Drive Links | 140 CM |
| CHV-A5-30-12-5 | HARVESTER | CANNON HARVESTER BAR, A5 Mount, 30 Inches, .122 Gauge, 0.750 Pitch, 48 Drive Links | |
| CHV-A5-32-12-5 | HARVESTER | CANNON HARVESTER BAR, A5 Mount, 32 Inches, .122 Gauge, 0.750 Pitch, 52 Drive Links | |
| CHV-A5-34-12-5 | HARVESTER | CANNON HARVESTER BAR, A5 Mount, 34 Inches, .122 Gauge, 0.750 Pitch, 54 Drive Links | |
| CHV-A5-36-12-5 | HARVESTER | CANNON HARVESTER BAR, A5 Mount, 36 Inches, .122 Gauge, 0.750 Pitch, 56/57 Drive Links | |
| CHV-A5-38-12-5 | HARVESTER | CANNON HARVESTER BAR, A5 Mount, 38 Inches, .122 Gauge, 0.750 Pitch, 59/60 Drive Links | |
| CHV-A5-40-12-5 | HARVESTER | CANNON HARVESTER BAR, A5 Mount, 40 Inches, .122 Gauge, 0.750 Pitch, 62 Drive Links | |
| CHV-A5-43-12-5 | HARVESTER | CANNON HARVESTER BAR, A5 Mount, 43 Inches, .122 Gauge, 0.750 Pitch, 67 Drive Links | |
| CHV-F8-32-12-5 | HARVESTER | CANNON HARVESTER BAR, F8 Mount, 32 Inches, .122 Gauge, 0.750 Pitch, 51 Drive Links | |
| CHV-F9-33-12-5 | HARVESTER | CANNON HARVESTER BAR, F9 Mount, 32 Inches, .122 Gauge, 0.750 Pitch, Check Owners Manual for Drive Links | |
| CHV-J1-40-12-5 | HARVESTER | CANNON HARVESTER BAR, J1 Mount, 40 Inches, .122 Gauge, 0.750 Pitch, 60 Drive Links | |
| CHV-J1-43-12-5 | HARVESTER | CANNON HARVESTER BAR, J1 Mount, 43 Inches, .122 Gauge, 0.750 Pitch, 67 Drive Links | |
| CHV-J3-28-12-5 | HARVESTER | CANNON HARVESTER BAR, J3 Mount, 28 Inches, .122 Gauge, 0.750 Pitch, 45 Drive Links | |
| CHV-K5-34-12-5 | HARVESTER | CANNON HARVESTER BAR, K5 Mount, 34 Inches, .122 Gauge, 0.750 Pitch, 54 Drive Links | |
| CHV-K5-36-12-5 | HARVESTER | CANNON HARVESTER BAR, K5 Mount, 36 Inches, .122 Gauge, 0.750 Pitch, 56/57 Drive Links | |
| CHV-K5-38-12-5 | HARVESTER | CANNON HARVESTER BAR, K5 Mount, 38 Inches, .122 Gauge, 0.750 Pitch, 59/60 Drive Links | |
| CHV-K5-43-12-5 | HARVESTER | CANNON HARVESTER BAR, K5 Mount, 43 Inches, .122 Gauge, 0.750 Pitch, 66 Drive Links | |
| CHV-K7-34-12-5 | HARVESTER | CANNON HARVESTER BAR, K7 Mount, 34 Inches, .122 Gauge, 0.750 Pitch, 54 Drive Links | |
| CHV-K7-36-12-5 | HARVESTER | CANNON HARVESTER BAR, K7 Mount, 36 Inches, .122 Gauge, 0.750 Pitch, 56/57 Drive Links | |
| CHV-K7-38-12-5 | HARVESTER | CANNON HARVESTER BAR, K7 Mount, 38 Inches, .122 Gauge, 0.750 Pitch, 59/60 Drive Links | |
| CHV-K7-40-12-5 | HARVESTER | CANNON HARVESTER BAR, K7 Mount, 40 Inches, .122 Gauge, 0.750 Pitch, 63 Drive Links | |
| CHV-K7-41-12-5 | HARVESTER | CANNON HARVESTER BAR, K7 Mount, 41 Inches, .122 Gauge, 0.750 Pitch, 65 Drive Links | |
| CHV-K7-43-12-5 | HARVESTER | CANNON HARVESTER BAR, K7 Mount, 43 Inches, .122 Gauge, 0.750 Pitch, 67 Drive Links | |
| CHV-K7-45-12-5 | HARVESTER | CANNON HARVESTER BAR, K7 Mount, 45 Inches, .122 Gauge, 0.750 Pitch, 67 Drive Links | |
| CHV-K7-51-12-5 | HARVESTER | CANNON HARVESTER BAR, K7 Mount, 51 Inches, .122 Gauge, 0.750 Pitch, Check Owners Manual for Drive Links | |
| CHV-K7-55-12-5 | HARVESTER | CANNON HARVESTER BAR, K7 Mount, 55 Inches, .122 Gauge, 0.750 Pitch, 80 Drive Links | |
| CHV-K7-60-12-5 | HARVESTER | CANNON HARVESTER BAR, K7 Mount, 60 Inches, .122 Gauge, 0.750 Pitch, Check Owners Manual for Drive Links | |
| CHV-K7-72-12-5 | HARVESTER | CANNON HARVESTER BAR, K7 Mount, 72 Inches, .122 Gauge, 0.750 Pitch, Check Owners Manual for Drive Links | |
| CHV-K8-45-12-5 | HARVESTER | CANNON HARVESTER BAR, K8 Mount, 45 Inches, .122 Gauge, 0.750 Pitch, 67 Drive Links | |
| CHV-K9-28-12-5 | HARVESTER | CANNON HARVESTER BAR, K9 Mount, 28 Inches, .122 Gauge, 0.750 Pitch, 45 Drive Links | |
| CHV-K9-31-12-5 | HARVESTER | CANNON HARVESTER BAR, K9 Mount, 31 Inches, .122 Gauge, 0.750 Pitch, 49 Drive Links | |
| CHV-N3-43-12-5 | HARVESTER | CANNON HARVESTER BAR, N3 Mount, 43 Inches, .122 Gauge, 0.750 Pitch, 65 Drive Links | |
| CHV-N3-49-12-5 | HARVESTER | CANNON HARVESTER BAR, N3 Mount, 49 Inches, .122 Gauge, 0.750 Pitch, Check Owners Manual for Drive Links | |
| CHV-N5-44-12-5 | HARVESTER | CANNON HARVESTER BAR, N5 Mount, 44 Inches, .122 Gauge, 0.750 Pitch, Check Owners Manual for Drive Links | |
| CHV-N7-32-12-5 | HARVESTER | CANNON HARVESTER BAR, N7 Mount, 32 Inches, .122 Gauge, 0.750 Pitch, 51 Drive Links | |
| CHV-N7-35-12-5 | HARVESTER | CANNON HARVESTER BAR, N7 Mount, 35 Inches, .122 Gauge, 0.750 Pitch, 56 Drive Links | |
| CHV-N9-43-12-5 | HARVESTER | CANNON HARVESTER BAR, N9 Mount, 43 Inches, .122 Gauge, 0.750 Pitch, 65 Drive Links | |
| CHV-Q6-28-12-5 | HARVESTER | CANNON HARVESTER BAR, Q6 Mount, 28 Inches, .122 Gauge, 0.750 Pitch, 47 Drive Links | |
| CHV-Q6-31-12-5 | HARVESTER | CANNON HARVESTER BAR, Q6 Mount, 31 Inches, .122 Gauge, 0.750 Pitch, 49 Drive Links | |
| CHV-Q6-36-12-5 | HARVESTER | CANNON HARVESTER BAR, Q6 Mount, 36 Inches, .122 Gauge, 0.750 Pitch, 57 Drive Links | |
| CHV-Q6-43-12-5 | HARVESTER | CANNON HARVESTER BAR, Q6 Mount, 43 Inches, .122 Gauge, 0.750 Pitch, 66 Drive Links | |
| CSL-E1-44-12 | HARVESTER | CANNON HARVESTER SLASHING BAR, DOUBLE ENDED, E1 Mount, 44 Inches, .122 Gauge, 0.750 Pitch, Check Owners Manual for Drive Links | |
| CSL-E1-51-12 | HARVESTER | CANNON HARVESTER SLASHING BAR, DOUBLE ENDED, E1 Mount, 51 Inches, .122 Gauge, 0.750 Pitch, Check Owners Manual for Drive Links | |
| CSL-E1-58-12 | HARVESTER | CANNON HARVESTER SLASHING BAR, DOUBLE ENDED, E1 Mount, 58 Inches, .122 Gauge, 0.750 Pitch, Check Owners Manual for Drive Links | |
| CSL-E4-58-12 | HARVESTER | CANNON HARVESTER SLASHING BAR, DOUBLE ENDED, E4 Mount, 58 Inches, .122 Gauge, 0.750 Pitch, Check Owners Manual for Drive Links | |
| CSL-E5-59-12 | HARVESTER | CANNON HARVESTER SLASHING BAR, DOUBLE ENDED, E5 Mount, 59 Inches, .122 Gauge, 0.750 Pitch, Check Owners Manual for Drive Links | |
| CSL-E9-65-12 | HARVESTER | CANNON HARVESTER SLASHING BAR, DOUBLE ENDED, E9 Mount, 65 Inches, .122 Gauge, 0.750 Pitch, Check Owners Manual for Drive Links | |
| CSL-L4-51-12 | HARVESTER | CANNON HARVESTER SLASHING BAR, DOUBLE ENDED, L4 Mount, 51 Inches, .122 Gauge, 0.750 Pitch, Check Owners Manual for Drive Links | |
| CSL-L4-58-12 | HARVESTER | CANNON HARVESTER SLASHING BAR, DOUBLE ENDED, L4 Mount, 58 Inches, .122 Gauge, 0.750 Pitch, Check Owners Manual for Drive Links | |
| CSL-ST-64-12 | HARVESTER | CANNON HARVESTER SLASHING BAR, DOUBLE ENDED, ST Mount, 64 Inches, .122 Gauge, 0.750 Pitch, Check Owners Manual for Drive Links | |
| CBR-CARVER-A | REPAIR | CANNON CARVING BAR REPAIR LEVEL "A" | .043, .050 AND .058 GAUGE, ANY LENGTH, WELDING NOT REQUIRED |
| CBR-CARVER-B | REPAIR | CANNON CARVING BAR REPAIR LEVEL "B" | .043, .050 AND .058 GAUGE, ANY LENGTH, WELDING REQUIRED |
| CBR-CBV-A | REPAIR | CANNON BEAVER BAR REPAIR LEVEL "A" | .063 AND .080 GAUGE, ANY LENGTH |
| CBR-CBV-A-3 | REPAIR | CANNON BEAVER BAR REPAIR LEVEL "A", WITH NEW STIHL .375 PITCH TIP | .063 AND .080 GAUGE, ANY LENGTH |
| CBR-CBV-A-4 | REPAIR | CANNON BEAVER BAR REPAIR LEVEL "A", WITH NEW STIHL .404 PITCH TIP | .063 AND .080 GAUGE, ANY LENGTH |
| CBR-CCP-A | REPAIR | CANNON COMPETITION BAR REPAIR LEVEL "A" | .050, .058 AND .063 GAUGE, ANY LENGTH, WELDING NOT REQUIRED |
| CBR-CCP-A-R | REPAIR | CANNON COMPETITION BAR REPAIR LEVEL "A", WITH NEW CANNON ROLLER NOSE | .050, .058 AND .063 GAUGE, ANY LENGTH, WELDING NOT REQUIRED |
| CBR-CCP-B | REPAIR | CANNON COMPETITION BAR REPAIR LEVEL "B" | .050, .058 AND .063 GAUGE, ANY LENGTH, WELDING REQUIRED |
| CBR-CCP-B-R | REPAIR | CANNON COMPETITION BAR REPAIR LEVEL "B", WITH NEW CANNON ROLLER NOSE | .050, .058 AND .063 GAUGE, ANY LENGTH, WELDING REQUIRED |
| CBR-CHA-A | REPAIR | CANNON .404 PITCH HARVESTER BAR REPAIR LEVEL "A" | .058, .063 OR .080 GAUGE, UP TO 39" IN LENGTH |
| CBR-CHA-A-4 | REPAIR | CANNON .404 PITCH HARVESTER BAR REPAIR LEVEL "A", WITH NEW CANNON TIP | .058, .063 OR .080 GAUGE, UP TO 39" IN LENGTH |
| CBR-CHA-B | REPAIR | CANNON .404 PITCH HARVESTER BAR REPAIR LEVEL "B" | .058, .063 OR .080 GAUGE, 40" AND OVER IN LENGTH |
| CBR-CHA-B-4 | REPAIR | CANNON .404 PITCH HARVESTER BAR REPAIR LEVEL "B", WITH NEW CANNON TIP | .058, .063 OR .080 GAUGE, 40" AND OVER IN LENGTH |
| CBR-CHV-A | REPAIR | CANNON .750 PITCH HARVESTER BAR REPAIR LEVEL "A" | .122 GAUGE, UP TO 45" IN LENGTH, MINOR LEVEL OF DAMAGE |
| CBR-CHV-A-5 | REPAIR | CANNON .750 PITCH HARVESTER BAR REPAIR LEVEL "A", WITH NEW CANNON TIP | .122 GAUGE, UP TO 45" IN LENGTH, MINOR LEVEL OF DAMAGE |
| CBR-CHV-B | REPAIR | CANNON .750 PITCH HARVESTER BAR REPAIR LEVEL "B" | .122 GAUGE, UP TO 45" IN LENGTH, INTERMEDIATE LEVEL OF DAMAGE |
| CBR-CHV-B-5 | REPAIR | CANNON .750 PITCH HARVESTER BAR REPAIR LEVEL "B", WITH NEW CANNON TIP | .122 GAUGE, UP TO 45" IN LENGTH, INTERMEDIATE LEVEL OF DAMAGE |
| CBR-CHV-C | REPAIR | CANNON .750 PITCH HARVESTER BAR REPAIR LEVEL "C" | .122 GAUGE, UP TO 45" IN LENGTH, MAJOR LEVEL OF DAMAGE |
| CBR-CHV-C-5 | REPAIR | CANNON .750 PITCH HARVESTER BAR REPAIR LEVEL "C", WITH NEW CANNON TIP | .122 GAUGE, UP TO 45" IN LENGTH, MAJOR LEVEL OF DAMAGE |
| CBR-CHV-D | REPAIR | CANNON .750 PITCH HARVESTER BAR REPAIR LEVEL "D" | .122 GAUGE, 46" TO 55" IN LENGTH |
| CBR-CHV-D-5 | REPAIR | CANNON .750 PITCH HARVESTER BAR REPAIR LEVEL "D", WITH NEW CANNON TIP | .122 GAUGE, 46" TO 55" IN LENGTH |
| CBR-CHV-E | REPAIR | CANNON .750 PITCH HARVESTER BAR REPAIR LEVEL "E" | .122 GAUGE, 56" TO 124" IN LENGTH |
| CBR-CHV-E-5 | REPAIR | CANNON .750 PITCH HARVESTER BAR REPAIR LEVEL "E", WITH NEW CANNON TIP | .122 GAUGE, 56" TO 124" IN LENGTH |
| CBR-CHV-F | REPAIR | CANNON .750 PITCH HARVESTER BAR REPAIR LEVEL "F" | .122 GAUGE, 125" AND OVER IN LENGTH |
| CBR-CHV-F-5 | REPAIR | CANNON .750 PITCH HARVESTER BAR REPAIR LEVEL "F", WITH NEW CANNON TIP | .122 GAUGE, 125" AND OVER IN LENGTH |
| CBR-CPB-A | REPAIR | CANNON DOUBLE ENDED BAR REPAIR LEVEL "A" | ANY GAUGE, FLAME HARDENING REQUIRED, UP TO 72" IN LENGTH |
| CBR-CPB-B | REPAIR | CANNON DOUBLE ENDED BAR REPAIR LEVEL "B" | ANY GAUGE, FLAME HARDENING REQUIRED, 73" TO 84" IN LENGTH |
| CBR-CPB-C | REPAIR | CANNON DOUBLE ENDED BAR REPAIR LEVEL "C" | ANY GAUGE, FLAME HARDENING REQUIRED, 85" TO 96" IN LENGTH |
| CBR-CPK-A | REPAIR | CANNON DOUBLE ENDED BAR REPAIR LEVEL "A", | ANY GAUGE, FLAME HARDENING NOT REQUIRED, UP TO 72" IN LENGTH, MINOR DAMAGE |
| CBR-CPK-B | REPAIR | CANNON DOUBLE ENDED BAR REPAIR LEVEL "B" | ANY GAUGE, FLAME HARDENING NOT REQUIRED, UP TO 72" IN LENGTH, MAJOR DAMAGE |
| CBR-CPK-C | REPAIR | CANNON DOUBLE ENDED BAR REPAIR LEVEL "C" | ANY GAUGE, FLAME HARDENING NOT REQUIRED, 73" AND OVER IN LENGTH |
| CBR-CPK-D | REPAIR | CANNON DOUBLE ENDED BAR REPAIR LEVEL "D" | ANY GAUGE, FLAME HARDENING NOT REQUIRED, WELDING OF RAILS REQUIRED, ANY LENGTH |
| CBR-CSB-A | REPAIR | CANNON CHAINSAW BAR REPAIR LEVEL "A" | .050, .058 OR .063 GAUGE, UP TO 49" IN LENGTH |
| CBR-CSB-A-2 | REPAIR | CANNON CHAINSAW BAR REPAIR LEVEL "A" WITH NEW .325 PITCH CANNON SUPERBAR TIP | .050, .058 OR .063 GAUGE, UP TO 49" IN LENGTH |
| CBR-CSB-A-3 | REPAIR | CANNON CHAINSAW BAR REPAIR LEVEL "A" WITH NEW .375 PITCH CANNON SUPERBAR TIP | .050, .058 OR .063 GAUGE, UP TO 49" IN LENGTH |
| CBR-CSB-A-4 | REPAIR | CANNON CHAINSAW BAR REPAIR LEVEL "A" WITH NEW .404 PITCH CANNON SUPERBAR TIP | .050, .058 OR .063 GAUGE, UP TO 49" IN LENGTH |
| CBR-CSB-B | REPAIR | CANNON CHAINSAW BAR REPAIR LEVEL "B" | .050, .058 OR .063 GAUGE, 50" AND OVER IN LENGTH |
| CBR-CSB-B-2 | REPAIR | CANNON CHAINSAW BAR REPAIR LEVEL "B" WITH NEW .325 PITCH CANNON SUPERBAR TIP | .050, .058 OR .063 GAUGE, 50" AND OVER IN LENGTH |
| CBR-CSB-B-3 | REPAIR | CANNON CHAINSAW BAR REPAIR LEVEL "B" WITH NEW .375 PITCH CANNON SUPERBAR TIP | .050, .058 OR .063 GAUGE, 50" AND OVER IN LENGTH |
| CBR-CSB-B-4 | REPAIR | CANNON CHAINSAW BAR REPAIR LEVEL "B" WITH NEW .404 PITCH CANNON SUPERBAR TIP | .050, .058 OR .063 GAUGE, 50" AND OVER IN LENGTH |